

Product catalogue



First of all

Thank you for your interest in our products. Please note that you must comply with the corresponding instructions for use when selecting and utilizing the products listed in the catalog. You can access them online using the THM number printed on the label at: www.ifu-tm.com, at www.thommenmedical.com/de/ueber-uns/download-center, or via the Thommen App (available free of charge for iOS and Android devices). Furthermore, we would like to point out that not all items listed in the catalog are available in every country. Of course, your Thommen Medical contact partners in our field sales force and back office teams are on hand to help you.

With the new webshop (available in selected markets), you can order our products intuitively, efficiently and with a good overview. Discover the Thommen Medical webshop at www.shop.thommenmedical.com and take advantage of more benefits.



The product configurator shows the components which Thommen Medical recommend for a restoration. Based on the previous configuration (tooth position, implant diameter, etc.) an article list corresponding with the required treatment method is proposed. This facilitates the selection of products and can be used as an additional and efficient aid along with the catalog. You can find the product configurator at: www.thommenmedical.com or download the App directly in the Apple App Store or Google Play Store.



Content

Surgical PF 3.5–6.0

- 4 SPI®NEVO INICELL® cylindrical-conical implant
- 5 SPI®ELEMENT INICELL® cylindrical implant
- 6 SPI®CONTACT INICELL® conical-cylindrical implant
- 7 SPI®ELEMENT cylindrical implant
- 7 SPI®CONTACT conical-cylindrical implant
- 8 Surgical planning aids
- 9 Drills and depth gauges

Thommen Medical PF 3.0 Implant System

- 11 SPI®ELEMENT INICELL® PF 3.0 implant, VARIOunite abutment PF 3.0 and the related tool set

Soft tissue management

- 14,15 Healing caps and gingiva formers
overview – soft tissue management and temporary restoration

Impression taking/analogs

- 16 Impression taking at implant level
- 18 Scan abutment
- 19 Impression taking at abutment level
- 20 Implant analogs
- 21 Abutment analogs

Biomaterials

Country-specific product information on biomaterials can be found at:
www.thommenmedical.com

Prosthetics

- 22 Prosthetic overview PF 3.5
- 24 Prosthetic overview PF 4.0
- 26 Prosthetic overview PF 4.5
- 28 Prosthetic overview PF 5.0
- 30 Prosthetic overview PF 6.0
- 32 SPI®VARIOtemp for temporary restorations
- 33 Titanium Base for CAD/CAM for cemented and screw-retained restorations
- 34 Dynamic Titanium Base for CAD/CAM for angled screw channels
- 35 Milling abutment for CAD/CAM type II for customized abutments
- 36 SPI®VARIOflex for cemented and screw-retained restorations
- 37 SPI®VARIOmulti for screw-retained restorations
- 41 SPI®VARIO for screw-retained restorations
- 43 SPI®EASY for cemented restorations
- 45 SPI®EASY emergence profile for cemented restorations
- 47 SPI®ART for esthetic restorations, cemented and screw-retained
- 49 SPI®RETAIN for hybrid removable dentures
- 51 ZEST® LOCATOR® implant attachment system

Instruments and accessories

- 54 Instruments for mechanical operation
- 54,55 Instruments for manual operation
- 56 Instruments for guided surgery
- 57 Cassettes
- 58 Explantation instruments

Index

- 59 Index by article numbers
- 66 Alphabetical index
- 73 Torque values
- 74 Symbols



SPI®NEVO INICELL®

cylindrical-conical implant

www.ifu-tm.com/THM61112


PF 3.5

PF 4.0

PF 4.5

PF 5.0


NEVO implant RC INICELL®, incl. healing cap, titanium



Length

	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm
core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	
Apical core Ø	< 2 mm	< 2 mm	< 2 mm	2.0 mm	
6.5 mm			4.23.021	4.23.031	4.23.041
8.0 mm	4.23.012	4.23.022	4.23.032	4.23.042	
9.5 mm	4.23.013	4.23.023	4.23.033	4.23.043	
11.0 mm	4.23.014	4.23.024	4.23.034	4.23.044	
12.5 mm	4.23.015	4.23.025	4.23.035	4.23.045	
14.0 mm	4.23.016	4.23.026	4.23.036	4.23.046	


NEVO implant MC INICELL®, incl. healing cap, titanium



Length

	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm
core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	
Apical core Ø	< 2 mm	< 2 mm	< 2 mm	2.0 mm	
8.0 mm	4.23.812	4.23.822	4.23.832	4.23.842	
9.5 mm	4.23.813	4.23.823	4.23.833	4.23.843	
11.0 mm	4.23.814	4.23.824	4.23.834	4.23.844	
12.5 mm	4.23.815	4.23.825	4.23.835	4.23.845	
14.0 mm	4.23.816	4.23.826	4.23.836	4.23.846	

NEVO implant LC INICELL®, incl. healing cap, titanium



Length

	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm
core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	
Apical core Ø	< 2 mm	< 2 mm	< 2 mm	2.0 mm	
6.5 mm		4.23.771	4.23.781	4.23.791	
8.0 mm	4.23.762	4.23.772	4.23.782	4.23.792	
9.5 mm	4.23.763	4.23.773	4.23.783	4.23.793	
11.0 mm	4.23.764	4.23.774	4.23.784	4.23.794	
12.5 mm	4.23.765	4.23.775	4.23.785	4.23.795	
14.0 mm	4.23.766	4.23.776	4.23.786	4.23.796	



Healing caps for SPI®NEVO INICELL® are included as standard in the delivery (component of the APLIQUIQ).

SPI®ELEMENT INICELL®

cylindrical implant

www.ifu-tm.com/THM61112

PF 3.5

PF 4.0

PF 4.5


PF 5.0

PF 6.0


ELEMENT implant RC INICELL®, incl. healing cap, titanium

Technical drawing of a dental implant showing dimensions: PF (platform feature), 1.0 mm (height), L (length), endosseous Ø (inner diameter), and core Ø (outer diameter).


Length						
	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm	6.0 mm
	core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	5.3 mm
6.5 mm			4.23.121	4.23.131	4.23.141	4.23.151
8.0 mm		4.23.112	4.23.122	4.23.132	4.23.142	4.23.152
9.5 mm		4.23.113	4.23.123	4.23.133	4.23.143	4.23.153
11.0 mm		4.23.114	4.23.124	4.23.134	4.23.144	4.23.154
12.5 mm		4.23.115	4.23.125	4.23.135	4.23.145	4.23.155
14.0 mm		4.23.116	4.23.126	4.23.136	4.23.146	
17.0 mm		4.23.117		4.23.137		



ELEMENT implant MC INICELL®, incl. healing cap, titanium




Length	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm	6.0 mm
	core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	5.3 mm
8.0 mm		4.23.512	4.23.522	4.23.532	4.23.542	4.23.552
9.5 mm		4.23.513	4.23.523	4.23.533	4.23.543	4.23.553
11.0 mm		4.23.514	4.23.524	4.23.534	4.23.544	4.23.554
12.5 mm		4.23.515	4.23.525	4.23.535	4.23.545	4.23.555
14.0 mm		4.23.516	4.23.526	4.23.536	4.23.546	



ELEMENT implant LC INICELL®, incl. healing cap, titanium

Technical drawing of a dental implant showing dimensions: PF (platform feature), 2.5 mm (height of the platform), L (total length), and a threaded section.

Length						
	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm	6.0 mm
	core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	5.3 mm
6.5 mm			4.23.721			
8.0 mm		4.23.712	4.23.722			
9.5 mm		4.23.713	4.23.723			
11.0 mm		4.23.714	4.23.724			
12.5 mm		4.23.715	4.23.725			
14.0 mm		4.23.716	4.23.726			



Healing caps for SPI®ELEMENT INICELL® are included as standard in the delivery (component of the APLIQUIQ).

SPI®CONTACT INICELL®

conical-cylindrical implant

www.ifu-tm.com/THM61112

PF 3.5


PF 4.0

PF 4.5

PF 5.0

PF 6.0


CONTACT implant RC INICELL®, incl. healing cap, titanium



Length

	endosseous Ø	2.7 mm	3.5 mm	3.5 mm	4.2 mm	5.0 mm
core Ø	2.0 mm	2.8 mm	2.8 mm	3.5 mm	4.3 mm	
9.5 mm			4.23.223	4.23.233	4.23.243	4.23.253
11.0 mm	4.23.214	4.23.224	4.23.234	4.23.244	4.23.254	
12.5 mm	4.23.215	4.23.225	4.23.235	4.23.245	4.23.255	
14.0 mm	4.23.216	4.23.226	4.23.236	4.23.246	4.23.256	
17.0 mm			4.23.237	4.23.247		

CONTACT implant MC INICELL®, incl. healing cap, titanium



Length


	endosseous Ø	2.7 mm	3.5 mm	3.5 mm	4.2 mm	5.0 mm
core Ø	2.0 mm	2.8 mm	2.8 mm	3.5 mm	4.3 mm	
11.0 mm			4.23.624	4.23.634	4.23.644	4.23.654
12.5 mm	4.23.615	4.23.625	4.23.635	4.23.645	4.23.655	
14.0 mm	4.23.616	4.23.626	4.23.636	4.23.646	4.23.656	
15.5 mm	4.23.617	4.23.627	4.23.637	4.23.647	4.23.657	



Healing caps for SPI®CONTACT INICELL® are included as standard in the delivery (component of the APLIQUIQ).



reddot design award
winner 2011



SPI®ELEMENT

cylindrical implant

www.ifu-tm.com/THM61113

PF 3.5


PF 4.0

PF 4.5

PF 5.0

PF 6.0

ELEMENT implant, incl. healing cap, titanium



Length


	endosseous Ø	3.5 mm	4.0 mm	4.2 mm	5.0 mm	6.0 mm
core Ø	2.8 mm	3.5 mm	3.5 mm	4.3 mm	5.3 mm	
6.5 mm		4.13.905	4.13.906	4.13.907	4.13.908	
8.0 mm	4.13.900	4.13.904	4.13.901	4.13.902	4.13.903	
9.5 mm	4.13.940	4.13.914	4.13.941	4.13.942	4.13.943	
11.0 mm	4.13.910	4.13.924	4.13.911	4.13.912	4.13.913	
12.5 mm	4.13.950	4.13.934	4.13.951	4.13.952	4.13.953	
14.0 mm	4.13.920	4.13.944	4.13.921	4.13.922		
17.0 mm	4.13.930		4.13.931			

SPI® CONTACT

conical-cylindrical implant

www.ifu-tm.com/THM61113

CONTACT implant, incl. healing cap, titanium



Length

	endosseous Ø	2.7 mm	3.5 mm	3.5 mm	4.2 mm	5.0 mm
core Ø	2.0 mm	2.8 mm	2.8 mm	3.5 mm	4.3 mm	
9.5 mm		4.13.214	4.13.211	4.13.212	4.13.213	
11.0 mm	4.13.220	4.13.224	4.13.221	4.13.222	4.13.223	
12.5 mm	4.13.230	4.13.234	4.13.231	4.13.232	4.13.233	
14.0 mm	4.13.240	4.13.244	4.13.241	4.13.242	4.13.243	
17.0 mm			4.13.261	4.13.262		






The healing caps for SPI®ELEMENT and SPI®CONTACT are included in delivery.


Surgical planning aids

www.ifu-tm.com/THM61141


X-ray template, for planning with two-dimensional x-ray devices



X-ray reference sphere, stainless steel



Guiding sleeve for VECTOdrill™ pilot drill, stainless steel, 4 per pack (Q4)



Instructions for digital planning aids can be found at: www.thommenmedical.com

Drills and depth gauges

www.ifu-tm.com/THM61141

VECTOdrill™ twist drill, single use, sterile packed, stainless steel, 4 per pack (Q4)

		Pilot drill				
Length		Ø 2.0 mm	Ø 2.8 mm	Ø 3.5 mm	Ø 4.3 mm	Ø 5.3 mm
	29.0 mm extra short *	3.03.624 Q4	3.03.625 Q4	3.03.626 Q4	3.03.627 Q4	3.03.628 Q4
	34.0 mm short	3.03.610 Q4	3.03.612 Q4	3.03.614 Q4	3.03.616 Q4	3.03.618 Q4
	40.0 mm long	3.03.611 Q4	3.03.613 Q4	3.03.615 Q4	3.03.617 Q4	

* The VECTOdrill™ twist drills, extra short, can only be used with implants of 6.5–14.0 mm in length.

VECTOdrill™ ceramic twist drill, reusable, ceramic

		Pilot drill				
Length		Ø 2.0 mm	Ø 2.8 mm	Ø 3.5 mm	Ø 4.3 mm	Ø 5.3 mm
	29.0 mm extra short *	3.03.660	3.03.662	3.03.664	3.03.666	3.03.668
	34.0 mm short	3.03.661	3.03.663	3.03.665	3.03.667	3.03.669

* The VECTOdrill™ twist drills, extra short, can only be used with implants of 6.5–14.0 mm in length.

VECTOdrill™ drill, reusable, stainless steel

		Pilot drill				
Length		Ø 2.0 mm	Ø 2.8 mm	Ø 3.5 mm	Ø 4.3 mm	Ø 5.3 mm
	29.0 mm extra short *	3.03.710	3.03.712	3.03.714	3.03.716	3.03.718
	34.0 mm short	3.03.720	3.03.722	3.03.724	3.03.726	3.03.728
	40.0 mm long	3.03.730	3.03.732	3.03.734	3.03.736	

* The VECTOdrill™ twist drills, extra short, can only be used with implants of 6.5–14.0 mm in length.

VECTOdrill™ depth gauge titanium

Length	Ø 2.0 mm	Ø 2.8 mm	Ø 3.5 mm	Ø 4.3 mm	Ø 5.3 mm
 27.5 mm	3.03.630	3.03.632	3.03.634	3.03.636	3.03.638

Drill Ø 1.5 mm, single use, sterile packed, stainless steel, 4 per pack (Q4)

Length	
 34.0 mm short	3.03.690 Q4

Drill Ø 1.5 mm, reusable, stainless steel

Length	
 34.0 mm short	3.03.790

Depth gauge Ø 1.5 mm, shortenable, titanium

Length	
 30.5 mm	3.03.692

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

SPI®NEVO/ELEMENT profile drill, reusable, stainless steel

Length

29.0 mm

extra short

3.03.751

3.03.752

3.03.753

3.03.754

SPI®ELEMENT profile drill, single use, sterile packed, stainless steel, 4 per pack (Q4)

Length

29.0 mm

extra short

3.03.651 Q4

3.03.657 Q4

3.03.653 Q4

3.03.655 Q4

3.03.659 Q4

SPI®CONTACT profile drill, single use, sterile packed, stainless steel, 4 per pack (Q4)

Length

29.0 mm

extra short

3.03.641 Q4

3.03.649 Q4

3.03.643 Q4

3.03.645 Q4

3.03.647 Q4



34.0 mm

short

3.03.640 Q4

3.03.648 Q4

3.03.642 Q4

3.03.644 Q4

3.03.646 Q4

Thread tap, reusable, stainless steel

Length

endosseous Ø

34.0 mm

3.5 mm

4.0 mm

4.2 mm

5.0 mm

6.0 mm

3.03.680

3.03.682

3.03.684

3.03.686

3.03.688

Bone contouring instrument, reusable, stainless steel

Length

29.0 mm

3.03.671

3.03.673

3.03.675

3.03.677

3.03.679

Bone contouring instrument+, reusable, stainless steel

Length

29.0 mm

3.03.670

3.03.672

3.03.674

3.03.676

For the angled VARIOmulti abutment.

Drill extension, stainless steel

Length

External Ø

26.0 mm

3.7 mm

3.03.231

26.0 mm

5.0 mm

3.03.230

Mucosa punch, reusable, stainless steel

Length

27.0 mm

3.03.315

3.03.316


3.03.320

3.03.317


3.03.318

SPI®ELEMENT INICELL® PF 3.0

implant, VARIOunite abutment PF 3.0 and the related tool set,
www.ifu-tm.com/THM61146




Rotation locked
 Rotation unlocked



ELEMENT implant RC INICELL® PF 3.0, incl. healing cap, titanium


Length

	core Ø	2.5 mm
8.0 mm		4.23.102
9.5 mm		4.23.103
11.0 mm		4.23.104
12.5 mm		4.23.105



The healing caps for SPI®ELEMENT INICELL® are included as standard in delivery (component of APLIQUIQ).


Gingiva former for PF 3.0, 4-lobe, titanium



Height

3.2 mm	4.03.538
4.5 mm	4.03.548
7.0 mm	4.03.558

SPI®ELEMENT INICELL® PF 3.0



X-ray template, for planning with two-dimensional x-ray devices

for the ELEMENT implant line

Fo_20d184

VECTOdrill™ pilot drill, reusable, stainless steel



Length	Pilot drill
40.0 mm	long
	Ø 2.0 mm
	3.03.730

VECTOdrill™ pilot drill, single use, sterile packed, stainless steel, 4 per pack unit (Q4)



Length	Pilot drill
40.0 mm	long
	Ø 2.0 mm
	3.03.611 Q4

SPI®ELEMENT profile drill for PF 3.0, single use, sterile packed, stainless steel



For implant lengths	8.0 mm	9.5 mm	11.0 mm	12.5 mm
	3.03.740	3.03.741	3.03.742	3.03.743

-  Rotation locked
 Rotation unlocked

Bone contouring instrument for PF 3.0, reusable, stainless steel



Length
 29.0 mm **3.03.658**

Adapter for hand piece PF 3.0, stainless steel



Length
 28.0 mm **3.03.238**

Adapter for hand piece, one-piece, stainless steel



Length
 24.0 mm **3.03.248**

 VARIOunite abutment PF 3.0 for crown, incl. abutment screw, titanium alloy



Height
 12.0 mm **1.04.138**

 VARIOunite burn-out plastic cap, PF 3.0, POM



Height
 11.8 mm **2.03.848**

Laboratory cylindrical pin, PTFE, 5 per pack (Q5)



Length
 70.0 mm **2.03.450 Q5**

 Impression coping PF 3.0 for open tray technique, reusable, retentive, screw-retained, titanium



External Ø 3.3 mm
 cylindrical, height 16.0 mm **3.04.028**

Screw for impression copings, reusable, 4-lobe, stainless steel



Length
 12.5 mm extra short **3.03.572**



21.5 mm long **3.03.574**



27.5 mm extra long **3.03.580**

 Rotation locked
 Rotation unlocked

 digital




 **Scan abutment**, stainless steel, coated, PF 3.0
 Including screw for scan abutment: The screw is included separately in the scope of delivery.

Height
 10.0 mm **5.03.774**

Exclusive screw
 Height
 10.0 mm **3.03.774**

Selection of appropriate screw length:



 digital



 **Implant analog for CAD/CAM**, titanium, PF 3.0

Length
 11.0 mm **3.03.084**

Implant analogs for CAD/CAM are used for 3D-printed models.

Insertion device for implant analog for CAD/CAM, stainless steel



Length
 35.0 mm **3.03.158**

 **Implant analog PF 3.0**, titanium



Length
 14.0 mm **3.03.098**


Abutment screw, 4-lobe, titanium alloy




Length
 5.8 mm **4.03.500**

Healing caps and gingiva formers


Overview – soft tissue management and temporary restoration



At the abutment level: The temporary caps of the EASY (see page 44, 46, 48) and VARIOmulti (see page 39) abutment lines offer the possibility to fabricate a provisional cap already on the final abutment.



Rotation locked



Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Healing cap SE, titanium, non-sterile

Height

1.0 mm

4.03.515

4.03.519

4.03.516

4.03.517

4.03.518



Gingiva former, titanium, non-sterile

Height

2.0 mm

4.03.520

4.03.524

4.03.521

4.03.522

4.03.523

3.2 mm

4.03.530

4.03.534

4.03.531

4.03.532

4.03.533

4.5 mm

4.03.540

4.03.544

4.03.541

4.03.542

4.03.543

5.7 mm

4.03.560

4.03.564

4.03.561

4.03.562

4.03.563

7.0 mm


4.03.550

4.03.554

4.03.551

4.03.552

4.03.553



Gingiva former narrow, titanium, non-sterile

Height

2.0 mm

4.04.310

4.04.311

4.04.312

4.04.313

4.04.314

3.2 mm

4.04.320

4.04.321

4.04.322

4.04.323

4.04.324

4.5 mm

4.04.330

4.04.331

4.04.332

4.04.333

4.04.334

5.7 mm

4.04.340

4.04.341

4.04.342

4.04.343

4.04.344

7.0 mm


4.04.350

4.04.351

4.04.352

4.04.353

4.04.354



Gingiva former+, titanium, non-sterile

Height

2.0 mm

4.03.525

3.2 mm

4.03.535



Gingiva former, customizable, titanium/PMMA-base, non-sterile

Height

7.5 mm

4.03.570

4.03.571

4.03.572

4.03.573

4.03.574



The abutment screw is included separately in the scope of delivery: 4.03.500 for PF 3.5, 4.03.501 for PF 4.0-6.0

Fabrication screw, 4-lobe, for gingiva former, customizable and VARIOtemp abutment, stainless steel, 4 per pack unit (Q4)

Length

22.5 mm

3.03.590 Q4

23.4 mm

3.03.591 Q4



Abutment screw, 4-lobe, titanium alloy

Length

5.8 mm

4.03.500

7.2 mm

4.03.501


10.2 mm

4.03.502



Impression taking at implant level

www.ifu-tm.com/THM61127



PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Impression coping for closed tray technique, single use, repositionable, screw-retained, aluminum, anodized

Including screw for impression coping, extra short: The screw is included separately in the scope of delivery



Height	External Ø	3.9 mm	5.0 mm	5.5 mm	6.0 mm	7.0 mm
8.0 mm	short	5.03.074	5.03.079	5.03.075	5.03.076	5.03.077



Exclusive screw

8.0 mm	short	3.03.074	3.03.079	3.03.075	3.03.076	3.03.077
--------	-------	-----------------	-----------------	-----------------	-----------------	-----------------

Impression coping for closed tray technique, reusable, repositionable, screw-retained, titanium

Including screw for impression coping, extra short: The screw is included separately in the scope of delivery



Height	External Ø	3.9 mm	5.0 mm	5.5 mm	6.0 mm	7.0 mm
8.0 mm	short	5.04.030	5.04.031	5.04.032	5.04.033	5.04.034



Exclusive screw

8.0 mm	short	3.04.030	3.04.031	3.04.032	3.04.033	3.04.034
--------	-------	-----------------	-----------------	-----------------	-----------------	-----------------

Impression coping for closed tray technique, single use, repositionable, screw-retained, aluminum, anodized

Including screw for impression coping, short: The screw is included separately in the scope of delivery



Height	External Ø	3.9 mm	5.0 mm	5.5 mm	6.0 mm	7.0 mm
12.0 mm	long	5.03.014	5.03.019	5.03.015	5.03.016	5.03.017



Exclusive screw

12.0 mm	long	3.03.014	3.03.019	3.03.015	3.03.016	3.03.017
---------	------	-----------------	-----------------	-----------------	-----------------	-----------------

Impression coping for closed tray technique, reusable, repositionable, screw-retained, titanium

Including screw for impression coping, short: The screw is included separately in the scope of delivery



Height	External Ø	3.9 mm	5.0 mm	5.5 mm	6.0 mm	7.0 mm
12.0 mm	long	5.04.046	5.04.047	5.04.048	5.04.049	5.04.050



Exclusive screw

12.0 mm	long	3.04.046	3.04.047	3.04.048	3.04.049	3.04.050
---------	------	-----------------	-----------------	-----------------	-----------------	-----------------

Screws for impression coping for closed tray technique, short



Length

12.5 mm	extra short	3.03.572				
---------	-------------	-----------------	--	--	--	--




16.5 mm	short	3.03.573				
---------	-------	-----------------	--	--	--	--



13.2 mm	extra short		3.03.575			
---------	-------------	--	-----------------	--	--	--



17.2 mm	short		3.03.576			
---------	-------	--	-----------------	--	--	--



Rotation locked
Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Impression coping for open tray technique, single use, retentive, screw-retained, aluminum, anodized



Height	External-Ø	3.8 mm	4.3 mm	4.8 mm	5.3 mm	6.3 mm
cylindrical 10.0 mm		3.03.010	3.03.018	3.03.011	3.03.012	3.03.013



Height	External-Ø	3.8 mm	5.0 mm	5.5 mm	6.0 mm	7.0 mm
conical 10.0 mm			3.03.078	3.03.071	3.03.072	3.03.073

Impression coping for open tray technique, reusable, retentive, screw-retained, titanium



Height	External-Ø	3.8 mm	4.3 mm	4.8 mm	5.3 mm	6.3 mm
cylindrical 16.0 mm		3.04.020	3.04.021	3.04.022	3.04.023	3.04.024



Height	External-Ø	5.0 mm	5.5 mm	6.0 mm	7.0 mm
conical 16.0 mm		3.04.037	3.04.038	3.04.039	3.04.040

Screws for impression copings, reusable, 4-lobe, stainless steel





Length					
12.5 mm	extra short	3.03.572			
16.5 mm	short	3.03.573			
21.5 mm	long	3.03.574			
27.5 mm	extra short	3.03.580			



13.2 mm	extra short		3.03.575		
17.2 mm	short		3.03.576		
22.2 mm	long		3.03.577		
28.2 mm	extra short		3.03.581		



Selection of appropriate screw length:



Positioning handle, stainless steel



Length	Ø	
17.0 mm	6.0 mm	3.03.522 *

* The positioning handle (art. no. 3.03.522) may be used for all impression copings at implant level (except for impression copings 16.0 mm in height).

Scan abutments

www.ifu-tm.com/THM61143

 Rotation locked
 Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

 digital



 **Scan abutment**, stainless steel, coated

Including screw for scan abutment: The screw is included separately in the scope of delivery

Height

10.0 mm

5.03.775

5.03.776

5.03.777

5.03.778

5.03.779

Exclusive screw

Height

10.0 mm

3.03.775

3.03.776

3.03.777

3.03.778

3.03.779



Screw for impression copings, reusable, 4-lobe, stainless steel

Length

12.5 mm extra short

3.03.572

13.2 mm extra short

3.03.575



Important Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

 digital



 **VARIOmulti, scan abutment**, titanium, 4-lobe

Height

8.0 mm

3.03.780

 digital



 **VARIOmulti, scan abutment, short**, titanium, 4-lobe

Height

5.0 mm

3.03.781

No additional screws are necessary for the attachment of VARIOmulti scan abutments.

The VARIOmulti scan abutments should be used as follows:

- Laboratory scan: long scan abutment (3.03.780)
- Intraoral scan with neighboring teeth: long scan abutment (3.03.780)
- Intraoral scan without neighboring teeth: short scan abutment (3.03.781), as long as the laser marking projects above the gingiva.

Impression taking at abutment level

 Rotation locked
 Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Thommen Medical offers impression copings for impression taking at abutment level for the EASY, VARIOmulti implant lines, as well as for the LOCATOR® and bar abutments. Temporary and protective caps are available for the temporary restoration of EASY and VARIOmulti abutments (see pages 38, 44, 46, 48).

EASY impression coping, plastic



Height	Cone					
9.5 mm	4.0 mm	2.03.700	2.03.708	2.03.701	2.03.702	2.03.703
11.5 mm	6.0 mm	2.03.704	2.03.709	2.03.705	2.03.706	2.03.707

 **Important** Not suitable for EASY abutment 20°.

VARIOmulti impression coping*, titanium



Height	Ø	
18.0 mm	5.3 mm	3.04.805

* Use the yellow screws for impression copings PF 3.5 (art. nos. 3.03.572, 3.03.573, 3.03.574, 3.03.580) to attach the VARIOmulti impression copings, see p. 38.

Impression coping for bar, aluminum, anodized/plastic




Height	Ø	
5.0 mm	6.0 mm	3.03.101

LOCATOR® impression coping, aluminum/LDPE, 4 per pack



8505

Implant analogs



Rotation locked
Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0



Implant analogs, titanium

Length

14.0 mm

3.03.090

3.03.095

3.03.091

3.03.092

3.03.093*

22.0 mm

3.03.060

3.03.061

3.03.065

3.03.062

3.03.063

Implant analogs are used for impression taking with impression copings at the implant level.

* Due to design requirements the overall length is 15.0 mm



Implant analogs for CAD/CAM, titanium



Length

11.4 mm

3.03.085

3.03.086

3.03.087

3.03.088

3.03.089

Implant analogs for CAD/CAM are used for 3D-printed models.

Insertion device for implant analog for CAD/CAM, stainless steel



Length

35.0 mm

3.03.158

35.0 mm

3.03.159

Handle for dental laboratory, brass/steel



Length


120.0 mm

3.03.250



Important Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

Abutment analogs



PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Abutment analogs are only used for impression taking using an impression coping at abutment level. The abutment analogs are also available for the individual abutment lines.

EASY analog, stainless steel



Height	Cone					
14.0 mm	4.0 mm	3.03.700	3.03.708	3.03.701	3.03.702	3.03.703
16.0 mm	6.0 mm	3.03.704	3.03.709	3.03.705	3.03.706	3.03.707

VARIOmulti analog, stainless steel



Ø	Height	
4.8 mm	21.2 mm	3.03.800



VARIOmulti analog, for CAD/CAM, titanium



Ø	Length	
4.8 mm	13.2 mm	3.03.083

VARIOmulti analogs for CAD/CAM are used for 3D-printed models.

Insertion device for VARIOmulti analog for CAD/CAM, stainless steel



Length	
35.8 mm	3.03.157

LOCATOR® analog, 4 per pack, aluminum



Ø	
4.0 mm (preferably used with PF 3.5, 4.0 and 4.5 mm)	8530
5.0 mm (preferably used with PF 5.0 and 6.0 mm)	8516

Retentive anchor analog, titanium



Length	
13.0 mm	3.03.033

Thommen Medical retentive anchors have a spherical diameter of 2.25 mm and are compatible with all matrices of this geometry (e.g. Dalbo®-Plus, Tima®, Ecco®, Pro-Snap®, etc.).







Bar analog, titanium



Length	Ø	
21.5 mm	4.0 mm	3.03.105

Prosthetic overview PF 3.5

Screws	Gingiva former
Applicable for all restorations	
Occlusal screw  Length 3.5 mm 4.03.507	Gingiva former customizable  Height 7.5 mm 4.03.570
Screw for bar  Length 4.3 mm 4.03.506	Healing cap SE  Height 1.0 mm 4.03.515
Abutment screw  Length 5.8 mm 4.03.500	Gingiva former  Height 2.0 mm 4.03.520 3.2 mm 4.03.530 4.5 mm 4.03.540 5.7 mm 4.03.560 7.0 mm 4.03.550
VARIOmulti fabrication screw  Length 19.3 mm Pcs. 4 3.03.598 Q4	Gingiva former narrow  Height 2.0 mm 4.04.310 3.2 mm 4.04.320 4.5 mm 4.04.330 5.7 mm 4.04.340 7.0 mm 4.04.350
Laboratory screw  Length 25.0 mm 3.03.515	Gingiva former +  Height 2.0 mm 4.03.525 3.2 mm 4.03.535
Fabrication screw  Length 22.5 mm Pcs. 4 3.03.590 Q4	
Dynamic Abutment screw  Length 6.9 mm 41.314.069.01-2	

	Impression taking	Temp. restoration
Cemented	EASY impression coping  Height 9.5 mm Cone 4.0 mm 2.03.700 EASY 11.5 mm 6.0 mm 2.03.704 ART 11.5 mm 6.0 mm 2.03.705	EASY temporary cap  Height 5.0 mm Cone 4.0 mm 2.03.740 EASY 7.0 mm 6.0 mm 2.03.744 ART 7.0 mm 6.0 mm 2.03.745
Screw-retained & cemented	Impression copings  Titanium Conical 3.04.030 ¹ 3.04.046 ¹ Cylindrical 3.04.020 ¹ Alu Conical 3.03.074 ¹ 3.03.014 ¹ Cylindrical 3.03.010 ¹ 5.03.074 5.03.014 Scan abutment Screw for impression coping  Stainless steel, coated 3.03.775 ¹ 5.03.775 Length 12.5 mm 3.03.572	VARIOtemp set  Height 12.0 mm 1.04.080 12.0 mm 1.04.085 ¹
Screw-retained	Impression copings  Titanium Conical 3.04.030 ¹ 3.04.046 ¹ Cylindrical 3.04.020 ¹ Alu Conical 3.03.074 ¹ 3.03.014 ¹ Cylindrical 3.03.010 ¹ 5.03.074 5.03.014 VARIOmulti impression coping  Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 VARIOmulti Scan abutment VARIOmulti Scan abutment, short  Height 8.0 mm 4.5 mm 3.03.780 5.0 mm 5.0 mm 3.03.781	VARIOtemp set  Height 12.0 mm 1.04.080 12.0 mm 1.04.085 ¹
Overdenture	LOCATOR® Bar abutment Abutment impression coping Impression coping  Alu 4 pcs. 8505 Height 5.0 mm 6.0 mm 3.03.101	VARIOmulti protective cap VARIOmulti temp. cap  Height 4.5 mm 4.03.801 15.0 mm 3.03.804
Overdenture		LOCATOR®  20 pcs. 8515-20

- NOTICE:**
- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
 - In each case, the symbols correspond to required components, which can be ordered separately **I** – **VII**.
 - Rotation locked Rotation unlocked
 - *Item is supplied without screw.

Final restoration

EASY abutment

Collar	Cone	Height	
short 0.5 mm	4.0 mm	4.5 mm	4.03.700
short 0.5 mm	6.0 mm	6.5 mm	4.03.704
long 2.0 mm	4.0 mm	6.0 mm	4.03.710
long 2.0 mm	6.0 mm	8.0 mm	4.03.714
extra long 4.0 mm	6.0 mm	10.0 mm	4.03.734

EASY abutment 20°

Collar	Height	
20° short 0.5 mm	6.5 mm	4.03.010
20° long 3.0 mm	8.0 mm	4.03.014

EASY abutment set

Collar	Cone	Height	
short 0.5 mm	4.0 mm	4.5 mm	1.04.700
short 0.5 mm	6.0 mm	6.5 mm	1.04.704
long 2.0 mm	4.0 mm	6.0 mm	1.04.710
long 2.0 mm	6.0 mm	8.0 mm	1.04.714
extra long 4.0 mm	6.0 mm	10.0 mm	1.04.734

Set contents:

- EASY abutment
- abutment screw
- EASY impression coping
- EASY analog
- EASY temporary cap
- EASY burn-out cap, for crown, burn-out plastic
- EASY burn-out cap, for bridge, burn-out plastic

Burn-out cap

EASY burn-out cap

Height	Cone	
4.7 mm	4.0 mm	2.03.720
6.7 mm	6.0 mm	2.03.724
4.7 mm	4.0 mm	2.03.730*
6.7 mm	6.0 mm	2.03.734*

Analog

EASY analog

Cone	
4.0 mm	3.03.700
6.0 mm	3.03.704

Implant analog

Length	
22.0 mm	3.03.060
14.0 mm	3.03.090

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.085

ART abutment set

Cone	Height	
6.0 mm	9.0 mm	1.03.623

ART grinding cylinder set

Height	
12.0 mm	1.03.649

Dynamic Tibase®

Height	
4.0 mm	31.311.113.01-2
4.0 mm	31.321.113.01-2*

Dynamic Tibase® shortenable

Height	
9.0 mm	31.310.113.21-2
9.0 mm	31.320.113.21-2*

EASY burn-out cap

Height	Cone	
ART 6.7 mm	6.0 mm	2.03.725
ART 6.7 mm	6.0 mm	2.03.735*

EASY analog

Cone	
6.0 mm	3.03.705

Implant analog

Length	
22.0 mm	3.03.060
14.0 mm	3.03.090

VARIOflex set

Height	
12.0 mm	1.04.830
12.0 mm	1.04.835*

Titanium Base CAD/CAM set

Height	
5.2 mm	1.04.750
5.2 mm	1.04.760*

Milling abutment for CAD/CAM Type II

Length	Ø	
15.0 mm	8.0 mm	1.04.401

VARIOeco burn-out cap

Height	
12.0 mm	2.03.790

VARIOflex burn-out cap

Height	
11.5 mm	2.03.840

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.085

VARIO abutment 17° set

0°	Height	Shoulder height	Type A	
	5.6 mm	0.5 mm		1.03.160
30°	Height	Shoulder height	Type B	
	5.6 mm	0.5 mm		1.03.180

Set contents:

- VARIO abutment 17° (titanium)
- VARIO 17° gold-screw seat
- occlusal screw
- abutment screw

VARIO gold abutment, NOA

Height	Cone	
12.7 mm	3.5 mm	2.03.410
12.7 mm	3.5 mm	2.03.400*

VARIO 17° gold screw seat

Height	Ø	
11.3 mm	2.9 mm	2.03.610

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.085

Implant analog

Length	
22.0 mm	3.03.060
14.0 mm	3.03.090

VARIOmulti abutment

Collar height (h)	
0.8 mm	4.03.6005
2.0 mm	4.03.6055
3.0 mm	4.03.6105

VARIOmulti abutment angled

Angle	Collar height (h)	
17°	1.6 mm	4.03.3005
17°	2.5 mm	4.03.3105
30°	1.2 mm	4.03.3055
30°	2.5 mm	4.03.3155

VARIOmulti gold cap NOA

Height	Ø	
4.2/13.5 mm	4.8 mm	2.03.600

VARIOmulti titanium base for CAD/CAM

Height	Ø	
4.5 mm	4.8 mm	1.04.850

VARIOmulti titanium base for CAD/CAM, shortenable

Height	Ø	
9.0 mm	4.8 mm	1.04.851

VARIOmulti burn-out cap

Height	Ø	pcs.	
13.5 mm	4.8 mm	2	2.03.601 02

VARIOmulti analog

Height	Ø	
21.2 mm	4.8 mm	3.03.800

VARIOmulti analog for CAD/CAM

Height	Ø	
13.2 mm	4.8 mm	3.03.083

LOCATOR® abutment

Height	
0.73 mm	8875
2.0 mm	8876
3.0 mm	8877
4.0 mm	8878
5.0 mm	8879*
6.0 mm	8880*

*Only available in the US.

RETAIN Milling abutment

Height	
11.0 mm	4.03.420

Bar abutment

Height	
5.5 mm	4.03.380

Coping for bar

Gold	
	2.03.335
Titanium	
	4.03.070

LOCATOR®
For components, see:
thommenmedical.com
or product catalogue

Length	
21.5 mm	3.03.105
Ø	pcs.
4.0 mm	4 8530
5.0 mm	4 8516




Bar analog

LOCATOR® analog

Length	
21.5 mm	3.03.105
Ø	pcs.
4.0 mm	4 8530
5.0 mm	4 8516

Prosthetic overview PF 4.0

Screws	Gingiva former
Occlusal screw  Length 3.5 mm 4.03.507	Applicable for all restorations Gingiva former customizable  Height 7.5 mm 4.03.571
Screw for bar  Length 4.3 mm 4.03.506	Healing cap SE  Height 1.0 mm 4.03.519
Abutment screw  Length 7.2 mm 4.03.501 10.2 mm 4.03.502	Gingiva former  Height 2.0 mm 4.03.524 3.2 mm 4.03.534 4.5 mm 4.03.544 5.7 mm 4.03.564 7.0 mm 4.03.554
VARIOmulti fabrication screw  Length Pcs. 19.3 mm 4 3.03.598 04	Gingiva former narrow  Height 2.0 mm 4.04.311 3.2 mm 4.04.321 4.5 mm 4.04.331 5.7 mm 4.04.341 7.0 mm 4.04.351
Laboratory screw  Length 25.0 mm 3.03.516	
Fabrication screw  Length Pcs. 23.4 mm 4 3.03.591 04	
Dynamic Abutment screw  Length 7.6 mm 41.316.076.02-2	

	Impression taking																																																			
Cemented	EASY impression coping  <table> <tr> <th></th><th>Height</th><th>Cone</th><th></th></tr> <tr> <td>EASY</td><td>9.5 mm</td><td>4.0 mm</td><td>2.03.708</td></tr> <tr> <td>EASY</td><td>11.5 mm</td><td>6.0 mm</td><td>2.03.709</td></tr> <tr> <td>EASY e.p.</td><td>9.5 mm</td><td>4.0 mm</td><td>2.03.701</td></tr> <tr> <td>EASY e.p./ART</td><td>11.5 mm</td><td>6.0 mm</td><td>2.03.705</td></tr> </table> <table> <tr> <td>Konisch</td><td>Konisch</td><td>Zylindrisch</td><td>Zylindrisch</td></tr> <tr> <td>3.03.079¹</td><td>3.03.019¹</td><td>3.03.018¹</td><td>3.04.021¹</td></tr> <tr> <td>5.03.079</td><td>5.03.019</td><td></td><td></td></tr> </table>		Height	Cone		EASY	9.5 mm	4.0 mm	2.03.708	EASY	11.5 mm	6.0 mm	2.03.709	EASY e.p.	9.5 mm	4.0 mm	2.03.701	EASY e.p./ART	11.5 mm	6.0 mm	2.03.705	Konisch	Konisch	Zylindrisch	Zylindrisch	3.03.079¹	3.03.019¹	3.03.018¹	3.04.021¹	5.03.079	5.03.019																					
	Height	Cone																																																		
EASY	9.5 mm	4.0 mm	2.03.708																																																	
EASY	11.5 mm	6.0 mm	2.03.709																																																	
EASY e.p.	9.5 mm	4.0 mm	2.03.701																																																	
EASY e.p./ART	11.5 mm	6.0 mm	2.03.705																																																	
Konisch	Konisch	Zylindrisch	Zylindrisch																																																	
3.03.079¹	3.03.019¹	3.03.018¹	3.04.021¹																																																	
5.03.079	5.03.019																																																			
Screw-retained & cemented	Impression copings  <table> <tr> <th></th><th>Conical</th><th>Conical</th><th>Conical</th><th>Conical</th><th></th></tr> <tr> <td>Titanium</td><td>3.04.031¹</td><td>3.04.047¹</td><td>3.03.078¹</td><td>3.04.037¹</td><td></td></tr> <tr> <td></td><td>5.04.031¹</td><td>5.04.047¹</td><td></td><td></td><td></td></tr> <tr> <td>Alu</td><td>3.03.079¹</td><td>3.03.019¹</td><td>3.03.018¹</td><td>3.04.021¹</td><td></td></tr> <tr> <td></td><td>5.03.079</td><td>5.03.019</td><td></td><td></td><td></td></tr> </table> Scan abutment  Stainless steel, coated 3.03.776¹ 5.03.776 Screw for impression coping  Length 13.2 mm 3.03.575		Conical	Conical	Conical	Conical		Titanium	3.04.031¹	3.04.047¹	3.03.078¹	3.04.037¹			5.04.031¹	5.04.047¹				Alu	3.03.079¹	3.03.019¹	3.03.018¹	3.04.021¹			5.03.079	5.03.019																								
	Conical	Conical	Conical	Conical																																																
Titanium	3.04.031¹	3.04.047¹	3.03.078¹	3.04.037¹																																																
	5.04.031¹	5.04.047¹																																																		
Alu	3.03.079¹	3.03.019¹	3.03.018¹	3.04.021¹																																																
	5.03.079	5.03.019																																																		
Screw-retained	Impression copings  <table> <tr> <th></th><th>Conical</th><th>Conical</th><th>Conical</th><th>Conical</th><th></th></tr> <tr> <td>Titanium</td><td>3.04.031¹</td><td>3.04.047¹</td><td>3.03.078¹</td><td>3.04.037¹</td><td></td></tr> <tr> <td></td><td>5.04.031¹</td><td>5.04.047¹</td><td></td><td></td><td></td></tr> <tr> <td>Alu</td><td>3.03.079¹</td><td>3.03.019¹</td><td>3.03.018¹</td><td>3.04.021¹</td><td></td></tr> <tr> <td></td><td>5.03.079</td><td>5.03.019</td><td></td><td></td><td></td></tr> </table> VARIOmulti impression coping  <table> <tr> <th></th><th>Height</th><th></th></tr> <tr> <td>Alu</td><td>18.0 mm</td><td>3.04.805</td></tr> <tr> <td>Titanium</td><td></td><td></td></tr> <tr> <td></td><td></td><td>3.03.572</td></tr> <tr> <td></td><td></td><td>3.03.573</td></tr> <tr> <td></td><td></td><td>3.03.574</td></tr> <tr> <td></td><td></td><td>3.03.580</td></tr> </table> VARIOmulti Scan abutment  Height 8.0 mm Ø 4.5 mm 3.03.780 VARIOmulti Scan abutment, short  Height 5.0 mm Ø 5.0 mm 3.03.781		Conical	Conical	Conical	Conical		Titanium	3.04.031¹	3.04.047¹	3.03.078¹	3.04.037¹			5.04.031¹	5.04.047¹				Alu	3.03.079¹	3.03.019¹	3.03.018¹	3.04.021¹			5.03.079	5.03.019					Height		Alu	18.0 mm	3.04.805	Titanium					3.03.572			3.03.573			3.03.574			3.03.580
	Conical	Conical	Conical	Conical																																																
Titanium	3.04.031¹	3.04.047¹	3.03.078¹	3.04.037¹																																																
	5.04.031¹	5.04.047¹																																																		
Alu	3.03.079¹	3.03.019¹	3.03.018¹	3.04.021¹																																																
	5.03.079	5.03.019																																																		
	Height																																																			
Alu	18.0 mm	3.04.805																																																		
Titanium																																																				
		3.03.572																																																		
		3.03.573																																																		
		3.03.574																																																		
		3.03.580																																																		
Overdenture	LOCATOR® Abutment impression coping  Alu 4 pcs. 8505 Bar abutment Impression coping  Height Ø 5.0 mm 6.0 mm 3.03.101																																																			

Temp. restoration

EASY temporary cap

<

- NOTICE:**
- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
 - In each case, the symbols correspond to required components, which can be ordered separately **I** – **VII**.
 - Rotation locked Rotation unlocked
 - *Item is supplied without screw.

Final restoration

EASY abutment

Collar	Cone	Height
short 0.5 mm	4.0 mm	4.5 mm 4.03.708
short 0.5 mm	6.0 mm	6.5 mm 4.03.709
long 2.0 mm	4.0 mm	6.0 mm 4.03.718
long 2.0 mm	6.0 mm	8.0 mm 4.03.719
extra long 4.0 mm	6.0 mm	10.0 mm 4.03.739

EASY abutment 20°

Collar	Height
20° short 0.5 mm	6.5 mm 4.03.018
20° long 3.0 mm	9.0 mm 4.03.019

EASY abutment set

Collar	Cone	Height
short 0.5 mm	4.0 mm	4.5 mm 1.04.708
short 0.5 mm	6.0 mm	6.5 mm 1.04.709
long 2.0 mm	4.0 mm	6.0 mm 1.04.718
long 2.0 mm	6.0 mm	8.0 mm 1.04.719
extra long 4.0 mm	6.0 mm	10.0 mm 1.04.739

Set contents:

- EASY abutment
- abutment screw
- EASY impression coping
- EASY analog
- EASY temporary cap
- EASY burn-out cap for crown
- EASY burn-out cap for bridge

EASY abutment e.p.

Height	Cone
7.0 mm	4.0 mm 4.03.728
9.0 mm	6.0 mm 4.03.729

Burn-out cap

EASY burn-out cap

Height	Cone
EASY 4.7 mm	4.0 mm 2.03.728
EASY 6.7 mm	6.0 mm 2.03.729
EASY 4.7 mm	4.0 mm 2.03.738*
EASY 6.7 mm	6.0 mm 2.03.739*
EASY e.p. 4.7 mm	4.0 mm 2.03.721
EASY e.p. 6.7 mm	6.0 mm 2.03.725
EASY e.p. 4.7 mm	4.0 mm 2.03.731*
EASY e.p. 6.7 mm	6.0 mm 2.03.735*

Analog

EASY analog

Cone
EASY 4.0 mm 3.03.708
EASY 6.0 mm 3.03.709
EASY e.p. 4.0 mm 3.03.701
EASY e.p. 6.0 mm 3.03.705

Implant analog

Length
22.0 mm 3.03.061
14.0 mm 3.03.095

Implant analog for CAD/CAM

Length
11.4 mm 3.03.086

ART abutment set

Cone	Height
6.0 mm	9.0 mm 1.03.624

ART grinding cylinder set

Height
12.0 mm 1.03.650

Dynamic Tibase®

Height
4.0 mm 31.312.114.01-2
4.0 mm 31.322.114.01-2*

Dynamic Tibase® shortenable

Height
9.0 mm 31.312.114.21-2
9.0 mm 31.322.114.21-2*

EASY burn-out cap

Height	Cone
ART 6.7 mm	6.0 mm 2.03.725
ART 6.7 mm	6.0 mm 2.03.735*

EASY analog

Cone
ART 6.0 mm 3.03.705

Implant analog

Length
22.0 mm 3.03.061
14.0 mm 3.03.095

VARIOflex set

Height
12.0 mm 1.04.831
12.0 mm 1.04.836*

Titanium Base CAD/CAM set

Height
5.2 mm 1.04.751
5.2 mm 1.04.761*

Milling abutment for CAD/CAM Type II

Length	Ø
15.0 mm	11.5 mm 1.04.403

VARIOeco burn-out cap

Height
12.0 mm 2.03.791

VARIOflex burn-out cap

Height
11.5 mm 2.03.841

Implant analog for CAD/CAM

Length
11.4 mm 3.03.086

VARIO abutment 17° set

0°	Height	Shoulder height	Type A
	5.6 mm	0.5 mm	1.03.161
30°	Height	Shoulder height	Type B
	5.6 mm	0.5 mm	1.03.181

Set contents:

- VARIO abutment 17° (titanium)
- VARIO 17° gold screw seat
- occlusal screw
- abutment screw

VARIO gold abutment, NOA

Height	Cone
12.7 mm	3.5 mm 2.03.414
12.7 mm	3.5 mm 2.03.404*

VARIO 17° gold screw seat

Height	Ø
11.3 mm	2.9 mm 2.03.610

Implant analog for CAD/CAM

Length
11.4 mm 3.03.086

Implant analog

Length
22.0 mm 3.03.061
14.0 mm 3.03.095

VARIOmulti abutment

Collar height (h)
0.8 mm 4.03.601S
2.0 mm 4.03.606S
3.0 mm 4.03.611S

VARIOmulti abutment angled

Angle	Collar height (h)
17°	1.6 mm 4.03.301S
17°	2.5 mm 4.03.311S
30°	1.2 mm 4.03.306S
30°	2.5 mm 4.03.316S

VARIOmulti gold cap, NOA

Height	Ø
4.2/13.5 mm	4.8 mm 2.03.600

VARIOmulti titanium base for CAD/CAM

Height	Ø
4.5 mm	4.8 mm 1.04.850

VARIOmulti titanium base for CAD/CAM, shortenable

Height	Ø
9.0 mm	4.8 mm 1.04.851

VARIOmulti burn-out cap

Height	Ø	pcs.
13.5 mm	4.8 mm	2 2.03.601 Q2

VARIOmulti analog

Height	Ø
21.2 mm	4.8 mm 3.03.800

VARIOmulti analog for CAD/CAM

Height	Ø
13.2 mm	4.8 mm 3.03.083

LOCATOR® abutment

Height
1.0 mm 8461
2.0 mm 8462
3.0 mm 8463
4.0 mm 8464
5.0 mm 8465
6.0 mm 8466

Retentive anchor abutment

Height
1.8 mm 4.03.048
3.0 mm 4.03.049

RETAIN

Milling abutment
Height 12.0 mm 4.03.428
Bar abutment
Height 5.5 mm 4.03.388
Coping for bar
Gold 2.03.395
Titanium 4.03.070

LOCATOR®
For components, see:
thommenmedical.com
or product catalogue

Retentive anchor Analog








Length
13.0 mm 3.03.033

LOCATOR® analog

Ø	Pcs.
4.0 mm	4 8530
5.0 mm	4 8516

Prosthetic overview PF 4.5

Screws	Gingiva former
Applicable for all restorations	Applicable for all restorations
Occlusal screw  Length 3.5 mm 4.03.507	Gingiva former customizable  Height 7.5 mm 4.03.572
Screw for bar  Length 4.3 mm 4.03.506	Healing cap SE  Height 1.0 mm 4.03.516
Abutment screw  Length 7.2 mm 4.03.501 10.2 mm 4.03.502	Gingiva former  Height 2.0 mm 4.03.521 3.2 mm 4.03.531 3.5 mm 4.03.531 4.5 mm 4.03.541 5.7 mm 4.03.561 7.0 mm 4.03.551
VARIOmulti fabrication screw  Length Pcs. 19.3 mm 4 3.03.598 04	Gingiva former narrow  Height 2.0 mm 4.04.312 3.2 mm 4.04.322 3.5 mm 4.04.322 4.5 mm 4.04.332 5.7 mm 4.04.342 7.0 mm 4.04.352
Laboratory screw  Length 25.0 mm 3.03.516	
Fabrication screw  Length Pcs. 23.4 mm 4 3.03.591 04	
Dynamic Abutment screw  Length 7.6 mm 41.316.076.02-2	

Impression taking	Temp. restoration
EASY impression coping  Height Cone EASY 9.5 mm 4.0 mm 2.03.701 EASY 11.5 mm 6.0 mm 2.03.705 EASY e.p. 9.5 mm 4.0 mm 2.03.702 EASY e.p./ART 11.5 mm 6.0 mm 2.03.706	EASY temporary cap  Height Cone EASY 5.0 mm 4.0 mm 2.03.741 EASY 7.0 mm 6.0 mm 2.03.745 EASY e.p. 5.0 mm 4.0 mm 2.03.742 EASY e.p./ART 7.0 mm 6.0 mm 2.03.746
Impression copings  Alu Titanium Titanium Conical Conical Conical Conical 3.04.032 3.04.048 3.03.071 3.04.038 5.04.032 5.04.048 Alu Conical Conical Cylindrical Cylindrical 3.03.075 3.03.015 3.03.011 3.04.022 5.03.075 5.03.015 Screws 3.03.575 3.03.576 3.03.577 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm Scan abutment Screw for impression coping  Stainless steel, coated 3.03.777 5.03.777 Length 13.2 mm 3.03.575	VARIOtemp set  Height 12.0 mm 1.04.082 12.0 mm 1.04.087*
Impression copings  Alu Titanium Titanium Conical Conical Conical Conical 3.04.032 3.04.048 3.03.071 3.04.038 5.04.032 5.04.048 Alu Conical Conical Cylindrical Cylindrical 3.03.075 3.03.015 3.03.011 3.04.022 5.03.075 5.03.015 Screws 3.03.575 3.03.576 3.03.577 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm VARIOmulti impression coping  VARIOmulti Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 12.5 mm 16.5 mm 21.5 mm 27.5 mm VARIOmulti Scan abutment VARIOmulti Scan abutment, short  Height Ø 8.0 mm 4.5 mm 3.03.780 5.0 mm 5.0 mm 3.03.781	VARIOtemp set  Height 12.0 mm 1.04.082 12.0 mm 1.04.087* VARIOmulti protective cap VARIOmulti temp. cap  Height 4.5 mm 4.03.801 15.0 mm 3.03.804
LOCATOR® Abutment impression coping  Alu 4 pcs. 8505 Bar abutment Impression coping  Height Ø 5.0 mm 6.0 mm 3.03.101	LOCATOR®  20 pcs. 8515-20

- NOTICE:**
- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
 - In each case, the symbols correspond to required components, which can be ordered separately **I** – **VII**.
 - Rotation locked Rotation unlocked
 - *Item is supplied without screw.

Final restoration

EASY abutment

Collar	Cone	Height	
short 0.5 mm	4.0 mm 4.5 mm		4.03.701
short 0.5 mm	6.0 mm 6.5 mm		4.03.705
long 2.0 mm	4.0 mm 6.0 mm		4.03.711
long 2.0 mm	6.0 mm 8.0 mm		4.03.715
extra long 4.0 mm	6.0 mm 10.0 mm		4.03.735

EASY abutment 20°

Collar	Height	
20° short 0.5 mm	6.5 mm	4.03.011
20° long 3.0 mm	9.0 mm	4.03.015

EASY abutment set

Collar	Cone	Height	
short 0.5 mm	4.0 mm 4.5 mm		1.04.701
short 0.5 mm	6.0 mm 6.5 mm		1.04.705
long 2.0 mm	4.0 mm 6.0 mm		1.04.711
long 2.0 mm	6.0 mm 8.0 mm		1.04.715
extra long 4.0 mm	6.0 mm 10.0 mm		1.04.735

- Set contents:
- EASY abutment
 - abutment screw
 - EASY impression coping
 - EASY analog
 - EASY temporary cap
 - EASY burn-out cap for crown
 - EASY burn-out cap for bridge

EASY abutment e.p.

Height	Cone	
7.0 mm	4.0 mm	4.03.721
9.0 mm	6.0 mm	4.03.725

Burn-out cap

EASY burn-out cap

Height	Cone	
EASY 4.7 mm 4.0 mm		2.03.721
EASY 6.7 mm 6.0 mm		2.03.725
EASY 4.7 mm 4.0 mm		2.03.731*
EASY 6.7 mm 6.0 mm		2.03.735*
EASY e.p. 4.7 mm 4.0 mm		2.03.722
EASY e.p. 6.7 mm 6.0 mm		2.03.726
EASY e.p. 4.7 mm 4.0 mm		2.03.732*
EASY e.p. 6.7 mm 6.0 mm		2.03.736*

Analog

EASY analog

Cone	
EASY 4.0 mm	3.03.701
EASY 6.0 mm	3.03.705
EASY e.p. 4.0 mm	3.03.702
EASY e.p. 6.0 mm	3.03.706

Implant analog

Length	
22.0 mm	3.03.065
14.0 mm	3.03.091

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.087

ART abutment set

Cone	Height	
6.0 mm	9.0 mm	1.03.625

ART grinding cylinder set

Height	
12.0 mm	1.03.651

Dynamic Tibase®

Height	
4.0 mm	31.313.115.01-2
4.0 mm	31.323.115.01-2*

Dynamic Tibase® shortenable

Height	
9.0 mm	31.313.115.21-2
9.0 mm	31.323.115.21-2*

EASY burn-out cap

Height	Cone	
ART 6.7 mm	6.0 mm	2.03.726
ART 6.7 mm	6.0 mm	2.03.736*

EASY analog

Cone	
ART 6.0 mm	3.03.706

Implant analog

Length	
22.0 mm	3.03.065
14.0 mm	3.03.091

VARIOflex set

Height	
12.0 mm	1.04.832
12.0 mm	1.04.837*

Titanium Base CAD/CAM set

Height	
5.2 mm	1.04.752
5.2 mm	1.04.762*

Milling abutment for CAD/CAM Type II

Length	Ø	
15.0 mm	11.5 mm	1.04.405

VARIOeco burn-out cap

Height	
12.0 mm	2.03.792

VARIOflex burn-out cap

Height	
11.5 mm	2.03.842

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.087

VARIO abutment 17° set

0°	Height	Shoulder height	Type A	
	5.6 mm	0.5 mm		1.03.162
30°	Height	Shoulder height	Type B	
	5.6 mm	0.5 mm		1.03.182

- Set contents:
- VARIO abutment 17° (titanium)
 - VARIO 17° gold screw seat
 - occlusal screw
 - abutment screw

VARIO gold abutment, NOA

Height	Cone	
12.7 mm	3.5 mm	2.03.411
12.7 mm	3.5 mm	2.03.401*

VARIO 17° gold screw seat

Height	Ø	
11.3 mm	2.9 mm	2.03.610

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.087

Implant analog

Length	
22.0 mm	3.03.065
14.0 mm	3.03.091

VARIOmulti abutment

Collar height (h)	
0.8 mm	4.03.6025
2.0 mm	4.03.6075
3.0 mm	4.03.6125

VARIOmulti abutment angled

Angle	Collar height (h)	
17°	1.6 mm	4.03.3025
17°	2.5 mm	4.03.3125
30°	1.2 mm	4.03.3075
30°	2.5 mm	4.03.3175

VARIOmulti gold abutment, NOA

Height	Ø	
4.2/13.5 mm	4.8 mm	2.03.600

VARIOmulti titanium base for CAD/CAM

Height	Ø	
4.5 mm	4.8 mm	1.04.850

VARIOmulti titanium base for CAD/CAM, shortenable

Height	Ø	
9.0 mm	4.8 mm	1.04.851

VARIOmulti burn-out cap

Height	Ø	pcs.	
13.5 mm	4.8 mm	2	2.03.601 02

VARIOmulti analog

Height	Ø	
21.2 mm	4.8 mm	3.03.800

VARIOmulti analog for CAD/CAM

Height	Ø	
13.2 mm	4.8 mm	3.03.083

LOCATOR® abutment

Height	
1.0 mm	8786
2.0 mm	8787
3.0 mm	8788
4.0 mm	8789
5.0 mm	8790
6.0 mm	8791

Retentive anchor abutment

Height	
1.8 mm	4.03.040
3.0 mm	4.03.041

RETAIN Milling abutment

Height	
12.0 mm	4.03.421

Bar abutment

Height	
5.5 mm	4.03.381

Coping for bar

Gold	
	2.03.335
Titanium	
	4.03.070

LOCATOR®
For components, see:
thommenmedical.com
or product catalogue

Retentive anchor Analog











Length	
13.0 mm	3.03.033

LOCATOR® analog

Ø	pcs.	
4.0 mm	4	8530
5.0 mm	4	8516

Prosthetic overview PF 5.0

Screws	Gingiva former
	Applicable for all restorations
Occlusal screw  Length 3.5 mm 4.03.507	Gingiva former customizable  Height 7.5 mm 4.03.573
Screw for bar  Length 4.3 mm 4.03.506	Healing cap SE  Height 1.0 mm 4.03.517
Abutment screw  Length 7.2 mm 4.03.501 10.2 mm 4.03.502	Gingiva former  Height 2.0 mm 4.03.522 3.2 mm 4.03.532 4.5 mm 4.03.542 5.7 mm 4.03.562 7.0 mm 4.03.552
VARIOmulti fabrication screw  Length Pcs. 19.3 mm 4 3.03.598 04	Gingiva former narrow  Height 2.0 mm 4.04.313 3.2 mm 4.04.323 4.5 mm 4.04.333 5.7 mm 4.04.343 7.0 mm 4.04.353
Laboratory screw  Length 25.0 mm 3.03.516	
Fabrication screw  Length Pcs. 23.4 mm 4 3.03.591 04	
Dynamic Abutment screw  Length 7.6 mm 41.316.076.02-2	

	Impression taking	Temp. restoration
	EASY impression coping  Height Cone EASY 9.5 mm 4.0 mm 2.03.702 EASY 11.5 mm 6.0 mm 2.03.706 EASY e.p. 9.5 mm 4.0 mm 2.03.703 EASY e.p./ART 11.5 mm 6.0 mm 2.03.707	EASY temporary cap  Height Cone EASY 5.0 mm 4.0 mm 2.03.742 EASY 7.0 mm 6.0 mm 2.03.746 EASY e.p. 5.0 mm 4.0 mm 2.03.743 EASY e.p./ART 7.0 mm 6.0 mm 2.03.747
Cemented		
	Impression copings Closed tray Open tray Screws  Titanium Conical Conical Conical Conical 3.04.033 [†] 3.04.049 [†] 3.03.072 [†] 3.04.039 [†] 5.04.033 5.04.049 Alu Conical Conical Cylindrical Cylindrical 3.03.076 [†] 3.03.016 [†] 3.03.012 [†] 3.04.023 [†] 5.03.076 5.03.016 Scan abutment Screw for impression coping  Stainless steel, coated 3.03.778 [†] 5.03.778 Length 13.2 mm 3.03.575	VARIOtemp set  Height 12.0 mm 1.04.083 12.0 mm 1.04.088*
Screw-retained & cemented		
	Impression copings Closed tray Open tray Screws  Titanium Conical Conical Conical Conical 3.04.033 [†] 3.04.049 [†] 3.03.072 [†] 3.04.039 [†] 5.04.033 5.04.049 Alu Conical Conical Cylindrical Cylindrical 3.03.076 [†] 3.03.016 [†] 3.03.012 [†] 3.04.023 [†] 5.03.076 5.03.016 VARIOmulti impression coping Open tray Screws  Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 VARIOmulti Scan abutment Scan abutment, short  Height Ø 8.0 mm 4.5 mm 3.03.780 5.0 mm 5.0 mm 3.03.781	VARIOtemp set  Height 12.0 mm 1.04.083 12.0 mm 1.04.088*
Screw-retained		
	VARIOmulti impression coping Open tray Screws  Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 VARIOmulti Scan abutment Scan abutment, short  Height Ø 8.0 mm 4.5 mm 3.03.780 5.0 mm 5.0 mm 3.03.781	VARIOmulti protective cap VARIOmulti temp. cap  Height 4.5 mm 4.03.801 15.0 mm 3.03.804
Overdenture		
	LOCATOR® LOCATOR® Abutment impression coping Bar abutment Impression coping  Alu 4 pcs. 8505 Height Ø 5.0 mm 6.0 mm 3.03.101	LOCATOR®  20 pcs. 8515-20

- NOTICE:**
- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
 - In each case, the symbols correspond to required components, which can be ordered separately **I** – **VII**.
 - Rotation locked Rotation unlocked
 - *Item is supplied without screw.

Final restoration

EASY abutment

Collar	Cone	Height	
short 0.5 mm	4.0 mm	4.5 mm	4.03.702
short 0.5 mm	6.0 mm	6.5 mm	4.03.706
long 2.0 mm	4.0 mm	6.0 mm	4.03.712
long 2.0 mm	6.0 mm	8.0 mm	4.03.716
extra long 4.0 mm	6.0 mm	10.0 mm	4.03.736

EASY abutment 20°

Collar	Height	
20° short 0.5 mm	6.5 mm	4.03.012
20° long 3.0 mm	9.0 mm	4.03.016

EASY abutment set

Collar	Cone	Height	
short 0.5 mm	4.0 mm	4.5 mm	1.04.702
short 0.5 mm	6.0 mm	6.5 mm	1.04.706
long 2.0 mm	4.0 mm	6.0 mm	1.04.712
long 2.0 mm	6.0 mm	8.0 mm	1.04.716
extra long 4.0 mm	6.0 mm	10.0 mm	1.04.736

- Set contents:
- EASY abutment
 - abutment screw
 - EASY impression coping
 - EASY analog
 - EASY temporary cap
 - EASY burn-out cap for crown
 - EASY burn-out cap for bridge

EASY abutment e.p.

Height	Cone	
7.0 mm	4.0 mm	4.03.722
9.0 mm	6.0 mm	4.03.726

Burn-out cap

EASY burn-out cap

Height	Cone	
EASY 4.7 mm	4.0 mm	2.03.722
EASY 6.7 mm	6.0 mm	2.03.726
EASY 4.7 mm	4.0 mm	2.03.732*
EASY 6.7 mm	6.0 mm	2.03.736*
EASY e.p. 4.7 mm	4.0 mm	2.03.723
EASY e.p. 6.7 mm	6.0 mm	2.03.727
EASY e.p. 4.7 mm	4.0 mm	2.03.733*
EASY e.p. 6.7 mm	6.0 mm	2.03.737*

Analog

EASY analog

Cone	
EASY 4.0 mm	3.03.702
EASY 6.0 mm	3.03.706
EASY e.p. 4.0 mm	3.03.703
EASY e.p. 6.0 mm	3.03.707

Implant analog

Length	
22.0 mm	3.03.062
14.0 mm	3.03.092

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.088

ART abutment set

Cone	Height	
6.0 mm	9.0 mm	1.03.626

ART grinding cylinder set

Height	
12.0 mm	1.03.652

Dynamic Tibase®

Height	
4.0 mm	31.314.116.01-2
4.0 mm	31.324.116.01-2*

Dynamic Tibase® shortenable

Height	
9.0 mm	31.314.116.21-2
9.0 mm	31.324.116.21-2*

EASY burn-out cap

Height	Cone	
ART 6.7 mm	6.0 mm	2.03.727
ART 6.7 mm	6.0 mm	2.03.737*

EASY analog

Cone	
ART 6.0 mm	3.03.707

Implant analog

Length	
22.0 mm	3.03.062
14.0 mm	3.03.092

VARIOflex set

Height	
12.0 mm	1.04.833
12.0 mm	1.04.838*

Titanium Base CAD/CAM set

Height	
5.2 mm	1.04.753
5.2 mm	1.04.763*

Milling abutment for CAD/CAM Type II

Length	Ø	
15.0 mm	11.5 mm	1.04.407

VARIOeco burn-out cap

Height	
12.0 mm	2.03.793

VARIOflex burn-out cap

Height	
11.5 mm	2.03.843

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.088

VARIO abutment 17° set

0° Height	Shoulder height	Type A	
5.6 mm	0.5 mm		1.03.163
30° Height	Shoulder height	Type B	
5.6 mm	0.5 mm		1.03.183

- Set contents:
- VARIO abutment 17° (titanium)
 - VARIO 17° gold screw seat
 - occlusal screw
 - abutment screw

VARIO gold abutment, NOA

Height	Cone	
12.7 mm	3.5 mm	2.03.412
12.7 mm	3.5 mm	2.03.402*

VARIO 17° gold screw seat

Height	Ø	
11.3 mm	2.9 mm	2.03.610

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.088

Implant analog

Length	
22.0 mm	3.03.062
14.0 mm	3.03.092

VARIOmulti abutment

Collar height (h)	
0.8 mm	4.03.6035
2.0 mm	4.03.6085
3.0 mm	4.03.6135

VARIOmulti abutment angled

Angle	Collar height (h)	
17°	1.6 mm	4.03.3035
17°	2.5 mm	4.03.3135
30°	1.2 mm	4.03.3085
30°	2.5 mm	4.03.3185

VARIOmulti gold abutment, NOA

Height	Ø	
4.2/13.5 mm	4.8 mm	2.03.600

VARIOmulti titanium base for CAD/CAM

Height	Ø	
4.5 mm	4.8 mm	1.04.850

VARIOmulti titanium base for CAD/CAM, shortenable

Height	Ø	
9.0 mm	4.8 mm	1.04.851

VARIOmulti burn-out cap

Height	Ø	pcs.	
13.5 mm	4.8 mm	2	2.03.601 02

VARIOmulti analog

Height	Ø	
21.2 mm	4.8 mm	3.03.800

VARIOmulti analog for CAD/CAM

Height	Ø	
13.2 mm	4.8 mm	3.03.083

LOCATOR® abutment

Height	
1.0 mm	8792
2.0 mm	8793
3.0 mm	8794
4.0 mm	8795
5.0 mm	8796
6.0 mm	8797

Retentive anchor® abutment

Height	
1.8 mm	4.03.042
3.0 mm	4.03.043

RETAIN

Milling abutment	Height	
	12.0 mm	4.03.422
Bar abutment	Height	
	5.5 mm	4.03.382
Coping for bar		
Gold		2.03.335
Titanium		4.03.070

LOCATOR®
For components, see:
thommenmedical.com
or product catalogue

Retentive anchor Analog





Length	
13.0 mm	3.03.033

LOCATOR® analog

Ø	Pcs.	
4.0 mm	4	8530
5.0 mm	4	8516

Prosthetic overview PF 6.0

Screws		Gingiva former	
Occlusal screw		Applicable for all restorations	
 Length 3.5 mm 4.03.507		Gingiva former customizable  Height 7.5 mm 4.03.574	
Screw for bar  Length 4.3 mm 4.03.506		Healing cap SE  Height 1.0 mm 4.03.518	
Abutment screw  Length 7.2 mm 4.03.501 10.2 mm 4.03.502		Gingiva former  Height 2.0 mm 4.03.523 3.2 mm 4.03.533 4.5 mm 4.03.543 5.7 mm 4.03.563 7.0 mm 4.03.553	
VARIOmulti fabrication screw  Length Pcs. 19.3 mm 4 3.03.598 Q4		Gingiva former narrow  Height 2.0 mm 4.04.314 3.2 mm 4.04.324 4.5 mm 4.04.334 5.7 mm 4.04.344 7.0 mm 4.04.354	
Laboratory screw  Length 25.0 mm 3.03.516			
Fabrication screw  Length Pcs. 23.4 mm 4 3.03.591 Q4			

Impression taking		Temp. restoration	
EASY impression coping  Height Cone 9.5 mm 4.0 mm 2.03.703 11.5 mm 6.0 mm 2.03.707		EASY temporary cap  Height Cone 5.0 mm 4.0 mm 2.03.743 7.0 mm 6.0 mm 2.03.747	
Impression copings  Closed tray Open tray Screws Titanium Conical 3.04.034¹ 3.04.050¹ 3.03.073¹ 3.04.040¹ 5.04.034 5.04.050 Alu Conical 3.03.077¹ 3.03.017¹ 3.03.013¹ 3.04.024¹ 5.03.077 5.03.017 Cylindrical 3.03.575 Cylindrical 3.03.576 Cylindrical 3.03.577 Cylindrical 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm		VARIOtemp set  Height 12.0 mm 1.04.084 12.0 mm 1.04.089*	
Scan abutment  Stainless steel, coated 3.03.779¹ 5.03.779		Screw for impression coping  Length 13.2 mm 3.03.575	
Impression copings  Closed tray Open tray Screws Titanium Conical 3.04.034¹ 3.04.050¹ 3.03.073¹ 3.04.040¹ 5.04.034 5.04.050 Alu Conical 3.03.077¹ 3.03.017¹ 3.03.013¹ 3.04.024¹ 5.03.077 5.03.017 Cylindrical 3.03.575 Cylindrical 3.03.576 Cylindrical 3.03.577 Cylindrical 3.03.581 13.2 mm 17.2 mm 22.2 mm 28.2 mm		VARIOtemp set  Height 12.0 mm 1.04.084 12.0 mm 1.04.089*	
VARIOmulti impression coping  Open tray Screws Height 18.0 mm 3.04.805 3.03.572 3.03.573 3.03.574 3.03.580 12.5 mm 16.5 mm 21.5 mm 27.5 mm		VARIOmulti protective cap  Height 4.5 mm 4.03.801	
VARIOmulti Scan abutment  Height Ø 8.0 mm 4.5 mm 3.03.780		VARIOmulti Scan abutment, short  Height Ø 5.0 mm 5.0 mm 3.03.781	
LOCATOR® abutment Impression coping  Alu 4 pcs. 8505		LOCATOR®  20 pcs. 8515-20 Block-out spacer 20 pcs. 8514	

- NOTICE:**
- For information on customized CAD/CAM solutions, visit: www.thommenmedical.com.
 - In each case, the symbols correspond to required components, which can be ordered separately **I** – **VI**.
 - Rotation locked Rotation unlocked
 - *Item is supplied without screw.

Final restoration

EASY abutment

Collar	Cone	Height	
short 0.5 mm	4.0 mm	4.5 mm	4.03.703
short 0.5 mm	6.0 mm	6.5 mm	4.03.707
long 2.0 mm	4.0 mm	6.0 mm	4.03.713
long 2.0 mm	6.0 mm	8.0 mm	4.03.717

EASY abutment 20°

Collar	Height	
20° short 0.5 mm	6.5 mm	4.03.013
20° long 3.0 mm	9.0 mm	4.03.017

EASY abutment set

Collar	Cone	Height	
short 0.5 mm	4.0 mm	4.5 mm	1.04.703
short 0.5 mm	6.0 mm	6.5 mm	1.04.707
long 2.0 mm	4.0 mm	6.0 mm	1.04.713
long 2.0 mm	6.0 mm	8.0 mm	1.04.717

Set contents:

- EASY abutment
- abutment screw
- EASY impression coping
- EASY analog
- EASY temporary cap
- EASY burn-out cap, for crown, burn-out plastic
- EASY burn-out cap, for bridge, burn-out plastic

Burn-out cap

EASY burn-out cap

Height	Cone	
4.7 mm	4.0 mm	2.03.723
6.7 mm	6.0 mm	2.03.727
4.7 mm	4.0 mm	2.03.733*
6.7 mm	6.0 mm	2.03.737*

Analog

EASY analog

Cone	
4.0 mm	3.03.703
6.0 mm	3.03.707

Implant analog

Length	
22.0 mm	3.03.063
15.0 mm	3.03.093

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.089

VARIOflex set

Height	
12.0 mm	1.04.834
12.0 mm	1.04.839*

Titanium Base CAD/CAM Set

Height	
5.2 mm	1.04.754
5.2 mm	1.04.764*

Milling abutment for CAD/CAM Type II

Length	Ø	
15.0 mm	11.5 mm	1.04.409

VARIOeco burn-out cap

Height	
12.0 mm	2.03.794

VARIOflex burn-out cap

Height	
11.5 mm	2.03.844

Implant analog

Length	
22.0 mm	3.03.063
15.0 mm	3.03.093

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.089

VARIO gold abutment, NOA

Height	Cone	
12.7 mm	3.5 mm	2.03.413
12.7 mm	3.5 mm	2.03.403*

Implant analog for CAD/CAM

Length	
11.4 mm	3.03.089

Implant analog

Length	
22.0 mm	3.03.063
15.0 mm	3.03.093

VARIOmulti abutment

Collar height (h)	
1.5 mm	4.03.604S

VARIOmulti abutment angled

Angle	Collar height (h)	
17°	1.6 mm	4.03.304S
30°	1.2 mm	4.03.309S

VARIOmulti gold abutment, NOA

Height	Ø	
4.2/13.5 mm	4.8 mm	2.03.600

VARIOmulti titanium base for CAD/CAM

Height	Ø	
4.5 mm	4.8 mm	1.04.850

VARIOmulti titanium base for CAD/CAM, shortenable

Height	Ø	
9.0 mm	4.8 mm	1.04.851

VARIOmulti burn-out cap

Height	Ø	pcs.	
13.5 mm	4.8 mm	2	2.03.601 02

VARIOmulti analog

Height	Ø	
21.2 mm	4.8 mm	3.03.800

VARIOmulti analog for CAD/CAM

Height	Ø	
13.2 mm	4.8 mm	3.03.083

LOCATOR® abutment

Height	
1.0 mm	8881
2.0 mm	8882
3.0 mm	8883
4.0 mm	8884

RETAIN milling abutment

Height	
12.0 mm	4.03.423

LOCATOR®

For components, see:
thommenmedical.com
or product catalogue

Ø	Pcs.	
4.0 mm	4	8530
5.0 mm	4	8516

SPI®VARIOtemp

for temporary restorations

www.ifu-tm.com/THM61121

 Rotation locked
 Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0



Important Do not use abutments designed for single crowns with screw-retained bridge constructions, as axial divergences cannot be bridged.

 digital



 **VARIOtemp abutment set for crown**, incl. modeling screw, titanium/stainless steel

Height

12.0 mm

1.04.080

1.04.081

1.04.082

1.04.083

1.04.084

The abutment screw is included separately in the scope of delivery:

- 4.03.500 for PF 3.5

- 4.03.501 for PF 4.0 – 6.0

 digital



 **VARIOtemp abutment set for bridge**, incl. modeling screw, titanium/stainless steel

Height

12.0 mm

1.04.085

1.04.086

1.04.087

1.04.088

1.04.089

The abutment screw is included separately in the scope of delivery:

- 4.03.500 for PF 3.5

- 4.03.501 for PF 4.0 – 6.0

Abutment screw, 4-lobe, titanium alloy

Length

5.8 mm

4.03.500

7.2 mm

4.03.501

10.2 mm

4.03.502




Important Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

Titanium Base for CAD/CAM

for cemented and screw-retained restorations

www.ifu-tm.com/THM61123



Rotation locked
Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0



Important Do not use abutments designed for single crowns with screw-retained bridge constructions, as axial divergences cannot be bridged.



Titanium Base with hexagon for CAD/CAM, incl. abutment screw, titanium

Height

5.2 mm

1.04.750

1.04.751

1.04.752

1.04.753

1.04.754



Titanium Base bridge for CAD/CAM, incl. abutment screw, titanium

Height

5.2 mm

1.04.760

1.04.761

1.04.762

1.04.763

1.04.764

Abutment screw, 4-lobe, titanium alloy

Length

5.8 mm

4.03.500

7.2 mm

4.03.501

10.2 mm

4.03.502

Laboratory screw, stainless steel, 5 per pack (Q5)

Length

25.0 mm

3.03.515

3.03.516

25.0 mm

3.03.515 Q5

3.03.516 Q5

Laboratory cylindrical pin, PTFE, 5 per pack (Q5)

Length

70.0 mm

2.03.450 Q5

2.03.451 Q5



VARIOeco burn-out plastic cap, for Titanium Base, POM

Height

12.0 mm

2.03.790

2.03.791

2.03.792

2.03.793

2.03.794

Burn-out fabrication cap for the conventional fabrication of frameworks on the Titanium Base.



Important Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

Dynamic Titanium Base for CAD/CAM

www.dynamicabutment.com

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0



Important Do not use abutments designed for single crowns with screw-retained bridge constructions, as axial divergences cannot be bridged.



Dynamic Titanium Base for crown, incl. Dynamic abutment screw, titanium alloy



Height

4.0 mm

31.311.113.01-2

31.312.114.01-2

31.313.115.01-2

31.314.116.01-2

The dynamic abutment screw is included separately in the scope of delivery:

- 41.314.069.01-2 for PF 3.5

- 41.316.076.02-2 for PF 4.0 – 5.0



Dynamic Titanium Base for bridge, incl. Dynamic abutment screw, titanium alloy



Height

4.0 mm

31.321.113.01-2

31.322.114.01-2

31.323.115.01-2

31.324.116.01-2

The dynamic abutment screw is included separately in the scope of delivery:

- 41.314.069.01-2 for PF 3.5

- 41.316.076.02-2 for PF 4.0 – 5.0



Dynamic Titanium Base for crown, shortenable, titanium alloy



Height

9.0 mm

31.310.113.21-2

31.312.114.21-2

31.313.115.21-2

31.314.116.21-2

The dynamic abutment screw is included separately in the scope of delivery:

- 41.314.069.01-2 for PF 3.5

- 41.316.076.02-2 for PF 4.0 – 5.0



Dynamic Titanium Base for bridge, shortenable, titanium alloy



Height

9.0 mm

31.320.113.21-2

31.322.114.21-2

31.323.115.21-2

31.324.116.21-2

The dynamic abutment screw is included separately in the scope of delivery:

- 41.314.069.01-2 for PF 3.5

- 41.316.076.02-2 for PF 4.0 – 5.0

Dynamic abutment screw, titanium alloy



Length

6.9 mm

41.314.069.01-2

7.6 mm

41.316.076.02-2

Dynamic screwdriver, stainless steel



Length

18.0 mm

43.618.201.01-2

24.0 mm

43.624.201.01-2

32.0 mm

43.632.201.01-2

All latch-type instruments can be utilized with the MONO insertion device, short [art. no. 3.03.162], and with the MONO torque ratchet [art. no. 3.03.160].



Important Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

Milling abutment for CAD/CAM Type II

for customized abutments

www.ifu-tm.com/THM61137

 Rotation locked
 Rotation unlocked

PF 3.5	PF 4.0	PF 4.5	PF 5.0	PF 6.0
--------	--------	--------	--------	--------



 **Milling abutment for CAD/CAM Type II, incl. abutment screw, titanium**

Length	Ø					
15.0 mm	8.0 mm	1.04.401				
15.0 mm	11.5 mm		1.04.403	1.04.405	1.04.407	1.04.409

Abutment screw, 4-lobe, titanium alloy



Length				
5.8 mm	4.03.500			
7.2 mm		4.03.501		
10.2 mm		4.03.502		


The milling abutments for CAD/CAM type II are compatible with Medentika® PreFace abutment holders, which are available for a large number of milling machines. You can find an overview of compatible milling machines at: www.thommenmedical.com.

 **Important** Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

SPI®VARIOflex

for cemented and screw-retained restorations

www.ifu-tm.com/THM61119



PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0



Important Do not use abutments designed for single crowns with screw-retained bridge constructions, as axial divergences cannot be bridged.



VARIOflex abutment set for crown, titanium/POM



Height

12.0 mm

1.04.830

1.04.831

1.04.832

1.04.833

1.04.834

Set contents:

- 1 abutment
- 1 abutment screw
- 1 burn-out cap



VARIOflex abutment set for bridge, titanium/POM



Height

12.0 mm

1.04.835

1.04.836

1.04.837

1.04.838

1.04.839

Set contents:

- 1 abutment
- 1 abutment screw
- 1 burn-out cap

VARIOflex burn-out plastic cap, POM



Height

11.5 mm

2.03.840

2.03.841

2.03.842

2.03.843

2.03.844

Laboratory cylindrical pin, PTFE, 5 per pack (Q5)



Length

70.0 mm

2.03.450 Q5

2.03.451 Q5




Important Thommen Medical provides the corresponding CAD libraries. You can find an overview at: www.thommenmedical.com.

SPI®VARIOmulti



for screw-retained restorations

www.ifu-tm.com/THM61118

VARIOmulti abutment



VARIOmulti abutment angled



Rotation locked
Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

VARIOmulti abutment, with handle, titanium, sterile

Collar height (h)



0.8 mm

4.03.600S

4.03.601S

4.03.602S

4.03.603S

4.03.604S

1.5 mm

2.0 mm

4.03.605S

4.03.606S

4.03.607S

4.03.608S

3.0 mm

4.03.610S

4.03.611S

4.03.612S

4.03.613S

VARIOmulti abutment angled, with handle, abutment screw, titanium, sterile

Angle Collar height (h)



17°

1.6 mm

4.03.300S

4.03.301S

4.03.302S

4.03.303S

4.03.304S

17°

2.5 mm

4.03.310S

4.03.311S

4.03.312S

4.03.313S

30°

1.2 mm

4.03.305S

4.03.306S

4.03.307S

4.03.308S

4.03.309S

30°

2.5 mm

4.03.315S

4.03.316S

4.03.317S

4.03.318S

Abutment screw, 4-lobe, titanium alloy

Length



5.8 mm

4.03.500

7.2 mm

4.03.501

Occlusal screw, 4-lobe, titanium alloy

Length



3.5 mm

4.03.507

Bone contouring instrument, reusable, stainless steel

Length



29.0 mm

3.03.671

3.03.673

3.03.675

3.03.677

3.03.679

For VARIOmulti abutment.

Bone contouring instrument+, reusable, stainless steel

Length



29.0 mm

3.03.670

3.03.672

3.03.674

3.03.676

For VARIOmulti abutment angled.

-  Rotation locked
 Rotation unlocked

 VARIOmulti protective cap, titanium



Ø	Height	
5.3 mm	4.5 mm	4.03.801

 VARIOmulti temporary cap, incl. fabrication screw, titanium/stainless steel



Ø	Height	
5.2 mm	15.0 mm	3.03.804

The occlusal screw is included separately in the scope of delivery:
- 4.03.507

Fabrication screw for VARIOmulti temporary cap, 4-lobe, stainless steel,
4 per pack (Q4)



Length	
19.3 mm	3.03.598 Q4

 VARIOmulti impression coping*, titanium



Ø	Height	
5.3 mm	18.0 mm	3.04.805

* Use the yellow screws for impression copings PF 3.5 (art. nos. 3.03.572, 3.03.573, 3.03.574, 3.03.580) to attach the VARIOmulti impression copings (see page 17).

 VARIOmulti analog, stainless steel



Ø	Height	
4.8 mm	21.2 mm	3.03.800

VARIOmulti analog for CAD/CAM, titanium



Ø	Length	
4.8 mm	13.2 mm	3.03.083

VARIOmulti analogs for CAD/CAM are used for 3D-printed models.

Insertion device for VARIOmulti analog for CAD/CAM, stainless steel



Length	
35.8 mm	3.03.157

 Rotation locked
 Rotation unlocked



 **VARIOmulti scan abutment**, titanium, surface treated, 4-lobe



Ø	Height	
4.5 mm	8.0 mm	3.03.780



 **VARIOmulti scan abutment, short**, titanium, surface treated, 4-lobe



Ø	Height	
5.0 mm	5.0 mm	3.03.781

No additional screws are necessary for the attachment of VARIOmulti scan abutments.
 The VARIOmulti scan abutments should be used as follows:

- Laboratory scan: long scan abutment (3.03.780)
- Intraoral scan with neighboring teeth: long scan abutment (3.03.780)
- Intraoral scan without neighboring teeth: short scan abutment (3.03.781), as long as the laser marking projects above the gingiva.



VARIOmulti titanium base for CAD/CAM, incl. occlusal screw, titanium/titanium alloy



Ø	Height	
4.8 mm	4.5 mm	1.04.850



VARIOmulti titanium base for CAD/CAM, customizable, incl. occlusal screw, titanium/titanium alloy



Ø	Height	
4.8 mm	9.0 mm	1.04.851

 **VARIOmulti gold cap**, incl. burn-out cylinder, NOA/burn-out plastic



Ø	Height	
4.8 mm	4.2/13.5 mm	2.03.600

The occlusal screw is included separately in the scope of delivery:

- 4.03.507

 **VARIOmulti burn-out cap**, plastic, 2 per pack (Q2)



Ø	Height	
4.8 mm	13.5 mm	2.03.601 Q2

The occlusal screw is included separately in the scope of delivery:

- 4.03.507

Positioning handle for angled VARIO and VARIOmulti abutments, stainless steel

Ø	Length	
4.0 mm	25.0 mm	3.03.521

VARIO/VARIOmulti reamer for base *, tungsten carbide

Length	
16.0 mm	3.03.420

* The VARIO reamer for base (art. no. 3.03.420) can also be used for processing the VARIOmulti gold cap (art. no. 2.03.600). For correct reworking of the base, use the VARIOmulti reamer for base with the associated VARIO guide pin (art. no. 3.03.424).

VARIO guide pin for VARIOmulti reamer, stainless steel

Length	
15.0 mm	3.03.424

Gauge for VARIO and VARIOmulti reamers for screw channel, for laboratory use, stainless steel

3.03.430

For correct reworking of the screw channel, use the VARIO (art. nos. 3.03.435, 3.03.436) and VARIOmulti (art. no. 3.03.437) reamer for screw channel.

VARIOmulti reamer for screw channel, tungsten carbide, stainless steel

Length	
40.0 mm	3.03.437

For correct reworking of the screw seat, use the VARIOmulti reamer for screw channel with the associated gauge (art. no. 3.03.430). A MONO insertion device (art. nos. 3.03.162, 3.03.163) is also required when using the reamer.

MONO insertion device, stainless steel/PEEK


Length	short *	long
	15.4 mm	25.8 mm
	3.03.162	3.03.163

* All latch-type instruments can be utilized with the MONO insertion device, short (art. no. 3.03.162).

SPI®VARIO

for screw-retained restorations

www.ifu-tm.com/THM61134, www.ifu-tm.com/THM61136



Rotation locked
Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0



Important Do not use abutments designed for single crowns with screw-retained bridge constructions, as axial divergences cannot be bridged.

VARIO gold abutment for crown, NOA/burn-out plastic



Height (H) Cone (h)

12.7 mm 3.5 mm

2.03.410

2.03.414

2.03.411

2.03.412

2.03.413

The abutment screw is included separately in the scope of delivery:

- 4.03.500 for PF 3.5

- 4.03.501 for PF 4.0 – 6.0

VARIO gold abutment for bridge, NOA/burn-out plastic



Height (H) Cone (h)

12.7 mm 3.5 mm

2.03.400

2.03.404

2.03.401

2.03.402

2.03.403

The abutment screw is included separately in the scope of delivery:

- 4.03.500 for PF 3.5

- 4.03.501 for PF 4.0 – 6.0

Abutment screw, 4-lobe, titanium alloy



Length

5.8 mm

4.03.500


7.2 mm

4.03.501

10.2 mm

4.03.502

VARIO abutment 17° set



Height Shoulder height

5.6 mm 0.5 mm

Type A

1.03.160

1.03.161

1.03.162

1.03.163

Type B

1.03.180

1.03.181

1.03.182

1.03.183

Set contents:

· 1 VARIO abutment 17° (titanium)

· 1 VARIO 17° gold screw seat

· 1 occlusal screw

· 1 abutment screw

VARIO abutments 17° have a Type A (0°) or B (30°) hexagon. They can therefore be aligned in 30° increments.

VARIO 17° gold screw seat, NOA/burn-out plastic (fits all platform sizes)



Height Ø

2.0/11.3 mm 2.9 mm

2.03.610

Occlusal screw, 4-lobe, titanium alloy



Length

3.5 mm

4.03.507

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Positioning handle for angled VARIO and VARIOmulti abutments, stainless steelLength $\varnothing$

25.0 mm 4.0 mm

3.03.521**VARIO/VARIOmulti reamer for base *, tungsten carbide**

Length

16.0 mm

3.03.420**3.03.421**

* The VARIO reamer for base [art. no. 3.03.420] can also be used for processing the VARIOmulti gold cap [art. no. 2.03.600]. For correct reworking of the base, use the VARIOmulti reamer for base with the associated VARIO guide pin [art. no. 3.03.424].

VARIO guide pin for VARIO reamer, stainless steel

Length

12.5 mm

3.03.425**3.03.423**

15.0 mm

3.03.424**Gauge for VARIO and VARIOmulti reamers for screw channel, for laboratory use, stainless steel****3.03.430**

For correct reworking of the screw channel, use the VARIO [art. nos. 3.03.435, 3.03.436] and VARIOmulti [art. no. 3.03.437] reamer for screw channel.

VARIO reamer for screw channel, tungsten carbide, stainless steel

Length

44.0 mm

3.03.435**3.03.436**

For correct reworking of the screw seat, use the VARIOmulti reamer for screw channel [art. No. 3.03.435] with the associated gauge [art. no. 3.03.430]. A MONO insertion device [art. nos. 3.03.162, 3.03.163] is also required when using the reamer.

MONO insertion device, stainless steel/PEEK

Length

short*

15.4 mm

long

25.8 mm


3.03.162**3.03.163**

* All latch-type instruments can be utilized with the MONO insertion device, short [art. no. 3.03.162].

SPI®EASY

for cemented restorations

www.ifu-tm.com/THM61115



PF 3.5	PF 4.0	PF 4.5	PF 5.0	PF 6.0
--------	--------	--------	--------	--------

EASY abutment set, titanium

Collar	Cone	Height					
short 0.5 mm	4.0 mm	4.5 mm	1.04.700	1.04.708	1.04.701	1.04.702	1.04.703
short 0.5 mm	6.0 mm	6.5 mm	1.04.704	1.04.709	1.04.705	1.04.706	1.04.707
long 2.0 mm	4.0 mm	6.0 mm	1.04.710	1.04.718	1.04.711	1.04.712	1.04.713
long 2.0 mm	6.0 mm	8.0 mm	1.04.714	1.04.719	1.04.715	1.04.716	1.04.717
extra long 4.0 mm	6.0 mm	10.0 mm	1.04.734	1.04.739	1.04.735	1.04.736	



Set contents:

- 1 EASY abutment
- 1 abutment screw
- 1 EASY impression coping
- 1 EASY analog
- 1 EASY temporary cap
- 1 EASY burn-out cap, for crowns
- 1 EASY burn-out cap, for bridges

EASY abutments are also available both individually and in sets with separate article numbers for all platforms. Angled EASY abutments and EASY Abutments e.p. (emergency profile) can only be ordered individually.

EASY abutment, titanium

	Collar	Cone	Height					
	short 0.5 mm	4.0 mm	4.5 mm	4.03.700	4.03.708	4.03.701	4.03.702	4.03.703
	short 0.5 mm	6.0 mm	6.5 mm	4.03.704	4.03.709	4.03.705	4.03.706	4.03.707
	long 2.0 mm	4.0 mm	6.0 mm	4.03.710	4.03.718	4.03.711	4.03.712	4.03.713
	long 2.0 mm	6.0 mm	8.0 mm	4.03.714	4.03.719	4.03.715	4.03.716	4.03.717
	extra long 4.0 mm	6.0 mm	10.0 mm	4.03.734	4.03.739	4.03.735	4.03.736	
	20°/short 0.5 mm		6.5 mm	4.03.010	4.03.018	4.03.011	4.03.012	4.03.013
	20°/long 3.0 mm		8.0 mm	4.03.014				
	20°/long 3.0 mm		9.0 mm		4.03.019	4.03.015	4.03.016	4.03.017

The abutment screw is included separately in the scope of delivery:

- 4.03.500 for PF 3.5
- 4.03.501 for PF 4.0 – 6.0

Abutment screw, 4-lobe, titanium alloy

	Length				
	5.8 mm	4.03.500			
	7.2 mm			4.03.501	
	10.2 mm			4.03.502	

 Rotation locked
 Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

EASY impression coping, plastic



Height	Cone					
9.5 mm	4.0 mm	2.03.700	2.03.708	2.03.701	2.03.702	2.03.703
11.5 mm	6.0 mm	2.03.704	2.03.709	2.03.705	2.03.706	2.03.707

Not suitable for EASY abutment 20°.

EASY temporary cap, PMMA-based plastic



Height	Cone					
5.0 mm	4.0 mm	2.03.740	2.03.748	2.03.741	2.03.742	2.03.743
7.0 mm	6.0 mm	2.03.744	2.03.749	2.03.745	2.03.746	2.03.747

EASY analog, stainless steel



Height	Cone					
14.0 mm	4.0 mm	3.03.700	3.03.708	3.03.701	3.03.702	3.03.703
16.0 mm	6.0 mm	3.03.704	3.03.709	3.03.705	3.03.706	3.03.707

EASY burn-out cap, for crown, burn-out plastic



Height	Cone					
4.7 mm	4.0 mm	2.03.720	2.03.728	2.03.721	2.03.722	2.03.723
6.7 mm	6.0 mm	2.03.724	2.03.729	2.03.725	2.03.726	2.03.727

EASY burn-out cap, for bridge, burn-out plastic



Height	Cone					
4.7 mm	4.0 mm	2.03.730	2.03.738	2.03.731	2.03.732	2.03.733
6.7 mm	6.0 mm	2.03.734	2.03.739	2.03.735	2.03.736	2.03.737

SPI®EASY emergence profile

for cemented restorations

Rotation locked

Rotation unlocked

PF 4.0

PF 4.5

PF 5.0

EASY abutment e.p., titanium

Collar height for all EASY abutments e.p.: 3.0 mm




PF / PF e.p.	Cone (h)	Height (H)			
4.0 / 4.5	4.0 mm	7.0 mm	4.03.728		
4.0 / 4.5	6.0 mm	9.0 mm	4.03.729		
4.5 / 5.0	4.0 mm	7.0 mm		4.03.721	
4.5 / 5.0	6.0 mm	9.0 mm		4.03.725	
5.0 / 6.0	4.0 mm	7.0 mm			4.03.722
5.0 / 6.0	6.0 mm	9.0 mm			4.03.726

The abutment screw is included separately in the scope of delivery:
- 4.03.501 for PF 4.0 – 6.0

!

Important If using EASY abutments emergence profile (e.p.) always use prefabricated EASY accessory components (impression copings, temporary caps, analogs, burn-out caps) of the **next larger platform diameter**.



 Rotation locked
 Rotation unlocked

PF 4.5

PF 5.0

PF 6.0



EASY impression coping, plastic

Height	Cone (h)			
9.5 mm	4.0 mm	2.03.701	2.03.702	2.03.703
11.5 mm	6.0 mm	2.03.705	2.03.706	2.03.707

Not suitable for EASY abutment 20°.



EASY temporary cap, PMMA-based plastic

Height	Cone (h)			
5.0 mm	4.0 mm	2.03.741	2.03.742	2.03.743
7.0 mm	6.0 mm	2.03.745	2.03.746	2.03.747



EASY analog, stainless steel

Height	Cone (h)			
14.0 mm	4.0 mm	3.03.701	3.03.702	3.03.703
16.0 mm	6.0 mm	3.03.705	3.03.706	3.03.707



EASY burn-out cap, for crown, burn-out plastic

Height	Cone (h)			
4.7 mm	4.0 mm	2.03.721	2.03.722	2.03.723
6.7 mm	6.0 mm	2.03.725	2.03.726	2.03.727



EASY burn-out cap, for bridge, burn-out plastic

Height	Cone (h)			
4.7 mm	4.0 mm	2.03.731	2.03.732	2.03.733
6.7 mm	6.0 mm	2.03.735	2.03.736	2.03.737




Abutment screw, 4-lobe, titanium alloy

Length	
7.2 mm	4.03.501
10.2 mm	4.03.502

SPI®ART

for esthetic restorations, cemented and screw-retained

www.ifu-tm.com/THM61135



PF 3.5

PF 4.0

PF 4.5

PF 5.0



ART grinding cylinder abutment, incl. abutment screw, zirconium/titanium alloy

Height

12.0 mm

1.03.649

1.03.650

1.03.651

1.03.652



ART abutment, incl. abutment screw, zirconium/titanium alloy

PF / PF e.p. Height (H) Cone (h)

3.5 / 4.5 9.0 mm 6.0 mm

1.03.623

4.0 / 4.5 9.0 mm 6.0 mm

1.03.624

4.5 / 5.0 9.0 mm 6.0 mm

1.03.625


5.0 / 6.0 9.0 mm 6.0 mm

1.03.626




Important When using ART abutments always use prefabricated EASY accessory components (impression copings, temporary caps, analogs) of the **next larger platform diameter**.

An exception is the platform 3.5, which has a prosthetic base (e.p.) of 4.5.



Ø base proth. (e.p.)



Ø implant platform

 Rotation locked
 Rotation unlocked

PF 4.5

PF 5.0

PF 6.0



 EASY impression coping, plastic

Height	Cone (h)			
11.5 mm	6.0 mm	2.03.705	2.03.706	2.03.707



 EASY temporary cap, PMMA-based plastic

Height	Cone (h)			
7.0 mm	6.0 mm	2.03.745	2.03.746	2.03.747



 EASY analog, stainless steel

Height	Cone (h)			
16.0 mm	6.0 mm	3.03.705	3.03.706	3.03.707

SPI®RETAIN

for hybrid removable dentures

www.ifu-tm.com/THM61128

 Rotation locked
 Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Retentive anchor, titanium



Height

1.8 mm short

4.03.048

4.03.040

4.03.042

3.0 mm long

4.03.049

4.03.041

4.03.043

Thommen Medical retentive anchors have a spherical diameter of 2.25 mm and are compatible with all matrices of this geometry (e.g. Dalbo®-PLUS, Tima®, Ecco®, Pro-Snap®, etc.).

Retentive anchor analog, titanium



Length

13.0 mm

3.03.033

Thommen Medical retentive anchors have a spherical diameter of 2.25 mm and are compatible with all matrices of this geometry (e.g. Dalbo®-PLUS, Tima®, Ecco®, Pro-Snap®, etc.).

MONO insertion device for retentive anchor, stainless steel/PEEK



Length Ø

26.0 mm 8.5 mm

3.03.169

Milling abutment, titanium



Height

11.0 mm

4.03.420

12.0 mm

4.03.428


4.03.421

4.03.422

4.03.423

Abutment screw is not included in delivery. Always use new abutment screws for the final insertion of abutments.

Abutment screw, 4-lobe, titanium alloy



Length

5.8 mm

4.03.500

7.2 mm

4.03.501

10.2 mm

4.03.502

 Rotation locked
 Rotation unlocked

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

 Bar abutment, titanium



Height

5.5 mm

4.03.380

4.03.388

4.03.381

4.03.382

Abutment screw is not included in delivery. Always use new abutment screws for the final insertion of abutments. Abutment screw 4.03.502 is not compatible with bar abutment.

 Gold cap for bar, gold alloy



Height

4.7 mm

2.03.335

 Titanium coping for bar, titanium



Height

4.7 mm

4.03.070

Occlusal screw for bar, 4-lobe, titanium alloy



Length

4.3 mm

4.03.506

 Solder pin for bar, stainless steel



Length

13.5 mm

3.03.151

 Impression coping for bar, aluminum, anodized/plastic



Height

5.0 mm

Ø

6.0 mm

3.03.101

 Bar analog, titanium



Length

21.5 mm

Ø


4.0 mm

3.03.105

ZEST® LOCATOR®

implant attachment system

www.zestdent.com



PF 3.5


PF 4.0

PF 4.5

PF 5.0

PF 6.0

LOCATOR® abutment, titanium alloy



Collar height

0.73 mm	8875				
1.0 mm		8461	8786	8792	8881
2.0 mm	8876	8462	8787	8793	8882
3.0 mm	8877	8463	8788	8794	8883
4.0 mm	8878	8464	8789	8795	8884
5.0 mm	8879*	8465	8790	8796	
6.0 mm	8880*	8466	8791	8797	

LOCATOR® abutment and collar for VARIOmulti, 2 per pack



Collar height

3.0 mm	8909-2
--------	--------

LOCATOR® Laborset, Packung enthält 2 Sets, Titan/Nylon



8519-2

Contents per set:

- 1 LOCATOR® cap with male processing, black (8515)
- 1 LOCATOR® block-out spacer (8514)
- 1 LOCATOR® male replacement, clear (8524)
- 1 LOCATOR® male replacement, pink (8527)
- 1 LOCATOR® male replacement, blue (8529)
- 1 LOCATOR® matrix housing

LOCATOR® laboratory set, for extended range, pack contains 2 sets, titanium/nylon



8540-2

Contents per set:

- 1 LOCATOR® cap with male processing, black (85152)
- 1 LOCATOR® block-out spacer (8514)
- 1 LOCATOR® male replacement, green (8547)
- 1 LOCATOR® male replacement, orange (8915)
- 1 LOCATOR® male replacement, red (8548)
- 1 LOCATOR® matrix housing

LOCATOR® male replacement, 4 per pack, nylon




Retention	Color	
High	clear	8524
Medium	pink	8527
Low	blue	8529

LOCATOR® male replacement, for extended range, 4 per pack, nylon



Retention	Color	
High	green	8547
Medium	orange	8915
Low	red	8548



LOCATOR® core tool, stainless steel



8393

LOCATOR® impression coping, 4 per pack, aluminum/LDPE



8505

LOCATOR® analog, 4 per pack, aluminum



Ø

4.0 mm (preferably used with PF 3.5, 4.0 and 4.5 mm)

8530

5.0 mm (preferably used with PF 5.0 and 6.0 mm)

8516

LOCATOR® parallel posts, 4 per pack, LDPE



8517

LOCATOR® angle measurement guide, stainless steel



Width Height

50.0 mm 15.0 mm

9530

LOCATOR® male processing, black, 20 per pack, nylon



8515-20

LOCATOR® block-out spacer, 20 per pack, Teflon®



8514

LOCATOR® insert for hand piece and for short MONO insertion device, Stainless steel



Length

23.0 mm

8913

29.0 mm

8914

Instruments

for mechanical operation

www.ifu-tm.com/THM61141

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Adapter for hand piece, one-piece, stainless steel



Length

24.0 mm

3.03.248

3.03.251

3.03.241

Adapter for hand piece, stainless steel



Length

18.0 mm

3.03.240



28.0 mm

3.03.249

Screwdriver for hand piece, 4-lobe, stainless steel



	extra short	short	long	extra long
Length	17.0 mm	22.0 mm	28.0 mm	38.0 mm
Shaft length	4.0 mm	8.5 mm	14.5 mm	24.5 mm
	3.03.500	3.03.501	3.03.502	3.03.503

All latch-type instruments can be utilized with the MONO insertion device, short (art. no. 3.03.162), and with the MONO torque ratchet (art. no. 3.03.160).

Instruments

for manual operation

www.ifu-tm.com/THM61141

MONO torque ratchet, titanium alloy



Length

110.0 mm

3.03.160

The MONO torque ratchet ensures a precise control of the torque applied. Please see the overview of torque values on page 75.

MONO guide key, stainless steel



Length

94.7 mm

3.03.203

MONO circlip, viton, 2 per pack (Q2)



2.03.170 Q2



MONO insertion device, stainless steel/PEEK

	short *	long
Length	15.4 mm	25.8 mm
	3.03.162	3.03.163

* All latch-type instruments can be utilized with the MONO insertion device, short (art. no. 3.03.162), and the MONO torque ratchet (art. no. 3.03.160).



MONO screw driver, 4-lobe, stainless steel/PEEK

	extra short *	short	long
Length	14.5 mm	22.2 mm	28.2 mm
Shaft length	5.1 mm	10.3 mm	16.3 mm
	3.03.165	3.03.166	3.03.167

* The MONO screwdriver extra short is made of stainless steel only, without PEEK finger rest.



Handle for dental laboratory, brass/steel

Length	
120.0 mm	3.03.250



Insertion device for implant analog for CAD/CAM, stainless steel

	PF 3.5	PF 4.0	PF 4.5	PF 5.0	PF 6.0
Length					
35.0 mm	3.03.158				
35.0 mm		3.03.159			



Insertion device for VARIOmulti analog for CAD/CAM, stainless steel

Length	
35.8 mm	3.03.157

Instruments for guided surgery

www.ifu-tm.com/THM61144

Initial drill, guided, stainless steel



Length	Ø 2.0 mm
28.5 mm L 4.0	3.04.110

VECTOdrill™ pilot drill and twist drill, guided, stainless steel



Diameter	Implant length	L 6.5	L 8.0	L 9.5	L 11.0	L 12.5
	Drill length	31.5 mm	33.0 mm	34.5 mm	36.0 mm	37.5 mm
Ø 2.0 mm		3.04.111	3.04.112	3.04.113	3.04.114	3.04.115
Ø 2.8 mm		3.04.121	3.04.122	3.04.123	3.04.124	3.04.125
Ø 3.5 mm		3.04.131	3.04.132	3.04.133	3.04.134	3.04.135

Profile drill, guided, stainless steel



PF	Implant type	CONTACT MC	CONTACT RC	ELEMENT MC
	Drill length	34.0 mm	32.5 mm	30.5 mm
PF 3.5		3.04.171	3.04.161	3.04.151
PF 4.0		3.04.172	3.04.162	3.04.152
PF 4.5		3.04.173	3.04.163	3.04.153

Adapter, guided, stainless steel



Length
25.5 mm

3.04.090

Guiding sleeve, stainless steel



Length	Ø 4.8 mm
5.0 mm	3.04.080 Q4

Seating instrument for guiding sleeve, stainless steel



Length	Ø 4.8 mm
28.5 mm	3.04.100

Guiding sleeve for VECTOdrill™ pilot drill, stainless steel, 4 per pack (Q4)



Length	Internal Ø
6.0 mm	2.0 mm

3.03.141 Q4

The guiding sleeve for **VECTOdrill™ pilot drill** can only be used with the **VECTOdrill™ pilot drill**.

Adapter for hand piece, one-piece, stainless steel



Length			
24.0 mm	3.03.248	3.03.251	3.03.241

Adapter for hand piece can be optionally be used for implant Insertion for non-guided surgery. The one-piece adapter for hand piece engages directly into the implant hexagon. You can find standard instruments for guided surgery at: www.ifu-tm.com/THM61144.

Cassettes

www.ifu-tm.com/THM61131



Surgical cassette, for mechanical cleaning, stainless steel/aluminum

Length × width × height
276.0 × 176.0 × 59.5 mm

1.03.030



Surgical cassette for guided surgery, PF 3.5 – PF 4.5 / L6.5 - L12.5 mm, for mechanical cleaning,

Length × width × height
276.0 × 176.0 × 59.5 mm

1.04.020



consisting of 2 instrument holders, size S

8.03.090 Q2

consisting of 1 instrument holder, size M

8.03.091

Size S is compatible with surgical cassette for guided surgery 1.04.020 and sizes S and M are compatible with surgical cassette 1.03.030.



Container for surgical cassette, incl. identification plate Thommen Medical, aluminum alloy

Length × width × height
312.0 × 189.0 × 83.0 mm


ER510.080E

Consisting of article ER505.080E and ER500.010E

Single-use paper filter, 100 per pack

Length × width
118.0 × 235.0 mm

ER802.000N



Permanent filter, 1200 sterilization cycles, PTFE

Length × width
95.0 × 215.0 mm

ER802.020

ER802.000N and ER802.020 are compatible with Container ER510.080E.
Not available in the USA.



Prosthetic cassette, incl. screw organizer, thermoplastic, sterilizable

Length × width × height
190.0 × 140.0 × 58.0 mm

1.03.022



Screw organizer for prosthetic cassette, plastic, sterilizable

Length × width × height
56.0 × 47.0 × 33.5 mm

8.03.019



Ultrasonic cleaning cassette, plastic

Length × width × height
160.0 × 72.0 × 28.0 mm

8.03.059



Silicone holder set, silicone, for surgical and prosthetic cassettes,
consisting of four different sizes, 2 pieces each, (grey)

1.03.056

Suitable for items 1.03.022 and 1.03.016.

Explantation instruments

www.ifu-tm.com/THM61152

PF 3.5

PF 4.0

PF 4.5

PF 5.0

PF 6.0

Explantation drill for ELEMENT implants, stainless steel

Length						
	31.0 mm *	External Ø	4.3 mm	5.0 mm	6.3 mm	7.3 mm
		internal Ø	3.8 mm	4.5 mm	5.3 mm	6.3 mm
	37.0 mm	short	3.03.303	3.03.304	3.03.305	3.03.306
		long	3.03.300	3.03.301	3.03.302	

Explantation drill for CONTACT implants, stainless steel

Length					
	31.0 mm *	External Ø	4.3 mm	5.0 mm	6.3 mm
		internal Ø	3.8 mm	4.5 mm	5.3 mm
	37.0 mm	short	3.03.303	3.03.304	3.03.305
		long	3.03.300	3.03.301	3.03.302

Guiding cylinder for ELEMENT and CONTACT implants, stainless steel

Length						
	3.0 mm	External Ø	3.7 mm	4.4 mm	4.4 mm	5.2 mm
		ELEMENT	3.03.308	3.03.307	3.03.309	3.03.310
	3.0 mm	CONTACT	3.03.308	3.03.307	3.03.309	3.03.310

Use abutment screws art. nos. 4.03.500 (PF B 3.5 mm) and 4.03.501 (PF 4.0–6.0) to attach guiding cylinders on the implant. Abutment screw is not included in the delivery.



*** Important** Only use explantation drills 31.0 mm in length for the following implant lengths:

ELEMENT	6.5–12.5 mm
CONTACT	6.5–12.5 mm
CONTACT PF 6.0	9.5–11.0 mm



Important Explantation drills for ONETIME and DIRECT Implants are still available. To purchase, please contact your country representative.

Index by article numbers

1.03	Prosthetic cassette, incl. screw organizer	
1.03.022	length 190.0 mm, width 140.0 mm, height 58.0 mm	57
	Surgical cassette, for mechanical cleaning	
1.03.030	length 274.8 mm, width 176.0 mm, height 63.6 mm	57
1.03.056	Silicone holder set, for surgical and prosthetic cassettes	57
	VARIO abutment 17° set	
1.03.160	Type A, PF 3.5, height 5.6 mm, shoulder height 0.5 mm	41
1.03.161	Type A, PF 4.0, height 5.6 mm, shoulder height 0.5 mm	41
1.03.162	Type A, PF 4.5, height 5.6 mm, shoulder height 0.5 mm	41
1.03.163	Type A, PF 5.0, height 5.6 mm, shoulder height 0.5 mm	41
1.03.180	Type B, PF 3.5, height 5.6 mm, shoulder height 0.5 mm	41
1.03.181	Type B, PF 4.0, height 5.6 mm, shoulder height 0.5 mm	41
1.03.182	Type B, PF 4.5, height 5.6 mm, shoulder height 0.5 mm	41
1.03.183	Type B, PF 5.0, height 5.6 mm, shoulder height 0.5 mm	41
	ART abutment, incl. abutment screw	
1.03.623	PF 3.5/4.5, cone 6.0 mm, height 9.0 mm	47
1.03.624	PF 4.0/4.5, cone 6.0 mm, height 9.0 mm	47
1.03.625	PF 4.5/5.0, cone 6.0 mm, height 9.0 mm	47
1.03.626	PF 5.0/6.0, cone 6.0 mm, height 9.0 mm	47
	ART grinding cylinder-abutment, incl. abutment screw	
1.03.649	PF 3.5, height 12.0 mm	47
1.03.650	PF 4.0, height 12.0 mm	47
1.03.651	PF 4.5, height 12.0 mm	47
1.03.652	PF 5.0, height 12.0 mm	47

1.04	Surgical cassette for guided surgery, for mechanical cleaning	57
	VARIOtemp abutment set for crowns	
1.04.080	PF 3.5, height 12.0 mm	32
1.04.081	PF 4.0, height 12.0 mm	32
1.04.082	PF 4.5, height 12.0 mm	32
1.04.083	PF 5.0, height 12.0 mm	32
1.04.084	PF 6.0, height 12.0 mm	32
	VARIOtemp abutment set for bridges	
1.04.085	PF 3.5, height 12.0 mm	32
1.04.086	PF 4.0, height 12.0 mm	32
1.04.087	PF 4.5, height 12.0 mm	32
1.04.088	PF 5.0, height 12.0 mm	32
1.04.089	PF 6.0, height 12.0 mm	32
1.04.138	VARIOunite abutment PF 3.0 for crown	12
	Milling abutment for CAD/CAM Type II, incl. abutment screw	
1.04.401	PF 3.5, length 15.0 mm, Ø 8.0 mm	35
1.04.403	PF 4.0, length 15.0 mm, Ø 11.5 mm	35
1.04.405	PF 4.5, length 15.0 mm, Ø 11.5 mm	35
1.04.407	PF 5.0, length 15.0 mm, Ø 11.5 mm	35
1.04.409	PF 6.0, length 15.0 mm, Ø 11.5 mm	35
	EASY abutment set, short	
1.04.700	PF 3.5, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	43
1.04.701	PF 4.5, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	43
1.04.702	PF 5.0, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	43
1.04.703	PF 6.0, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	43
1.04.704	PF 3.5, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	43
1.04.705	PF 4.5, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	43
1.04.706	PF 5.0, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	43
1.04.707	PF 6.0, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	43
1.04.708	PF 4.0, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	43
1.04.709	PF 4.0, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	43
	EASY abutment set, long	
1.04.710	PF 3.5, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	43
1.04.711	PF 4.5, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	43
1.04.712	PF 5.0, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	43
1.04.713	PF 6.0, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	43
1.04.714	PF 3.5, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	43
1.04.715	PF 4.5, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	43
1.04.716	PF 5.0, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	43
1.04.717	PF 6.0, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	43
1.04.718	PF 4.0, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	43
1.04.719	PF 4.0, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	43
	EASY abutment set, extra long	
1.04.734	PF 3.5, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	43
1.04.735	PF 4.5, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	43
1.04.736	PF 5.0, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	43
1.04.739	PF 4.0, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	43
	Titanium base with hexagon for CAD/CAM, incl. abutment screw	
1.04.750	PF 3.5, height 5.2 mm	33
1.04.751	PF 4.0, height 5.2 mm	33
1.04.752	PF 4.5, height 5.2 mm	33
1.04.753	PF 5.0, height 5.2 mm	33
1.04.754	PF 6.0, height 5.2 mm	33

	Titanium Base bridge for CAD/CAM, incl. abutment screw	
1.04.760	PF 3.5, height 5.2 mm	33
1.04.761	PF 4.0, height 5.2 mm	33
1.04.762	PF 4.5, height 5.2 mm	33
1.04.763	PF 5.0, height 5.2 mm	33
1.04.764	PF 6.0, height 5.2 mm	33
	VARIOflex abutment set for crown	
1.04.830	PF 3.5, height 12.0 mm	36
1.04.831	PF 4.0, height 12.0 mm	36
1.04.832	PF 4.5, height 12.0 mm	36
1.04.833	PF 5.0, height 12.0 mm	36
1.04.834	PF 6.0, height 12.0 mm	36
	VARIOflex abutment set for bridge	
1.04.835	PF 3.5, height 12.0 mm	36
1.04.836	PF 4.0, height 12.0 mm	36
1.04.837	PF 4.5, height 12.0 mm	36
1.04.838	PF 5.0, height 12.0 mm	36
1.04.839	PF 6.0, height 12.0 mm	36
	VARIOmulti titanium base for CAD/CAM, incl. occlusal screw, titanium/titanium alloy, Ø 4.8 mm, height 4.5 mm	39
1.04.850		
	VARIOmulti titanium base for CAD/CAM, customizable, incl. occlusal screw, titanium/titanium alloy, Ø 4.8 mm, height 9 mm	39
1.04.851		

2.03	2.03.170 Q2 MONO circlip [2 pieces]	54
	2.03.335 Gold cap for bar, height 4.7 mm	50
	VARIO gold abutment for bridge	
2.03.400	PF 3.5, height 12.7 mm, cone 3.5 mm	41
2.03.401	PF 4.5, height 12.7 mm, cone 3.5 mm	41
2.03.402	PF 5.0, height 12.7 mm, cone 3.5 mm	41
2.03.403	PF 6.0, height 12.7 mm, cone 3.5 mm	41
2.03.404	PF 4.0, height 12.7 mm, cone 3.5 mm	41
	VARIO gold abutment for crown	
2.03.410	PF 3.5, height 12.7 mm, cone 3.5 mm	41
2.03.411	PF 4.5, height 12.7 mm, cone 3.5 mm	41
2.03.412	PF 5.0, height 12.7 mm, cone 3.5 mm	41
2.03.413	PF 6.0, height 12.7 mm, cone 3.5 mm	41
2.03.414	PF 4.0, height 12.7 mm, cone 3.5 mm	41
	Laboratory cylindrical pin [5 pieces]	
2.03.450 Q5	PF 3.5, length 70.0 mm	12,33,36
2.03.451 Q5	PF 4.0–6.0, length 70.0 mm	33,36
	VARIOmulti gold cap, incl. burn-out plastic cylinder, Ø 4.8 mm, height 4.2/13.5 mm	39
2.03.600		
	VARIOmulti burn-out cap [2 pieces]	
2.03.601 Q2	Ø 4.8 mm, height 13.5 mm	39
	VARIO 17° gold screw seat [fits all platform sizes]	
2.03.610	Ø 2.9 mm, height 2.0/11.3 mm	41
	EASY impression coping	
2.03.700	PF 3.5, cone 4.0 mm, height 9.5 mm	19,44
2.03.701	PF 4.5, cone 4.0 mm, height 9.5 mm	19,44,46
2.03.702	PF 5.0, cone 4.0 mm, height 9.5 mm	19,44,46
2.03.703	PF 6.0, cone 4.0 mm, height 9.5 mm	19,44,46
2.03.704	PF 3.5, cone 6.0 mm, height 11.5 mm	19,44
2.03.705	PF 4.5, cone 6.0 mm, height 11.5 mm	19,44,46,48
2.03.706	PF 5.0, cone 6.0 mm, height 11.5 mm	19,44,46,48
2.03.707	PF 6.0, cone 6.0 mm, height 11.5 mm	19,44,46,48
2.03.708	PF 4.0, cone 4.0 mm, height 9.5 mm	19,44
2.03.709	PF 4.0, cone 6.0 mm, height 11.5 mm	19,44
	EASY burn-out cap, for crown, burn-out plastic	
2.03.720	PF 3.5, cone 4.0 mm, height 4.7 mm	44
2.03.721	PF 4.5, cone 4.0 mm, height 4.7 mm	44,46
2.03.722	PF 5.0, cone 4.0 mm, height 4.7 mm	44,46
2.03.723	PF 6.0, cone 4.0 mm, height 4.7 mm	44,46
2.03.724	PF 3.5, cone 6.0 mm, height 6.7 mm	44
2.03.725	PF 4.5, cone 6.0 mm, height 6.7 mm	44,46
2.03.726	PF 5.0, cone 6.0 mm, height 6.7 mm	44,46
2.03.727	PF 6.0, cone 6.0 mm, height 6.7 mm	44,46
2.03.728	PF 4.0, cone 4.0 mm, height 4.7 mm	44
2.03.729	PF 4.0, cone 6.0 mm, height 6.7 mm	44
	EASY burn-out cap for bridge	
2.03.730	PF 3.5, cone 4.0 mm, height 4.7 mm	44
2.03.731	PF 4.5, cone 4.0 mm, height 4.7 mm	44,46
2.03.732	PF 5.0, cone 4.0 mm, height 4.7 mm	44,46
2.03.733	PF 6.0, cone 4.0 mm, height 4.7 mm	44,46
2.03.734	PF 3.5, cone 6.0 mm, height 6.7 mm	44
2.03.735	PF 4.5, cone 6.0 mm, height 6.7 mm	44,46
2.03.736	PF 5.0, cone 6.0 mm, height 6.7 mm	44,46
2.03.737	PF 6.0, cone 6.0 mm, height 6.7 mm	44,46
2.03.738	PF 4.0, cone 4.0 mm, height 4.7 mm	44
2.03.739	PF 4.0, cone 6.0 mm, height 6.7 mm	44

	EASY temporary cap	
2.03.740	PF 3.5, cone 4.0 mm, height 5.0 mm	44
2.03.741	PF 4.5, cone 4.0 mm, height 5.0 mm	44,46
2.03.742	PF 5.0, cone 4.0 mm, height 5.0 mm	44,46
2.03.743	PF 6.0, cone 4.0 mm, height 5.0 mm	44,46
2.03.744	PF 3.5, cone 6.0 mm, height 7.0 mm	44
2.03.745	PF 4.5, cone 6.0 mm, height 7.0 mm	44,46,48
2.03.746	PF 5.0, cone 6.0 mm, height 7.0 mm	44,46,48
2.03.747	PF 6.0, cone 6.0 mm, height 7.0 mm	44,46,48
2.03.748	PF 4.0, cone 4.0 mm, height 5.0 mm	44
2.03.749	PF 4.0, cone 6.0 mm, height 7.0 mm	44
	VARIOeco burn-out plastic cap, for titanium base	
2.03.790	PF 3.5, height 12.0 mm	33
2.03.791	PF 4.0, height 12.0 mm	33
2.03.792	PF 4.5, height 12.0 mm	33
2.03.793	PF 5.0, height 12.0 mm	33
2.03.794	PF 6.0, height 12.0 mm	33
	VARIOflex burn-out plastic cap	
2.03.840	PF 3.5, height 11.5 mm	36
2.03.841	PF 4.0, height 11.5 mm	36
2.03.842	PF 4.5, height 11.5 mm	36
2.03.843	PF 5.0, height 11.5 mm	36
2.03.844	PF 6.0, height 11.5 mm	36
2.03.848	VARIOunite burn-out plastic cap PF 3.0,	12

3.03

	Impression coping for open tray technique, single use, retentive, screw-retained, cylindrical	
3.03.010	PF 3.5, external Ø 3.8 mm, height 10.0 mm	17
3.03.011	PF 4.5, external Ø 4.8 mm, height 10.0 mm	17
3.03.012	PF 5.0, external Ø 5.3 mm, height 10.0 mm	17
3.03.013	PF 6.0, external Ø 6.3 mm, height 10.0 mm	17
	Impression coping for closed tray technique, single use, repositionable, screw-retained, long	
3.03.014	PF 3.5, external Ø 3.9 mm, height 12.0 mm	16
3.03.015	PF 4.5, external Ø 5.5 mm, height 12.0 mm	16
3.03.016	PF 5.0, external Ø 6.0 mm, height 12.0 mm	16
3.03.017	PF 6.0, external Ø 7.0 mm, height 12.0 mm	16
	Impression coping for open tray technique, single use, retentive, screw-retained, cylindrical	
3.03.018	PF 4.0, external Ø 4.3 mm, height 10.0 mm	17
	Impression coping for closed tray technique, single use, repositionable, screw-retained, long	
3.03.019	PF 4.0, external Ø 5.0 mm, height 12.0 mm	16
3.03.033	Retentive anchor analog, length 13.0 mm	21,49
	Implant analog	
3.03.060	PF 3.5, length 22.0 mm	20
3.03.061	PF 4.0, length 22.0 mm	20
3.03.062	PF 5.0, length 22.0 mm	20
3.03.063	PF 6.0, length 22.0 mm	20
3.03.065	PF 4.5, length 22.0 mm	20
	Impression coping for open tray technique, single use, retentive, screw-retained, conical	
3.03.071	PF 4.5, external Ø 5.5 mm, height 10.0 mm	17
3.03.072	PF 5.0, external Ø 6.0 mm, height 10.0 mm	17
3.03.073	PF 6.0, external Ø 7.0 mm, height 10.0 mm	17
	Impression coping for closed tray technique, single use, repositionable, screw-retained, short	
3.03.074	PF 3.5, external Ø 3.9 mm, height 8.0 mm	16
3.03.075	PF 4.5, external Ø 5.5 mm, height 8.0 mm	16
3.03.076	PF 5.0, external Ø 6.0 mm, height 8.0 mm	16
3.03.077	PF 6.0, external Ø 7.0 mm, height 8.0 mm	16
	Impression coping for open tray technique, single use, retentive, screw-retained, conical	
3.03.078	PF 4.0, external Ø 5.0 mm, height 10.0 mm	17
	Impression coping for closed tray technique, single use, repositionable, screw-retained, short	
3.03.079	PF 4.0, external Ø 5.0 mm, height 8.0 mm	16
3.03.083	VARIOmulti analog for CAD/CAM, titanium	21,38
3.03.084	Implant-analog for CAD/CAM PF 3.0	13
	Implant-analog for CAD/CAM	
3.03.085	PF 3.5, length 11.4 mm	20
3.03.086	PF 4.0, length 11.4 mm	20
3.03.087	PF 4.5, length 11.4 mm	20
3.03.088	PF 5.0, length 11.4 mm	20
3.03.089	PF 6.0, length 11.4 mm	20
	Implant analog	
3.03.090	PF 3.5, length 14.0 mm	20
3.03.091	PF 4.5, length 14.0 mm	20
3.03.092	PF 5.0, length 14.0 mm	20
3.03.093	PF 6.0, length 15.0 mm	20
3.03.095	PF 4.0, length 14.0 mm	20

3.03.098	Implant-analog PF 3.0	13
3.03.101	Impression coping for bar, Ø 6.0 mm, height 5.0 mm	19,50
	Bar analog	
3.03.105	Ø 4.0 mm, length 21.5 mm	21,50
3.03.140	X-ray reference sphere, Ø 5.0 mm	8
	Guiding sleeve for VECTOdrill™ pilot drill (4 pieces)	
3.03.141 Q4	Internal Ø 2.0 mm, length 6.0 mm	8,56
3.03.151	Solder pin for bar, length 13.5 mm	50
3.03.157	Insertion device for VARIOmulti analog for CAD/CAM	21,38,55
	Insertion device for implant analog for CAD/CAM	
3.03.158	PF 3.5, length 35.0 mm	13,20,55
3.03.159	PF 4.0–6.0, length 35.0 mm	20,55
3.03.160	MONO torque ratchet, length 110.0 mm	54
	MONO insertion device	
3.03.162	short, length 15.4 mm	40,42,55
3.03.163	long, length 25.8 mm	40,42,55
	MONO screwdriver (4-lobe)	
3.03.165	extra short, length 14.5 mm, shaft length 5.1 mm	55
3.03.166	short, length 22.2 mm, shaft length 10.3 mm	55
3.03.167	long, length 28.2 mm, shaft length 16.3 mm	55
	MONO insertion device for retentive anchor	
3.03.169	length 26.0 mm, Ø 8.5 mm	49
3.03.203	MONO guide key, length 94.7 mm	54
	Drill extension	
3.03.230	PF 4.0–6.0, external Ø 5.0 mm, length 26.0 mm	10
3.03.231	PF 3.5–4.0, external Ø 3.7 mm, length 26.0 mm	10
3.03.238	Adapter for hand piece PF 3.0, length 28.0 mm	12
3.03.240	Adapter for hand piece, length 18 mm	54
	Adapter for hand piece, one-piece	
3.03.241	PF 4.5–6.0, length 24.0 mm	54,56
3.03.248	PF 3.5, length 24.0 mm	12,54,56
3.03.249	Adapter for hand piece, length 28.0 mm	54
3.03.250	Handle for dental laboratory, length 120.0 mm	20,55
	Adapter for hand piece, one-piece	
3.03.251	PF 4.0, length 24.0 mm	54,56
	Explantation drill	
	long, for ELEMENT and CONTACT PF 3.5, external Ø 4.3 mm, internal Ø 3.8 mm, length 37.0 mm	
3.03.300	long, for ELEMENT and CONTACT PF 4.0 and 4.5, external Ø 5.0 mm, internal Ø 4.5 mm, length 37.0 mm	58
3.03.301	long, for ELEMENT PF 5.0, CONTACT PF 5.0 and 6.0, external Ø 6.3 mm, internal Ø 5.3 mm, length 37.0 mm	58
3.03.302	short, for ELEMENT and CONTACT PF 3.5, external Ø 4.3 mm, internal Ø 3.8 mm, length 31.0 mm	58
3.03.303	short, for ELEMENT and CONTACT PF 4.0 and 4.5, external Ø 5.0 mm, internal Ø 4.5 mm, length 31.0 mm	58
3.03.304	short, for ELEMENT PF 5.0, CONTACT PF 5.0 and 6.0, external Ø 6.3 mm, internal Ø 5.3 mm, length 31.0 mm	58
3.03.305	short, for ELEMENT PF 6.0	
3.03.306	external Ø 7.3 mm, internal Ø 6.3 mm, length 31.0 mm	58
	Guiding cylinder for ELEMENT and CONTACT implants	
3.03.307	PF 4.0, external Ø 4.4 mm, length 3.0 mm	58
3.03.308	PF 3.5, external Ø 3.7 mm, length 3.0 mm	58
3.03.309	PF 4.5, external Ø 4.4 mm, length 3.0 mm	58
	ELEMENT PF 5.0, CONTACT PF 5.0 and 6.0, external Ø 5.2 mm, length 3.0 mm	58
	Guiding cylinder for ELEMENT implant	
3.03.313	PF 6.0, external Ø 6.2 mm, length 3.0 mm	58
	Mucosa punch, reusable	
3.03.315	PF 3.5, length 27.0 mm	10
3.03.316	PF 4.0, length 27.0 mm	10
3.03.317	PF 5.0, length 27.0 mm	10
3.03.318	PF 6.0, length 27.0 mm	10
3.03.320	PF 4.5, length 27.0 mm	10
	VARIO/VARIOmulti reamer for base	
3.03.420	PF 3.5–4.0, length 16.0 mm	40,42
	VARIO/VARIOmulti reamer for base	
3.03.421	PF 4.5–6.0, length 16.0 mm	42
	VARIO guide pin for VARIO reamer	
3.03.423	PF 4.5–6.0, length 12.5 mm	42
	VARIO guide pin for VARIO/VARIOmulti reamer	
3.03.424	PF 3.5, length 15.0 mm	40,42
	VARIO guide pin for VARIO reamer	
3.03.425	PF 4.0, length 12.5 mm	42
	Gauge for VARIO and VARIOmulti reamers for screw channel, for laboratory use	40,42
3.03.430	VARIO reamer for screw channel	
3.03.435	PF 3.5, length 44.0 mm	42
3.03.436	PF 4.0–6.0, length 44.0 mm	42
3.03.437	VARIOmulti reamer for screw channel, length 40.0 mm	40

Screwdriver for hand piece (4-lobe)		
3.03.500	extra short, length 17.0 mm, shaft length 3.5 mm	54
3.03.501	short, length 22.0 mm, shaft length 8.0 mm	54
3.03.502	long, length 28.0 mm, shaft length 14.5 mm	54
3.03.503	extra long, length 38.0 mm, shaft length 24.5 mm	54
Laboratory screw		
3.03.515	PF 3.5, length 25.0 mm	33
3.03.515 Q5	PF 3.5, length 25.0 mm [5 pieces]	33
3.03.516	PF 4.0–6.0, length 25.0 mm	33
3.03.516 Q5	PF 4.0–6.0, length 25.0 mm [5 pieces]	33
Positioning handle for angled VARIO and VARIOmulti abutments, length 25.0 mm, Ø 4.0 mm		
3.03.521		40,42
3.03.522	Positioning handle , length 17.0 mm, Ø 6.0 mm	16,17
Screw for impression copings, reusable (4-lobe)		
3.03.572	PF 3.5, extra short, length 12.5 mm	12,16,17,18
3.03.573	PF 3.5, short, length 16.5 mm	16,17
3.03.574	PF 3.5, long, length 21.5 mm	12,17
3.03.575	PF 4.0–6.0, extra short, length 13.2 mm	16,17,18
3.03.576	PF 4.0–6.0, short, length 17.2 mm	16,17
3.03.577	PF 4.0–6.0, long, length 22.2 mm	17
3.03.580	PF 3.5, extra long, length 27.5 mm	12,17
3.03.581	PF 4.0–6.0, extra long, length 28.2 mm	17
Fabrication screw, for customizable gingiva former and VARIOtemp (4-lobe), for PF 3.5, length 22.5 mm [4 pieces]		
3.03.590 Q4		15
Fabrication screw, for customizable gingiva former and VARIOtemp (4-lobe), for PF 4.0–6.0, length 23.4 mm [4 pieces]		
3.03.591 Q4		15
Fabrication screw for VARIOmulti temporary cap (4-lobe) length 19.3 mm [4 pieces]		
3.03.598 Q4		38
VECTOdriLL™ twist drill, single use [4 pieces]		
3.03.610 Q4	Pilot drill Ø 2.0 mm, short, length 34.0 mm	9
3.03.611 Q4	Pilot drill Ø 2.0 mm, long, length 40.0 mm	9,11
3.03.612 Q4	Drill Ø 2.8 mm, short, length 34.0 mm	9,11
3.03.613 Q4	Drill Ø 2.8 mm, long, length 40.0 mm	9
3.03.614 Q4	Drill Ø 3.5 mm, short, length 34.0 mm	9
3.03.615 Q4	Drill Ø 3.5 mm, long, length 40.0 mm	9
3.03.616 Q4	Drill Ø 4.3 mm, short, length 34.0 mm	9
3.03.617 Q4	Drill Ø 4.3 mm, long, length 40.0 mm	9
3.03.618 Q4	Drill Ø 5.3 mm, short, length 34.0 mm	9
Pilot drill Ø 2.0 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.624 Q4		9
Drill Ø 2.8 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.625 Q4		9
Drill Ø 3.5 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.626 Q4		9
Drill Ø 4.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.627 Q4		9
Drill Ø 5.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.628 Q4		9
VECTOdriLL™ Depth gauge		
3.03.630	Ø 2.0 mm, length 27.5 mm	9
3.03.632	Ø 2.8 mm, length 27.5 mm	9
3.03.634	Ø 3.5 mm, length 27.5 mm	9
3.03.636	Ø 4.3 mm, length 27.5 mm	9
3.03.638	Ø 5.3 mm, length 27.5 mm	9
CONTACT profile drill, single use [4 pieces]		
3.03.640 Q4	2.7/3.5 mm, short, length 34.0 mm	10
3.03.641 Q4	2.7/3.5 mm, extra short, length 29.0 mm	10
3.03.642 Q4	3.5/4.5 mm, short, length 34.0 mm	10
3.03.643 Q4	3.5/4.5 mm, extra short, length 29.0 mm	10
3.03.644 Q4	4.2/5.0 mm, short, length 34.0 mm	10
3.03.645 Q4	4.2/5.0 mm, extra short, length 29.0 mm	10
3.03.646 Q4	5.0/6.0 mm, short, length 34.0 mm	10
3.03.647 Q4	5.0/6.0 mm, extra short, length 29.0 mm	10
3.03.648 Q4	3.5/4.0 mm, short, length 34.0 mm	10
3.03.649 Q4	3.5/4.0 mm, extra short, length 29.0 mm	10
ELEMENT profile drill, single use [4 pieces]		
3.03.651 Q4	3.5/3.5 mm, extra short, length 29.0 mm	10
3.03.653 Q4	4.2/4.5 mm, extra short, length 29.0 mm	10
3.03.655 Q4	5.0/5.0 mm, extra short, length 29.0 mm	10
3.03.657 Q4	4.0/4.0 mm, extra short, length 29.0 mm	10
3.03.659 Q4	6.0/6.0 mm, extra short, length 29.0 mm	10
3.03.658	Bone contouring instrument for PF 3.0, reusable	12
VECTOdriLL™ ceramic drill, reusable		
Pilot drill Ø 2.0 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.660		9
Pilot drill Ø 2.0 mm, short, length 34.0 mm		
3.03.661		9
Drill Ø 2.8 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.662		9
Drill Ø 2.8 mm, short, length 34.0 mm		
3.03.663		9
Drill Ø 3.5 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.664		9

3.03.665	Drill Ø 3.5 mm, short, length 34.0 mm	9
Drill Ø 4.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.666		9
Drill Ø 4.3 mm, short, length 34.0 mm		
3.03.667		9
Drill Ø 5.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.668		9
Drill Ø 5.3 mm, short, length 34.0 mm		
3.03.669		9
Bone contouring instrument+, reusable		
3.03.670	PF 3.5, length 29.0 mm	10,37
Bone contouring instrument, reusable		
3.03.671	PF 3.5, length 29.0 mm	10
Bone contouring instrument+, reusable		
3.03.672	PF 4.0, length 29.0 mm	10,37
Bone contouring instrument, reusable		
3.03.673	PF 4.0, length 29.0 mm	10
Bone contouring instrument+, reusable		
3.03.674	PF 4.5, length 29.0 mm	10,37
Bone contouring instrument, reusable		
3.03.675	PF 4.5, length 29.0 mm	10
Bone contouring instrument+, reusable		
3.03.676	PF 5.0, length 29.0 mm	10,37
Bone contouring instrument, reusable		
3.03.677	PF 5.0, length 29.0 mm	10
3.03.679	PF 6.0, length 29.0 mm	10
Thread tap, reusable		
3.03.680	endosseous Ø 3.5 mm, length 34.0 mm	10
3.03.682	endosseous Ø 4.0 mm, length 34.0 mm	10
3.03.684	endosseous Ø 4.2 mm, length 34.0 mm	10
3.03.686	endosseous Ø 5.0 mm, length 34.0 mm	10
3.03.688	endosseous Ø 6.0 mm, length 34.0 mm	10
Drill Ø 1.5 mm, single use, short, length 34.0 mm [4 pieces]		
3.03.690 Q4		9
Depth gauge Ø 1.5 mm, shortenable, length 30.5 mm		
3.03.692		9
EASY analog		
3.03.700	PF 3.5, cone 4.0 mm, height 14.0 mm	21,44
3.03.701	PF 4.5, cone 4.0 mm, height 14.0 mm	21,44,46
3.03.702	PF 5.0, cone 4.0 mm, height 14.0 mm	21,44,46
3.03.703	PF 6.0, cone 4.0 mm, height 14.0 mm	21,44,46
3.03.704	PF 3.5, cone 6.0 mm, height 16.0 mm	21,44
3.03.705	PF 4.5, cone 6.0 mm, height 16.0 mm	21,44,46,48
3.03.706	PF 5.0, cone 6.0 mm, height 16.0 mm	21,44,46,48
3.03.707	PF 6.0, cone 6.0 mm, height 16.0 mm	21,44,46,48
3.03.708	PF 4.0, cone 4.0 mm, height 14.0 mm	21,44
3.03.709	PF 4.0, cone 6.0 mm, height 16.0 mm	21,44
VECTOdriLL™ twist drill, reusable		
Pilot drill Ø 2.0 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.710		9
Drill Ø 2.8 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.712		9
Drill Ø 3.5 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.714		9
Drill Ø 4.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.716		9
Drill Ø 5.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm		
3.03.718		9
3.03.720	Pilot drill Ø 2.0 mm, short, length 34.0 mm	9
3.03.722	Drill Ø 2.8 mm, short, length 34.0 mm	9
3.03.724	Drill Ø 3.5 mm, short, length 34.0 mm	9
3.03.726	Drill Ø 4.3 mm, short, length 34.0 mm	9
3.03.728	Drill Ø 5.3 mm, short, length 34.0 mm	9
3.03.730	Pilot drill Ø 2.0 mm, long, length 40.0 mm	9,11
3.03.732	Drill Ø 2.8 mm, long, length 40.0 mm	9
3.03.734	Drill Ø 3.5 mm, long, length 40.0 mm	9
3.03.736	Drill Ø 4.3 mm, long, length 40.0 mm	9
ELEMENT profile drill for PF 3.0, single use		
3.03.740	for implant of length 8.0 mm	11
3.03.741	for implant of length 9.5 mm,	11
3.03.742	for implant of length 11.0 mm	11
3.03.743	for implant of length 12.5 mm	11
NEVO/ELEMENT profile drill, reusable, stainless steel		
3.03.751	PF 3.5, extra short, L 29.0 mm	10
3.03.752	PF 4.0, extra short, L 29.0 mm	10
3.03.753	PF 4.5, extra short, L 29.0 mm	10
3.03.754	PF 5.0, extra short, L 29.0 mm	10
3.03.774	Scan abutment PF 3.0	13
Scan abutment		
3.03.775	PF 3.5	18
3.03.776	PF 4.0	18
3.03.777	PF 4.5	18
3.03.778	PF 5.0	18
3.03.779	PF 6.0	18

3.03.780	VARIOmulti scan abutment, Ø 4.5 mm, height 8.0 mm	18,39
3.03.781	VARIOmulti scan abutment, Ø 5.0 mm, height 5.0 mm	18,39
3.03.790	Drill Ø 1.5 mm, reusable, short, length 34.0 mm	8
3.03.800	VARIOmulti analog, Ø 4.8 mm, height 21.2 mm	21,38
3.03.804	VARIOmulti temporary cap, incl. fabrication screw Ø 5.2 mm, height 15.0 mm	38

3.04

	Impression coping for open tray technique, reusable, retentive, screw-retained, cylindrical	
3.04.020	PF 3.5, external Ø 3.8 mm, height 16.0 mm	17
3.04.021	PF 4.0, external Ø 4.3 mm, height 16.0 mm	17
3.04.022	PF 4.5, external Ø 4.8 mm, height 16.0 mm	17
3.04.023	PF 5.0, external Ø 5.3 mm, height 16.0 mm	17
3.04.024	PF 6.0, external Ø 6.3 mm, height 16.0 mm	17
3.04.028	Impression coping PF 3.0, for open tray technique, reusable, retentive, screw-retained, cylindrical	12
	Impression coping for closed tray technique, reusable, repositionable, screw-retained, short	
3.04.030	PF 3.5, external Ø 3.9 mm, height 8.0 mm	16
3.04.031	PF 4.0, external Ø 5.0 mm, height 8.0 mm	16
3.04.032	PF 4.5, external Ø 5.5 mm, height 8.0 mm	16
3.04.033	PF 5.0, external Ø 6.0 mm, height 8.0 mm	16
3.04.034	PF 6.0, external Ø 7.0 mm, height 8.0 mm	16
	Impression coping for open tray technique, reusable, retentive, screw-retained, conical	
3.04.037	PF 4.0, external Ø 5.0 mm, height 16.0 mm	17
3.04.038	PF 4.5, external Ø 5.5 mm, height 16.0 mm	17
3.04.039	PF 5.0, external Ø 6.0 mm, height 16.0 mm	17
3.04.040	PF 6.0, external Ø 7.0 mm, height 16.0 mm	17
	Impression coping for closed tray technique, reusable, repositionable, screw-retained, long	
3.04.046	PF 3.5, external Ø 3.9 mm, height 12.0 mm	16
3.04.047	PF 4.0, external Ø 5.0 mm, height 12.0 mm	16
3.04.048	PF 4.5, external Ø 5.5 mm, height 12.0 mm	16
3.04.049	PF 5.0, external Ø 6.0 mm, height 12.0 mm	16
3.04.050	PF 6.0, external Ø 7.0 mm, height 12.0 mm	16
3.04.080 04	Guiding sleeve , length 5.0 mm, Ø 4.8 mm	56
3.04.090	Adapter guided, length 25.5 mm	56
3.04.100	Seating instrument for guiding sleeve Ø 4.8 mm	56
3.04.110	Initial drill , guided, length 28.5 mm	56
	VECTOdrill pilot drill and twist drill , guided	
3.04.111	Pilot drill, Ø 2.0 mm, length 31.5 mm, L 6.5 mm	56
3.04.112	Pilot drill, Ø 2.0 mm, length 33.0 mm, L 8.0 mm	56
3.04.113	Pilot drill, Ø 2.0 mm, length 34.5 mm, L 9.5 mm	56
3.04.114	Pilot drill, Ø 2.0 mm, length 36.0 mm, L 11.0 mm	56
3.04.115	Pilot drill, Ø 2.0 mm, length 37.5 mm, L 12.5 mm	56
3.04.121	Drill, Ø 2.8 mm, length 31.5 mm, L 6.5 mm	56
3.04.122	Drill, Ø 2.8 mm, length 33.0 mm, L 8.0 mm	56
3.04.123	Drill, Ø 2.8 mm, length 34.5 mm, L 9.5 mm	56
3.04.124	Drill, Ø 2.8 mm, length 36.0 mm, L 11.0 mm	56
3.04.125	Drill, Ø 2.8 mm, length 37.5 mm, L 12.5 mm	56
3.04.131	Drill, Ø 3.5 mm, length 31.5 mm, L 6.5 mm	56
3.04.132	Drill, Ø 3.5 mm, length 33.0 mm, L 8.0 mm	56
3.04.133	Drill, Ø 3.5 mm, length 34.5 mm, L 9.5 mm	56
3.04.134	Drill, Ø 3.5 mm, length 36.0 mm, L 11.0 mm	56
3.04.135	Drill, Ø 3.5 mm, length 37.5 mm, L 12.5 mm	56
	Profile drill CONTACT AND ELEMENT , guided	
3.04.171	Profile drill CONTACT MC , Ø 3.5 mm, length 34.0 mm	56
3.04.172	Profile drill CONTACT MC, PF 4.0, length 34.0 mm	56
3.04.173	Profile drill CONTACT MC, PF 4.5, length 34.0 mm	56
3.04.161	Profile drill CONTACT RC, PF 3.5, length 32.5 mm	56
3.04.162	Profile drill CONTACT RC PF 4.0, length 32.5 mm	56
3.04.163	Profile drill CONTACT RC PF 4.5, length 32.5 mm	56
3.04.151	Profile drill ELEMENT MC, PF 3.5, length 30.5 mm	56
3.04.152	Profile drill ELEMENT MC, PF 4.0, length 30.5 mm	56
3.04.153	Profile drill ELEMENT MC, PF 4.5, length 30.5 mm	56
3.04.805	VARIOmulti impression coping, Ø 5.3 mm, height 18.0 mm	19,38

31

	Dynamic Titanium Base for crown	
31.311.113.01-2	PF 3.5, height 4.0 mm	34
31.312.114.01-2	PF 4.0, height 4.0 mm	34
31.313.115.01-2	PF 4.5, height 4.0 mm	34
31.314.116.01-2	PF 5.0, height 4.0 mm	34
	Dynamic Titanium Base for crown, shortenable , titanium alloy	
31.310.113.21-2	PF 3.5, height 9.0 mm	34
31.312.114.21-2	PF 4.0, height 9.0 mm	34
31.313.115.21-2	PF 4.5, height 9.0 mm	34
31.314.116.21-2	PF 5.0, height 9.0 mm	34
	Dynamic Titanium Base for bridge	
31.321.113.01-2	PF 3.5, height 4.0 mm	34

31.322.114.01-2	PF 4.0, height 4.0 mm	34
31.323.115.01-2	PF 4.5, height 4.0 mm	34
31.324.116.01-2	PF 5.0, height 4.0 mm	34
	Dynamic Titanium Base for bridge, shortenable , titanium alloy	
31.320.113.21-2	PF 3.5, height 9.0 mm	34
31.322.114.21-2	PF 4.0, height 9.0 mm	34
31.323.115.21-2	PF 4.5, height 9.0 mm	34
31.324.116.21-2	PF 5.0, height 9.0 mm	34

4.03

	EASY abutment, 20°	
4.03.010	PF 3.5, short 0.5 mm, height 6.5 mm	43
4.03.011	PF 4.5, short 0.5 mm, height 6.5 mm	43
4.03.012	PF 5.0, short 0.5 mm, height 6.5 mm	43
4.03.013	PF 6.0, short 0.5 mm, height 6.5 mm	43
4.03.014	PF 3.5, long 3.0 mm, height 8.0 mm	43
4.03.015	PF 4.5, long 3.0 mm, height 9.0 mm	43
4.03.016	PF 5.0, long 3.0 mm, height 9.0 mm	43
4.03.017	PF 6.0, long 3.0 mm, height 9.0 mm	43
4.03.018	PF 4.0, short 0.5 mm, height 6.5 mm	43
4.03.019	PF 4.0, long 3.0 mm, height 9.0 mm	43
	Retentive anchor	
4.03.040	PF 4.5, short, height 1.8 mm	49
4.03.041	PF 4.5, long, height 3.0 mm	49
4.03.042	PF 5.0, short, height 1.8 mm	49
4.03.043	PF 5.0, long, height 3.0 mm	49
4.03.048	PF 4.0, short, height 1.8 mm	49
4.03.049	PF 4.0, long, height 3.0 mm	49
4.03.070	Titanium cap for bar , height 4.7 mm	50
	VARIOmulti abutment angled, 17°, with handle and abutment screw, sterile	
4.03.300S	PF 3.5, collar height 1.6 mm	37
4.03.301S	PF 4.0, collar height 1.6 mm	37
4.03.302S	PF 4.5, collar height 1.6 mm	37
4.03.303S	PF 5.0, collar height 1.6 mm	37
4.03.304S	PF 6.0, collar height 1.6 mm	37
4.03.310S	PF 3.5, collar height 2.5 mm	37
4.03.311S	PF 4.0, collar height 2.5 mm	37
4.03.312S	PF 4.5, collar height 2.5 mm	37
4.03.313S	PF 5.0, collar height 2.5 mm	37
	VARIOmulti abutment angled, 30°, with handle and abutment screw, sterile	
4.03.305S	PF 3.5, collar height 1.2 mm	37
4.03.306S	PF 4.0, collar height 1.2 mm	37
4.03.307S	PF 4.5, collar height 1.2 mm	37
4.03.308S	PF 5.0, collar height 1.2 mm	37
4.03.309S	PF 6.0, collar height 1.2 mm	37
4.03.315S	PF 3.5, collar height 2.5 mm	37
4.03.316S	PF 4.0, collar height 2.5 mm	37
4.03.317S	PF 4.5, collar height 2.5 mm	37
4.03.318S	PF 5.0, collar height 2.5 mm	37
	Bar abutment	
4.03.380	PF 3.5, height 5.5 mm	50
4.03.381	PF 4.5, height 5.5 mm	50
4.03.382	PF 5.0, height 5.5 mm	50
4.03.388	PF 4.0, height 5.5 mm	50
	Milling abutment	
4.03.420	PF 3.5, height 11.0 mm	49
4.03.421	PF 4.5, height 12.0 mm	49
4.03.422	PF 5.0, height 12.0 mm	49
4.03.423	PF 6.0, height 12.0 mm	49
4.03.428	PF 4.0, height 12.0 mm	49
	Abutment screw (4-lobe)	
4.03.500	PF 3.5, length 5.8 mm	13,15,32,33,35,37,41,43,49
4.03.501	PF 4.0–6.0, length 7.2 mm	15,32,33,35,37,41,43,46,49
4.03.502	PF 4.0–6.0, length 10.2 mm	15,32,33,35,41,43,46,49
4.03.506	Occlusal screw for bar (4-lobe) , length 4.3 mm	50
4.03.507	Occlusal screw (4-lobe) , length 3.5 mm	37,41
	Healing cap SE (4-lobe)	
4.03.515	PF 3.5, height 1.0 mm	15
4.03.516	PF 4.5, height 1.0 mm	15
4.03.517	PF 5.0, height 1.0 mm	15
4.03.518	PF 6.0, height 1.0 mm	15
4.03.519	PF 4.0, height 1.0 mm	15
	Gingiva former for PF 3.0 (4-lobe)	
4.03.538	PF 3.0, height 3.2 mm	11
4.03.548	PF 3.0, height 4.5 mm	11
4.03.558	PF 3.0, height 7.0 mm	11
4.03.525	Gingiva former+ (4-lobe) PF 3.5, height 2.0 mm	15
	Gingiva former (4-lobe)	
4.03.520	PF 3.5, height 2.0 mm	15

4.03.521	PF 4.5, height 2.0 mm	15
4.03.522	PF 5.0, height 2.0 mm	15
4.03.523	PF 6.0, height 2.0 mm	15
4.03.524	PF 4.0, height 2.0 mm	15
Gingiva former (4-lobe)		
4.03.530	PF 3.5, height 3.2 mm	15
4.03.531	PF 4.5, height 3.2 mm	15
4.03.532	PF 5.0, height 3.2 mm	15
4.03.533	PF 6.0, height 3.2 mm	15
4.03.534	PF 4.0, height 3.2 mm	15
4.03.535	Gingiva former+ (4-lobe) PF 3.5, height 3.2 mm	15
Gingiva former (4-lobe)		
4.03.540	PF 3.5, height 4.5 mm	15
4.03.541	PF 4.5, height 4.5 mm	15
4.03.542	PF 5.0, height 4.5 mm	15
4.03.543	PF 6.0, height 4.5 mm	15
4.03.544	PF 4.0, height 4.5 mm	15
4.03.560	PF 3.5, height 5.7 mm	15
4.03.564	PF 4.0, height 5.7 mm	15
4.03.561	PF 4.5, height 5.7 mm	15
4.03.562	PF 5.0, height 5.7 mm	15
4.03.563	PF 6.0, height 5.7 mm	15
4.03.550	PF 3.5, height 7.0 mm	15
4.03.551	PF 4.5, height 7.0 mm	15
4.03.552	PF 5.0, height 7.0 mm	15
4.03.553	PF 6.0, height 7.0 mm	15
4.03.554	PF 4.0, height 7.0 mm	15
Gingiva former, customizable		
4.03.570	PF 3.5, height 7.5 mm	15
4.03.571	PF 4.0, height 7.5 mm	15
4.03.572	PF 4.5, height 7.5 mm	15
4.03.573	PF 5.0, height 7.5 mm	15
4.03.574	PF 6.0, height 7.5 mm	15
VARIOmulti abutment, with handle, sterile		
4.03.600S	PF 3.5, collar height 0.8 mm	37
4.03.601S	PF 4.0, collar height 0.8 mm	37
4.03.602S	PF 4.5, collar height 0.8 mm	37
4.03.603S	PF 5.0, collar height 0.8 mm	37
4.03.604S	PF 6.0, collar height 1.5 mm	37
4.03.605S	PF 3.5, collar height 2.0 mm	37
4.03.606S	PF 4.0, collar height 2.0 mm	37
4.03.607S	PF 4.5, collar height 2.0 mm	37
4.03.608S	PF 5.0, collar height 2.0 mm	37
4.03.610S	PF 3.5, collar height 3.0 mm	37
4.03.611S	PF 4.0, collar height 3.0 mm	37
4.03.612S	PF 4.5, collar height 3.0 mm	37
4.03.613S	PF 5.0, collar height 3.0 mm	37
EASY abutment		
4.03.700	PF 3.5, short 0.5 mm, cone 4.0 mm, height 4.5 mm	43
4.03.701	PF 4.5, short 0.5 mm, cone 4.0 mm, height 4.5 mm	43
4.03.702	PF 5.0, short 0.5 mm, cone 4.0 mm, height 4.5 mm	43
4.03.703	PF 6.0, short 0.5 mm, cone 4.0 mm, height 4.5 mm	43
4.03.704	PF 3.5, short 0.5 mm, cone 6.0 mm, height 6.5 mm	43
4.03.705	PF 4.5, short 0.5 mm, cone 6.0 mm, height 6.5 mm	43
4.03.706	PF 5.0, short 0.5 mm, cone 6.0 mm, height 6.5 mm	43
4.03.707	PF 6.0, short 0.5 mm, cone 6.0 mm, height 6.5 mm	43
4.03.708	PF 4.0, short 0.5 mm, cone 4.0 mm, height 4.5 mm	43
4.03.709	PF 4.0, short 0.5 mm, cone 6.0 mm, height 6.5 mm	43
4.03.710	PF 3.5, long 2.0 mm, cone 4.0 mm, height 6.0 mm	43
4.03.711	PF 4.5, long 2.0 mm, cone 4.0 mm, height 6.0 mm	43
4.03.712	PF 5.0, long 2.0 mm, cone 4.0 mm, height 6.0 mm	43
4.03.713	PF 6.0, long 2.0 mm, cone 4.0 mm, height 6.0 mm	43
4.03.714	PF 3.5, long 2.0 mm, cone 6.0 mm, height 8.0 mm	43
4.03.715	PF 4.5, long 2.0 mm, cone 6.0 mm, height 8.0 mm	43
4.03.716	PF 5.0, long 2.0 mm, cone 6.0 mm, height 8.0 mm	43
4.03.717	PF 6.0, long 2.0 mm, cone 6.0 mm, height 8.0 mm	43
4.03.718	PF 4.0, long 2.0 mm, cone 4.0 mm, height 6.0 mm	43
4.03.719	PF 4.0, long 2.0 mm, cone 6.0 mm, height 8.0 mm	43
EASY abutment e.p.		
4.03.721	PF 4.5/5.0, cone 4.0 mm, height 7.0 mm	45
4.03.722	PF 5.0/6.0, cone 4.0 mm, height 7.0 mm	45
4.03.725	PF 4.5/5.0, cone 6.0 mm, height 9.0 mm	45
4.03.726	PF 5.0/6.0, cone 6.0 mm, height 9.0 mm	45
4.03.728	PF 4.0/4.5, cone 4.0 mm, height 7.0 mm	45
4.03.729	PF 4.0/4.5, cone 6.0 mm, height 9.0 mm	45
EASY abutment		
4.03.734	PF 3.5, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	43
4.03.735	PF 4.5, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	43
4.03.736	PF 5.0, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	43
4.03.739	PF 4.0, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	43

4.03.801	VARIOmulti protective cap Ø 5.3 mm, height 4.5 mm	38
Gingiva former narrow (4-lobe)		
4.04.310	PF 3.5, height 2.0 mm	15
4.04.311	PF 4.0, height 2.0 mm	15
4.04.312	PF 4.5, height 2.0 mm	15
4.04.313	PF 5.0, height 2.0 mm	15
4.04.314	PF 6.0, height 2.0 mm	15
4.04.320	PF 3.5, height 3.2 mm	15
4.04.321	PF 4.0, height 3.2 mm	15
4.04.322	PF 4.5, height 3.2 mm	15
4.04.323	PF 5.0, height 3.2 mm	15
4.04.324	PF 6.0, height 3.2 mm	15
4.04.330	PF 3.5, height 4.5 mm	15
4.04.331	PF 4.0, height 4.5 mm	15
4.04.332	PF 4.5, height 4.5 mm	15
4.04.333	PF 5.0, height 4.5 mm	15
4.04.334	PF 6.0, height 4.5 mm	15
4.04.340	PF 3.5, height 5.7 mm	15
4.04.341	PF 4.0, height 5.7 mm	15
4.04.342	PF 4.5, height 5.7 mm	15
4.04.343	PF 5.0, height 5.7 mm	15
4.04.344	PF 6.0, height 5.7 mm	15
4.04.350	PF 3.5, height 7.0 mm	15
4.04.351	PF 4.0, height 7.0 mm	15
4.04.352	PF 4.5, height 7.0 mm	15
4.04.353	PF 5.0, height 7.0 mm	15
4.04.354	PF 6.0, height 7.0 mm	15

4.13

CONTACT implant, incl. healing cap		
4.13.211	PF 4.5, endosseous Ø 3.5 mm, length 9.5 mm	7
4.13.212	PF 5.0, endosseous Ø 4.2 mm, length 9.5 mm	7
4.13.213	PF 6.0, endosseous Ø 5.0 mm, length 9.5 mm	7
4.13.214	PF 4.0, endosseous Ø 3.5 mm, length 9.5 mm	7
4.13.220	PF 3.5, endosseous Ø 2.7 mm, length 11.0 mm	7
4.13.221	PF 4.5, endosseous Ø 3.5 mm, length 11.0 mm	7
4.13.222	PF 5.0, endosseous Ø 4.2 mm, length 11.0 mm	7
4.13.223	PF 6.0, endosseous Ø 5.0 mm, length 11.0 mm	7
4.13.224	PF 4.0, endosseous Ø 3.5 mm, length 11.0 mm	7
4.13.230	PF 3.5, endosseous Ø 2.7 mm, length 12.5 mm	7
4.13.231	PF 4.5, endosseous Ø 3.5 mm, length 12.5 mm	7
4.13.232	PF 5.0, endosseous Ø 4.2 mm, length 12.5 mm	7
4.13.233	PF 6.0, endosseous Ø 5.0 mm, length 12.5 mm	7
4.13.234	PF 4.0, endosseous Ø 3.5 mm, length 12.5 mm	7
4.13.240	PF 3.5, endosseous Ø 2.7 mm, length 14.0 mm	7
4.13.241	PF 4.5, endosseous Ø 3.5 mm, length 14.0 mm	7
4.13.242	PF 5.0, endosseous Ø 4.2 mm, length 14.0 mm	7
4.13.243	PF 6.0, endosseous Ø 5.0 mm, length 14.0 mm	7
4.13.244	PF 4.0, endosseous Ø 3.5 mm, length 14.0 mm	7
4.13.261	PF 4.5, endosseous Ø 3.5 mm, length 17.0 mm	7
4.13.262	PF 5.0, endosseous Ø 4.2 mm, length 17.0 mm	7
ELEMENT implant, incl. healing cap		
4.13.900	PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	7
4.13.901	PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	7
4.13.902	PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	7
4.13.903	PF 6.0, endosseous Ø 6.0 mm, length 8.0 mm	7
4.13.904	PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	7
4.13.905	PF 4.0, endosseous Ø 4.0 mm, length 6.5 mm	7
4.13.906	PF 4.5, endosseous Ø 4.2 mm, length 6.5 mm	7
4.13.907	PF 5.0, endosseous Ø 5.0 mm, length 6.5 mm	7
4.13.908	PF 6.0, endosseous Ø 6.0 mm, length 6.5 mm	7
4.13.910	PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	7
4.13.911	PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	7
4.13.912	PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	7
4.13.913	PF 6.0, endosseous Ø 6.0 mm, length 11.0 mm	7
4.13.914	PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	7
4.13.920	PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	7
4.13.921	PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	7
4.13.922	PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	7
4.13.924	PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	7
4.13.930	PF 3.5, endosseous Ø 3.5 mm, length 17.0 mm	7
4.13.931	PF 4.5, endosseous Ø 4.2 mm, length 17.0 mm	7
4.13.934	PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	7
4.13.940	PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	7
4.13.941	PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	7
4.13.942	PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	7
4.13.943	PF 6.0, endosseous Ø 6.0 mm, length 9.5 mm	7
4.13.944	PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	7
4.13.950	PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	7
4.13.951	PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	7
4.13.952	PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	7

4.23.792	PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4
4.23.793	PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4
4.23.794	PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4
4.23.795	PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4
4.23.796	PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4
	NEVO Implant MC INICELL®, incl. healing cap	
4.23.812	PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4
4.23.813	PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4
4.23.814	PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4
4.23.815	PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4
4.23.816	PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4
4.23.822	PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4
4.23.823	PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4
4.23.824	PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4
4.23.825	PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4
4.23.826	PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4
4.23.832	PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4
4.23.833	PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4
4.23.834	PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4
4.23.835	PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4
4.23.836	PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4
4.23.842	PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4
4.23.843	PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4
4.23.844	PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4
4.23.845	PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4
4.23.846	PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4
5.03	Impression coping for closed tray technique, single use, reposition- able, screw-retained, aluminum, anodized, long, including screw	
5.03.014	PF 3.5, External-Ø 3.9 mm, height 12.0 mm	16
5.03.019	PF 4.0, External-Ø 5.0 mm, height 12.0 mm	16
5.03.015	PF 4.5, External-Ø 5.5 mm, height 12.0 mm	16
5.03.016	PF 5.0, External-Ø 6.0 mm, height 12.0 mm	16
5.03.017	PF 6.0, External-Ø 7.0 mm, height 12.0 mm	16
	Impression coping for closed tray technique, single use, reposition- able, screw-retained, titanium short, including screw	
5.03.074	PF 3.5, External-Ø 3.9 mm, height 8.0 mm	16
5.03.079	PF 4.0, External-Ø 5.0 mm, height 8.0 mm	16
5.03.075	PF 4.5, External-Ø 5.5 mm, height 8.0 mm	16
5.03.076	PF 5.0, External-Ø 6.0 mm, height 8.0 mm	16
5.03.077	PF 6.0, External-Ø 7.0 mm, height 8.0 mm	16
	Scan abutment , including screw	
5.03.775	PF 3.5	18
5.03.776	PF 4.0	18
5.03.777	PF 4.5	18
5.03.778	PF 5.0	18
5.03.779	PF 6.0	18
5.04	Impression coping for closed tray technique, reusable, reposition- able, screw-retained, titanium long, including screw	
5.04.030	PF 3.5, External-Ø 3.9 mm, height 8.0 mm	16
5.04.031	PF 4.0, External-Ø 5.0 mm, height 8.0 mm	16
5.04.032	PF 4.5, External-Ø 5.5 mm, height 8.0 mm	16
5.04.033	PF 5.0, External-Ø 6.0 mm, height 8.0 mm	16
5.04.034	PF 6.0, External-Ø 7.0 mm, height 8.0 mm	16
	Impression coping for closed tray technique, reusable, reposition- able, screw-retained, titanium long, including screw	
5.04.046	PF 3.5, External-Ø 3.9 mm, height 12.0 mm	16
5.04.047	PF 4.0, External-Ø 5.0 mm, height 12.0 mm	16
5.04.048	PF 4.5, External-Ø 5.5 mm, height 12.0 mm	16
5.04.049	PF 5.0, External-Ø 6.0 mm, height 12.0 mm	16
5.04.050	PF 6.0, External-Ø 7.0 mm, height 12.0 mm	16
41	Dynamic abutment screw (6-lobe)	
41.314.069.01-2	PF 3.5, length 6.9 mm	34
41.316.076.02-2	PF 4.0-5.0, length 7.6 mm	34
43	Dynamic screwdriver (6-lobe)	
43.618.201.01-2	length 18.0 mm	34
43.624.201.01-2	length 24.0 mm	34
43.632.201.01-2	length 32.0 mm	34
8.03	Screw organizer for prosthetic cassette	
8.03.019	length 56.0 mm, width 47.0 mm, height 28.0 mm	57
	Ultrasonic cleaning-cassette	
8.03.059	length 160.0 mm, width 72.0 mm, height 28.0 mm	57
	Instrument holder set , for surgical cassette	
8.03.090 Q2	consisting of 2 holders, size S	57
8.03.091	consisting of 1 holder, size M	57

83	8393 LOCATOR® core tool	52
84	LOCATOR® abutment	
	8461 PF 4.0, collar height 1.0 mm	51
	8462 PF 4.0, collar height 2.0 mm	51
	8463 PF 4.0, collar height 3.0 mm	51
	8464 PF 4.0, collar height 4.0 mm	51
	8465 PF 4.0, collar height 5.0 mm	51
	8466 PF 4.0, collar height 6.0 mm	51
85	8505 LOCATOR® impression coping (4 pieces)	19,52
	8514 LOCATOR® block-out spacer (20 pieces)	52
	8515-20 LOCATOR® male processing, black (20 pieces)	52
	LOCATOR® analog , Ø 5.0 mm (preferably used with PF 5.0 and 6.0) (4 pieces)	21,52
	8517 LOCATOR® parallel posts (4 pieces)	52
	8519-2 LOCATOR® laboratory set (pack contains 2 sets)	51
	LOCATOR® male replacement (4 pieces)	
	8524 clear	51
	8527 pink	51
	8529 blue	51
	LOCATOR® analog , Ø 4.0 mm (preferably used with PF 3.5, 4.0 and 4.5) (4 pieces)	21,52
	LOCATOR® laboratory set , for extended range (pack contains 2 sets)	51
	LOCATOR® male replacement , for extended range (4 pieces)	
	8547 green	51
	8548 red	51
87/88	LOCATOR® abutment	
	8786 PF 4.5, collar height 1.0 mm	51
	8787 PF 4.5, collar height 2.0 mm	51
	8788 PF 4.5, collar height 3.0 mm	51
	8789 PF 4.5, collar height 4.0 mm	51
	8790 PF 4.5, collar height 5.0 mm	51
	8791 PF 4.5, collar height 6.0 mm	51
	8792 PF 5.0, collar height 1.0 mm	51
	8793 PF 5.0, collar height 2.0 mm	51
	8794 PF 5.0, collar height 3.0 mm	51
	8795 PF 5.0, collar height 4.0 mm	51
	8796 PF 5.0, collar height 5.0 mm	51
	8797 PF 5.0, collar height 6.0 mm	51
	8875 PF 3.5, collar height 0.73 mm	51
	8876 PF 3.5, collar height 2.0 mm	51
	8877 PF 3.5, collar height 3.0 mm	51
	8878 PF 3.5, collar height 4.0 mm	51
	8879 PF 3.5, collar height 5.0 mm, only available in the US	51
	8880 PF 3.5, collar height 6.0 mm, only available in the US	51
	8881 PF 6.0, collar height 1.0 mm	51
	8882 PF 6.0, collar height 2.0 mm	51
	8883 PF 6.0, collar height 3.0 mm	51
	8884 PF 6.0, collar height 4.0 mm	51
89	LOCATOR® abutment and collar for VARIOmulti (2 pieces) collar height 3.0 mm	51
	LOCATOR® insert for hand piece and for short MONO insert device	
	8913 length 23.0 mm	52
	8914 length 29.0 mm	52
	LOCATOR® male replacement for extended range orange, (4 pieces)	51
95	9530 LOCATOR® angle measurement guide , height 15.0 mm, width 50.0 mm	52
ER	Container for surgical cassette , incl. identification plate Thommen Medical	
	ER510.080E length 312.0 mm, width 189.0 mm, height 83.0 mm	57
	Single-use-paper-filter (100 per pack) length 118.0 mm, width 235.0 mm	57
	Permanent filter , 1200 sterilization cycles length 95.0 mm, width 215.0 mm	57
Fo	X-ray template , for planning with two-dimensional x-ray devices	
	Fo_20d305 for the NEVO implant line	8
	Fo_20d184 for the ELEMENT implant line	8,11
	Fo_20d185 for the CONTACT implant line	8

Alphabetical index

A Abutment screw (4-lobe)		
PF 3.5, length 5.8 mm	4.03.500	13,15,32,33,35, 37,41,43,49
PF 4.0–6.0, length 7.2 mm	4.03.501	15,32,33,35,37 41,43,46,49
PF 4.0–6.0, length 10.2 mm	4.03.502	15,32,33,35 41,43,46,49
Adapter , guided, length 25.5 mm	3.04.090	56
Adapter for hand piece PF 3.0 , length 28.0 mm	3.03.238	12
Adapter for hand piece, one-piece		
PF 3.5, length 24.0 mm	3.03.248	12,54,56
PF 4.0, length 24.0 mm	3.03.251	54,56
PF 4.5–6.0, length 24.0 mm	3.03.241	54,56
Adapter for hand piece		
length 18.0 mm	3.03.240	54
length 28.0 mm	3.03.249	54
ART abutment , incl. abutment screw		
PF 3.5/4.5, cone 6.0 mm, height 9.0 mm	1.03.623	47
PF 4.0/4.5, cone 6.0 mm, height 9.0 mm	1.03.624	47
PF 4.5/5.0, cone 6.0 mm, height 9.0 mm	1.03.625	47
PF 5.0/6.0, cone 6.0 mm, height 9.0 mm	1.03.626	47
ART grinding cylinder-abutment , incl. abutment screw		
PF 3.5, height 12.0 mm	1.03.649	47
PF 4.0, height 12.0 mm	1.03.650	47
PF 4.5, height 12.0 mm	1.03.651	47
PF 5.0, height 12.0 mm	1.03.652	47

B Bar abutment		
PF 3.5, height 5.5 mm	4.03.380	50
PF 4.0, height 5.5 mm	4.03.388	50
PF 4.5, height 5.5 mm	4.03.381	50
PF 5.0, height 5.5 mm	4.03.382	50
Bar analog Ø 4.0 mm, length 21.5 mm	3.03.105	21,50
Bone contouring instrument for PF 3.0 , reusable	3.03.658	12
Bone contouring instrument, reusable		
PF 3.5, length 29.0 mm	3.03.671	10
PF 4.0, length 29.0 mm	3.03.673	10
PF 4.5, length 29.0 mm	3.03.675	10
PF 5.0, length 29.0 mm	3.03.677	10
PF 6.0, length 29.0 mm	3.03.679	10
Bone contouring instrument+ , reusable		
PF 3.5, length 29.0 mm	3.03.670	10,37
PF 4.0, length 29.0 mm	3.03.672	10,37
PF 4.5, length 29.0 mm	3.03.674	10,37
PF 5.0, length 29.0 mm	3.03.676	10,37

C CONTACT implant , incl. healing cap		
PF 3.5, endosseous Ø 2.7 mm, length 11.0 mm	4.13.220	7
PF 3.5, endosseous Ø 2.7 mm, length 12.5 mm	4.13.230	7
PF 3.5, endosseous Ø 2.7 mm, length 14.0 mm	4.13.240	7
PF 4.0, endosseous Ø 3.5 mm, length 9.5 mm	4.13.214	7
PF 4.0, endosseous Ø 3.5 mm, length 11.0 mm	4.13.224	7
PF 4.0, endosseous Ø 3.5 mm, length 12.5 mm	4.13.234	7
PF 4.0, endosseous Ø 3.5 mm, length 14.0 mm	4.13.244	7
PF 4.5, endosseous Ø 3.5 mm, length 9.5 mm	4.13.211	7
PF 4.5, endosseous Ø 3.5 mm, length 11.0 mm	4.13.221	7
PF 4.5, endosseous Ø 3.5 mm, length 12.5 mm	4.13.231	7
PF 4.5, endosseous Ø 3.5 mm, length 14.0 mm	4.13.241	7
PF 4.5, endosseous Ø 3.5 mm, length 17.0 mm	4.13.261	7
PF 5.0, endosseous Ø 4.2 mm, length 9.5 mm	4.13.212	7
PF 5.0, endosseous Ø 4.2 mm, length 11.0 mm	4.13.222	7
PF 5.0, endosseous Ø 4.2 mm, length 12.5 mm	4.13.232	7
PF 5.0, endosseous Ø 4.2 mm, length 14.0 mm	4.13.242	7
PF 5.0, endosseous Ø 4.2 mm, length 17.0 mm	4.13.262	7
PF 6.0, endosseous Ø 5.0 mm, length 9.5 mm	4.13.213	7
PF 6.0, endosseous Ø 5.0 mm, length 11.0 mm	4.13.223	7
PF 6.0, endosseous Ø 5.0 mm, length 12.5 mm	4.13.233	7
PF 6.0, endosseous Ø 5.0 mm, length 14.0 mm	4.13.243	7
CONTACT implant MC INICELL® , incl. healing cap		
PF 3.5, endosseous Ø 2.7 mm, length 12.5 mm	4.23.615	6
PF 3.5, endosseous Ø 2.7 mm, length 14.0 mm	4.23.616	6
PF 3.5, endosseous Ø 2.7 mm, length 15.5 mm	4.23.617	6
PF 4.0, endosseous Ø 3.5 mm, length 11.0 mm	4.23.624	6
PF 4.0, endosseous Ø 3.5 mm, length 12.5 mm	4.23.625	6
PF 4.0, endosseous Ø 3.5 mm, length 14.0 mm	4.23.626	6
PF 4.0, endosseous Ø 3.5 mm, length 15.5 mm	4.23.627	6
PF 4.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.634	6
PF 4.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.635	6

PF 4.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.636	6
PF 4.5, endosseous Ø 3.5 mm, length 15.5 mm	4.23.637	6
PF 5.0, endosseous Ø 4.2 mm, length 11.0 mm	4.23.644	6
PF 5.0, endosseous Ø 4.2 mm, length 12.5 mm	4.23.645	6
PF 5.0, endosseous Ø 4.2 mm, length 14.0 mm	4.23.646	6
PF 5.0, endosseous Ø 4.2 mm, length 15.5 mm	4.23.647	6
PF 6.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.654	6
PF 6.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.655	6
PF 6.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.656	6
PF 6.0, endosseous Ø 5.0 mm, length 15.5 mm	4.23.657	6

CONTACT implant RC INICELL®, incl. healing cap		
PF 3.5, endosseous Ø 2.7 mm, length 11.0 mm	4.23.214	6
PF 3.5, endosseous Ø 2.7 mm, length 12.5 mm	4.23.215	6
PF 3.5, endosseous Ø 2.7 mm, length 14.0 mm	4.23.216	6
PF 4.0, endosseous Ø 3.5 mm, length 9.5 mm	4.23.223	6
PF 4.0, endosseous Ø 3.5 mm, length 11.0 mm	4.23.224	6
PF 4.0, endosseous Ø 3.5 mm, length 12.5 mm	4.23.225	6
PF 4.0, endosseous Ø 3.5 mm, length 14.0 mm	4.23.226	6
PF 4.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.233	6
PF 4.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.234	6
PF 4.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.235	6
PF 4.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.236	6
PF 4.5, endosseous Ø 3.5 mm, length 17.0 mm	4.23.237	6
PF 5.0, endosseous Ø 4.2 mm, length 9.5 mm	4.23.243	6
PF 5.0, endosseous Ø 4.2 mm, length 11.0 mm	4.23.244	6
PF 5.0, endosseous Ø 4.2 mm, length 12.5 mm	4.23.245	6
PF 5.0, endosseous Ø 4.2 mm, length 14.0 mm	4.23.246	6
PF 5.0, endosseous Ø 4.2 mm, length 17.0 mm	4.23.247	6
PF 6.0, endosseous Ø 5.0 mm, length 9.5 mm	4.23.253	6
PF 6.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.254	6
PF 6.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.255	6
PF 6.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.256	6

CONTACT profile drill , single use (4 pieces)		
2.7/3.5 mm, extra short, length 29.0 mm	3.03.641 Q4	10
2.7/3.5 mm, short, length 34.0 mm	3.03.640 Q4	10
3.5/4.0 mm, extra short, length 29.0 mm	3.03.649 Q4	10
3.5/4.0 mm, short, length 34.0 mm	3.03.648 Q4	10
3.5/4.5 mm, extra short, length 29.0 mm	3.03.643 Q4	10
3.5/4.5 mm, short, length 34.0 mm	3.03.642 Q4	10
4.2/5.0 mm, extra short, length 29.0 mm	3.03.645 Q4	10
4.2/5.0 mm, short, length 34.0 mm	3.03.644 Q4	10
5.0/6.0 mm, extra short, length 29.0 mm	3.03.647 Q4	10
5.0/6.0 mm, short, length 34.0 mm	3.03.646 Q4	10

Container for surgical cassette , incl. identification plate Thommen Medical length 312.0 mm, width 189.0 mm, height 83.0 mm	ER510.080E	57
---	------------	-----------

D Depth gauge Ø 1.5 mm, shortenable, length 30.5 mm		
Drill Ø 1.5 mm, single use, short, length 34.0 mm (4 pieces)	3.03.690 Q4	9
Drill Ø 1.5 mm, reusable, short, length 34.0 mm	3.03.790	9
Drill extension		
PF 3.5–4.0, external Ø 3.7 mm, length 26.0 mm	3.03.231	10
PF 4.0–6.0, external Ø 5.0 mm, length 26.0 mm	3.03.230	10
Dynamic Titanium Base for crown		
PF 3.5, height 4.0 mm	31.311.113.01-2	34
PF 4.0, height 4.0 mm	31.312.114.01-2	34
PF 4.5, height 4.0 mm	31.313.115.01-2	34
PF 5.0, height 4.0 mm	31.314.116.01-2	34
Dynamic Titanium Base for crown, shortenable, titanium alloy		
PF 3.5, height 9.0 mm	31.310.113.21-2	34
PF 4.0, height 9.0 mm	31.312.114.21-2	34
PF 4.5, height 9.0 mm	31.313.115.21-2	34
PF 5.0, height 9.0 mm	31.314.116.21-2	34
Dynamic Titanium Base for bridge		
PF 3.5, height 4.0 mm	31.321.113.01-2	34
PF 4.0, height 4.0 mm	31.322.114.01-2	34
PF 4.5, height 4.0 mm	31.323.115.01-2	34
PF 5.0, height 4.0 mm	31.324.116.01-2	34
Dynamic Titanium Base for bridge, shortenable, titanium alloy		
PF 3.5, height 9.0 mm	31.320.113.21-2	34
PF 4.0, height 9.0 mm	31.322.114.21-2	34
PF 4.5, height 9.0 mm	31.323.115.21-2	34
PF 5.0, height 9.0 mm	31.324.116.21-2	34
Dynamic abutment screw (6-lobe)		
PF 3.5, length 6.9 mm	41.314.069.01-2	34
PF 4.0–5.0, length 7.6 mm	41.316.076.02-2	34
Dynamic screwdriver (6-lobe)		
length 18.0 mm	43.618.201.01-2	34
length 24.0 mm	43.624.201.01-2	34

length 32.0 mm	43.632.201.01-2	34
EASY impression coping		
PF 3.5, cone 4.0 mm, height 9.5 mm	2.03.700	19,44
PF 3.5, cone 6.0 mm, height 11.5 mm	2.03.704	19,44
PF 4.0, cone 4.0 mm, height 9.5 mm	2.03.708	19,44
PF 4.0, cone 6.0 mm, height 11.5 mm	2.03.709	19,44
PF 4.5, cone 4.0 mm, height 9.5 mm	2.03.701	19,44,46
PF 4.5, cone 6.0 mm, height 11.5 mm	2.03.705	19,44,46,48
PF 5.0, cone 4.0 mm, height 9.5 mm	2.03.702	19,44,46
PF 5.0, cone 6.0 mm, height 11.5 mm	2.03.706	19,44,46,48
PF 6.0, cone 4.0 mm, height 9.5 mm	2.03.703	19,44,46
PF 6.0, cone 6.0 mm, height 11.5 mm	2.03.707	19,44,46,48
EASY abutment, 20°		
PF 3.5, short 0.5 mm, height 6.5 mm	4.03.010	43
PF 3.5, long 3.0 mm, height 8.0 mm	4.03.014	43
PF 4.0, short 0.5 mm, height 6.5 mm	4.03.018	43
PF 4.0, long 3.0 mm, height 9.0 mm	4.03.019	43
PF 4.5, short 0.5 mm, height 6.5 mm	4.03.011	43
PF 4.5, long 3.0 mm, height 9.0 mm	4.03.015	43
PF 5.0, short 0.5 mm, height 6.5 mm	4.03.012	43
PF 5.0, long 3.0 mm, height 9.0 mm	4.03.016	43
PF 6.0, short 0.5 mm, height 6.5 mm	4.03.013	43
PF 6.0, long 3.0 mm, height 9.0 mm	4.03.017	43
EASY abutment set, extra long		
PF 3.5, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	1.04.734	43
PF 4.0, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	1.04.739	43
PF 4.5, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	1.04.735	43
PF 5.0, collar 4.0 mm, cone 6.0 mm, height 10.0 mm	1.04.736	43
EASY abutment set, short		
PF 3.5, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	1.04.700	43
PF 3.5, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	1.04.704	43
PF 4.0, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	1.04.708	43
PF 4.0, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	1.04.709	43
PF 4.5, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	1.04.701	43
PF 4.5, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	1.04.705	43
PF 5.0, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	1.04.702	43
PF 5.0, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	1.04.706	43
PF 6.0, collar 0.5 mm, cone 4.0 mm, height 4.5 mm	1.04.703	43
PF 6.0, collar 0.5 mm, cone 6.0 mm, height 6.5 mm	1.04.707	43
EASY abutment set, long		
PF 3.5, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	1.04.710	43
PF 3.5, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	1.04.714	43
PF 4.0, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	1.04.718	43
PF 4.0, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	1.04.719	43
PF 4.5, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	1.04.711	43
PF 4.5, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	1.04.715	43
PF 5.0, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	1.04.712	43
PF 5.0, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	1.04.716	43
PF 6.0, collar 2.0 mm, cone 4.0 mm, height 6.0 mm	1.04.713	43
PF 6.0, collar 2.0 mm, cone 6.0 mm, height 8.0 mm	1.04.717	43
EASY abutment e.p.		
PF 4.0/4.5, cone 4.0 mm, height 7.0 mm	4.03.728	45
PF 4.0/4.5, cone 6.0 mm, height 9.0 mm	4.03.729	45
PF 4.5/5.0, cone 4.0 mm, height 7.0 mm	4.03.721	45
PF 4.5/5.0, cone 6.0 mm, height 9.0 mm	4.03.725	45
PF 5.0/6.0, cone 4.0 mm, height 7.0 mm	4.03.722	45
PF 5.0/6.0, cone 6.0 mm, height 9.0 mm	4.03.726	45
EASY abutment		
PF 3.5, short 0.5 mm, cone 4.0 mm, height 4.5 mm	4.03.700	43
PF 3.5, short 0.5 mm, cone 6.0 mm, height 6.5 mm	4.03.704	43
PF 3.5, long 2.0 mm, cone 4.0 mm, height 6.0 mm	4.03.710	43
PF 3.5, long 2.0 mm, cone 6.0 mm, height 8.0 mm	4.03.714	43
PF 3.5, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	4.03.734	43
PF 4.0, short 0.5 mm, cone 4.0 mm, height 4.5 mm	4.03.708	43
PF 4.0, short 0.5 mm, cone 6.0 mm, height 6.5 mm	4.03.709	43
PF 4.0, long 2.0 mm, cone 4.0 mm, height 6.0 mm	4.03.718	43
PF 4.0, long 2.0 mm, cone 6.0 mm, height 8.0 mm	4.03.719	43
PF 4.0, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	4.03.739	43
PF 4.5, short 0.5 mm, cone 4.0 mm, height 4.5 mm	4.03.701	43
PF 4.5, short 0.5 mm, cone 6.0 mm, height 6.5 mm	4.03.705	43
PF 4.5, long 2.0 mm, cone 4.0 mm, height 6.0 mm	4.03.711	43
PF 4.5, long 2.0 mm, cone 6.0 mm, height 8.0 mm	4.03.715	43
PF 4.5, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	4.03.735	43
PF 5.0, short 0.5 mm, cone 4.0 mm, height 4.5 mm	4.03.702	43
PF 5.0, short 0.5 mm, cone 6.0 mm, height 6.5 mm	4.03.706	43
PF 5.0, long 2.0 mm, cone 4.0 mm, height 6.0 mm	4.03.712	43
PF 5.0, long 2.0 mm, cone 6.0 mm, height 8.0 mm	4.03.716	43

PF 5.0, extra long 4.0 mm, cone 6.0 mm, height 10.0 mm	4.03.736	43
PF 6.0, short 0.5 mm, cone 4.0 mm, height 4.5 mm	4.03.703	43
PF 6.0, short 0.5 mm, cone 6.0 mm, height 6.5 mm	4.03.707	43
PF 6.0, long 2.0 mm, cone 4.0 mm, height 6.0 mm	4.03.713	43
PF 6.0, long 2.0 mm, cone 6.0 mm, height 8.0 mm	4.03.717	43
EASY analog		
PF 3.5, cone 4.0 mm, height 14.0 mm	3.03.700	21,44
PF 3.5, cone 6.0 mm, height 16.0 mm	3.03.704	21,44
PF 4.0, cone 4.0 mm, height 14.0 mm	3.03.708	21,44
PF 4.0, cone 6.0 mm, height 16.0 mm	3.03.709	21,44
PF 4.5, cone 4.0 mm, height 14.0 mm	3.03.701	21,44,46
PF 4.5, cone 6.0 mm, height 16.0 mm	3.03.705	21,44,46,48
PF 5.0, cone 4.0 mm, height 14.0 mm	3.03.702	21,44,46
PF 5.0, cone 6.0 mm, height 16.0 mm	3.03.706	21,44,46,48
PF 6.0, cone 4.0 mm, height 14.0 mm	3.03.703	21,44,46
PF 6.0, cone 6.0 mm, height 16.0 mm	3.03.707	21,44,46,48
EASY burn-out cap for bridge		
PF 3.5, cone 4.0 mm, height 4.7 mm	2.03.730	44
PF 3.5, cone 6.0 mm, height 6.7 mm	2.03.734	44
PF 4.0, cone 4.0 mm, height 4.7 mm	2.03.738	44
PF 4.0, cone 6.0 mm, height 6.7 mm	2.03.739	44
PF 4.5, cone 4.0 mm, height 4.7 mm	2.03.731	44,46
PF 4.5, cone 6.0 mm, height 6.7 mm	2.03.735	44,46
PF 5.0, cone 4.0 mm, height 4.7 mm	2.03.732	44,46
PF 5.0, cone 6.0 mm, height 6.7 mm	2.03.736	44,46
PF 6.0, cone 4.0 mm, height 4.7 mm	2.03.733	44,46
PF 6.0, cone 6.0 mm, height 6.7 mm	2.03.737	44,46
EASY burn-out cap, for crown, burn-out plastic		
PF 3.5, cone 4.0 mm, height 4.7 mm	2.03.720	44
PF 3.5, cone 6.0 mm, height 6.7 mm	2.03.724	44
PF 4.0, cone 4.0 mm, height 4.7 mm	2.03.728	44
PF 4.0, cone 6.0 mm, height 6.7 mm	2.03.729	44
PF 4.5, cone 4.0 mm, height 4.7 mm	2.03.721	44,46
PF 4.5, cone 6.0 mm, height 6.7 mm	2.03.725	44,46
PF 5.0, cone 4.0 mm, height 4.7 mm	2.03.722	44,46
PF 5.0, cone 6.0 mm, height 6.7 mm	2.03.726	44,46
PF 6.0, cone 4.0 mm, height 4.7 mm	2.03.723	44,46
PF 6.0, cone 6.0 mm, height 6.7 mm	2.03.727	44,46
EASY temporary cap		
PF 3.5, cone 4.0 mm, height 5.0 mm	2.03.740	44
PF 3.5, cone 6.0 mm, height 7.0 mm	2.03.744	44
PF 4.0, cone 4.0 mm, height 5.0 mm	2.03.748	44
PF 4.0, cone 6.0 mm, height 7.0 mm	2.03.749	44
PF 4.5, cone 4.0 mm, height 5.0 mm	2.03.741	44,46
PF 4.5, cone 6.0 mm, height 7.0 mm	2.03.745	44,46,48
PF 5.0, cone 4.0 mm, height 5.0 mm	2.03.742	44,46
PF 5.0, cone 6.0 mm, height 7.0 mm	2.03.746	44,46,48
PF 6.0, cone 4.0 mm, height 5.0 mm	2.03.743	44,46
PF 6.0, cone 6.0 mm, height 7.0 mm	2.03.747	44,46,48
ELEMENT implant, incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.13.900	7
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.13.940	7
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.13.910	7
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.13.950	7
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.13.920	7
PF 3.5, endosseous Ø 3.5 mm, length 17.0 mm	4.13.930	7
PF 4.0, endosseous Ø 4.0 mm, length 6.5 mm	4.13.905	7
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.13.904	7
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.13.914	7
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.13.924	7
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.13.934	7
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.13.944	7
PF 4.5, endosseous Ø 4.2 mm, length 6.5 mm	4.13.906	7
PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4.13.901	7
PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4.13.941	7
PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4.13.911	7
PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4.13.951	7
PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4.13.921	7
PF 4.5, endosseous Ø 4.2 mm, length 17.0 mm	4.13.931	7
PF 5.0, endosseous Ø 5.0 mm, length 6.5 mm	4.13.907	7
PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4.13.902	7
PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4.13.942	7
PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4.13.912	7
PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4.13.952	7
PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4.13.922	7
PF 6.0, endosseous Ø 6.0 mm, length 6.5 mm	4.13.908	7
PF 6.0, endosseous Ø 6.0 mm, length 8.0 mm	4.13.903	7
PF 6.0, endosseous Ø 6.0 mm, length 9.5 mm	4.13.943	7

PF 6.0, endosseous Ø 6.0 mm, length 11.0 mm	4.13.913	7
PF 6.0, endosseous Ø 6.0 mm, length 12.5 mm	4.13.953	7
ELEMENT implant LC INICELL® , incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.23.712	5
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.713	5
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.714	5
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.715	5
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.716	5
PF 4.0, endosseous Ø 4.0 mm, length 6.5 mm	4.23.721	5
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.23.722	5
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.23.723	5
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.23.724	5
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.23.725	5
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.23.726	5
ELEMENT implant MC INICELL® , incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.23.512	5
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.513	5
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.514	5
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.515	5
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.516	5
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.23.522	5
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.23.523	5
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.23.524	5
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.23.525	5
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.23.526	5
PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4.23.532	5
PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4.23.533	5
PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4.23.534	5
PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4.23.535	5
PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4.23.536	5
PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4.23.542	5
PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4.23.543	5
PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.544	5
PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.545	5
PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.546	5
PF 6.0, endosseous Ø 6.0 mm, length 8.0 mm	4.23.552	5
PF 6.0, endosseous Ø 6.0 mm, length 9.5 mm	4.23.553	5
PF 6.0, endosseous Ø 6.0 mm, length 11.0 mm	4.23.554	5
PF 6.0, endosseous Ø 6.0 mm, length 12.5 mm	4.23.555	5
ELEMENT implant RC INICELL® , incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.23.112	5
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.113	5
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.114	5
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.115	5
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.116	5
PF 3.5, endosseous Ø 3.5 mm, length 17.0 mm	4.23.117	5
PF 4.0, endosseous Ø 4.0 mm, length 6.5 mm	4.23.121	5
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.23.122	5
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.23.123	5
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.23.124	5
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.23.125	5
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.23.126	5
PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4.23.131	5
PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4.23.132	5
PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4.23.133	5
PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4.23.134	5
PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4.23.135	5
PF 4.5, endosseous Ø 4.2 mm, length 17.0 mm	4.23.137	5
PF 5.0, endosseous Ø 5.0 mm, length 6.5 mm	4.23.141	5
PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4.23.142	5
PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4.23.143	5
PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.144	5
PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.145	5
PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.146	5
PF 6.0, endosseous Ø 6.0 mm, length 8.5 mm	4.23.151	5
PF 6.0, endosseous Ø 6.0 mm, length 8.0 mm	4.23.152	5
PF 6.0, endosseous Ø 6.0 mm, length 9.5 mm	4.23.153	5
PF 6.0, endosseous Ø 6.0 mm, length 11.0 mm	4.23.154	5
PF 6.0, endosseous Ø 6.0 mm, length 12.5 mm	4.23.155	5
ELEMENT profile drill for PF 3.0 , single use		
PF 3.0, for length 8.0 mm	3.03.740	11
PF 3.0, for length 9.5 mm	3.03.741	11
PF 3.0, for length 11.0 mm	3.03.742	11
PF 3.0, for length 12.5 mm	3.03.743	11
ELEMENT implants RC INICELL PF 3.0 , incl. healing cap		
PF 3.0, for length 8.0 mm	4.23.102	11
PF 3.0, for length 9.5 mm	4.23.103	11

PF 3.0, for length 11.0 mm	4.23.104	11
PF 3.0, for length 12.5 mm	4.23.105	11
ELEMENT profile drill , single use [4 pieces]		
3.5/3.5 mm, extra short, length 29.0 mm	3.03.651 Q4	10
4.0/4.0 mm, extra short, length 29.0 mm	3.03.657 Q4	10
4.2/4.5 mm, extra short, length 29.0 mm	3.03.653 Q4	10
5.0/5.0 mm, extra short, length 29.0 mm	3.03.655 Q4	10
6.0/6.0 mm, extra short, length 29.0 mm	3.03.659 Q4	10
Explantation drill		
short, for ELEMENT and CONTACT PF 3.5, external Ø 4.3 mm, internal Ø 3.8 mm, length 31.0 mm	3.03.303	58
short, for ELEMENT and CONTACT PF 4.0 and 4.5, external Ø 5.0 mm, internal Ø 4.5 mm, length 31.0 mm	3.03.304	58
short, for ELEMENT PF 5.0, CONTACT PF 5.0 and 6.0, external Ø 6.3 mm, internal Ø 5.3 mm, length 31.0 mm	3.03.305	58
short, for ELEMENT PF 6.0		
external Ø 7.3 mm, internal Ø 6.3 mm, length 31.0 mm	3.03.306	58
long, for ELEMENT and CONTACT PF 3.5,		
external Ø 4.3 mm, internal Ø 3.8 mm, length 37.0 mm	3.03.300	58
long, for ELEMENT and CONTACT PF 4.0 and 4.5,		
external Ø 5.0 mm, internal Ø 4.5 mm, length 37.0 mm	3.03.301	58
long, for ELEMENT PF 5.0, CONTACT PF 5.0 and 6.0,		
external Ø 6.3 mm, internal Ø 5.3 mm, length 37.0 mm	3.03.302	58

F Fabrication screw , for customizable gingiva former and VARIOtemp [4-lobe]		
PF 3.5, length 22.5 mm [4 pieces]	3.03.590 Q4	15
PF 4.0–6.0, length 23.4 mm [4 pieces]	3.03.591 Q4	15
Fabrication screw for VARIOmulti temporary cap [4-lobe], length 19.3 mm [4 pieces]		
	3.03.598 Q4	38

G Gauge for VARIO and VARIOmulti reamers for screw channel , for laboratory use		
	3.03.430	40,42
Gingiva former [4-lobe]		
PF 3.5, height 2.0 mm	4.03.520	15
PF 3.5, height 3.2 mm	4.03.530	15
PF 3.5, height 4.5 mm	4.03.540	15
PF 3.5, height 5.7 mm	4.03.560	15
PF 3.5, height 7.0 mm	4.03.550	15
PF 4.0, height 2.0 mm	4.03.524	15
PF 4.0, height 3.2 mm	4.03.534	15
PF 4.0, height 4.5 mm	4.03.544	15
PF 4.0, height 5.7 mm	4.03.564	15
PF 4.0, height 7.0 mm	4.03.554	15
PF 4.5, height 2.0 mm	4.03.521	15
PF 4.5, height 3.2 mm	4.03.531	15
PF 4.5, height 4.5 mm	4.03.541	15
PF 4.5, height 5.7 mm	4.03.561	15
PF 4.5, height 7.0 mm	4.03.551	15
PF 5.0, height 2.0 mm	4.03.522	15
PF 5.0, height 3.2 mm	4.03.532	15
PF 5.0, height 4.5 mm	4.03.542	15
PF 5.0, height 5.7 mm	4.03.562	15
PF 5.0, height 7.0 mm	4.03.552	15
PF 6.0, height 2.0 mm	4.03.523	15
PF 6.0, height 3.2 mm	4.03.533	15
PF 6.0, height 4.5 mm	4.03.543	15
PF 6.0, height 5.7 mm	4.03.563	15
PF 6.0, height 7.0 mm	4.03.553	15
Gingiva former narrow [4-lobe]		
PF 3.5, height 2.0 mm	4.04.310	15
PF 4.0, height 2.0 mm	4.04.311	15
PF 4.5, height 2.0 mm	4.04.312	15
PF 5.0, height 2.0 mm	4.04.313	15
PF 6.0, height 2.0 mm	4.04.314	15
PF 3.5, height 3.2 mm	4.04.320	15
PF 4.0, height 3.2 mm	4.04.321	15
PF 4.5, height 3.2 mm	4.04.322	15
PF 5.0, height 3.2 mm	4.04.323	15
PF 6.0, height 3.2 mm	4.04.324	15
PF 3.5, height 4.5 mm	4.04.330	15
PF 4.0, height 4.5 mm	4.04.331	15
PF 4.5, height 4.5 mm	4.04.332	15
PF 5.0, height 4.5 mm	4.04.333	15
PF 6.0, height 4.5 mm	4.04.334	15
PF 3.5, height 5.7 mm	4.04.340	15
PF 4.0, height 5.7 mm	4.04.341	15
PF 4.5, height 5.7 mm	4.04.342	15

PF 5.0, height 5.7 mm	4.04.343	15
PF 6.0, height 5.7 mm	4.04.344	15
PF 3.5, height 7.0 mm	4.04.350	15
PF 4.0, height 7.0 mm	4.04.351	15
PF 4.5, height 7.0 mm	4.04.352	15
PF 5.0, height 7.0 mm	4.04.353	15
PF 6.0, height 7.0 mm	4.04.354	15
Gingiva former for PF 3.0, (4-lobe)		
PF 3.0, height 3.2 mm	4.03.538	11
PF 3.0, height 4.5 mm	4.03.548	11
PF 3.0, height 7.0 mm	4.03.558	11
Gingiva former, customizable		
PF 3.5, height 7.5 mm	4.03.570	15
PF 4.0, height 7.5 mm	4.03.571	15
PF 4.5, height 7.5 mm	4.03.572	15
PF 5.0, height 7.5 mm	4.03.573	15
PF 6.0, height 7.5 mm	4.03.574	15
Gingiva former+ (4-lobe)		
PF 3.5, height 2.0 mm	4.03.525	15
PF 3.5, height 3.2 mm	4.03.535	15
Gold cap for bar, height 4.7 mm	2.03.335	50
Guiding sleeve for VECTODRILL™ pilot drill (4 pieces)		
Internal Ø 2.0 mm, length 6.0 mm	3.03.141 Q4	8,56
Guiding sleeve, length 5.0 mm, Ø 4.8 mm	3.04.080 Q4	56
Guiding cylinder for ELEMENT and CONTACT implants		
PF 3.5, external Ø 3.7 mm, length 3.0 mm	3.03.308	58
PF 4.0, external Ø 4.4 mm, length 3.0 mm	3.03.307	58
PF 6.0, external Ø 6.2 mm, length 3.0 mm	3.03.313	58
PF 4.5, external Ø 4.4 mm, length 3.0 mm	3.03.309	58
ELEMENT PF 5.0, 5.0 and 6.0, external Ø 5.2 mm, length 3.0 mm	3.03.310	58
Handle for dental laboratory, length 120.0 mm		
	3.03.250	20,55
Healing cap SE (4-lobe)		
PF 3.5, height 1.0 mm	4.03.515	15
PF 4.0, height 1.0 mm	4.03.519	15
PF 4.5, height 1.0 mm	4.03.516	15
PF 5.0, height 1.0 mm	4.03.517	15
PF 6.0, height 1.0 mm	4.03.518	15
Implant analog PF 3.0, length 14.0 mm		
	3.03.098	13
Implant analogs for CAD/CAM PF 3.0, length 11.0 mm		
	3.03.084	13
Implant analog		
PF 3.5, length 14.0 mm	3.03.090	20
PF 3.5, length 22.0 mm	3.03.060	20
PF 4.0, length 14.0 mm	3.03.095	20
PF 4.0, length 22.0 mm	3.03.061	20
PF 4.5, length 14.0 mm	3.03.091	20
PF 4.5, length 22.0 mm	3.03.065	20
PF 5.0, length 14.0 mm	3.03.092	20
PF 5.0, length 22.0 mm	3.03.062	20
PF 6.0, length 15.0 mm	3.03.093	20
PF 6.0, length 22.0 mm	3.03.063	20
Implant-analog for CAD/CAM		
PF 3.5, length 11.4 mm	3.03.085	20
PF 4.0, length 11.4 mm	3.03.086	20
PF 4.5, length 11.4 mm	3.03.087	20
PF 5.0, length 11.4 mm	3.03.088	20
PF 6.0, length 11.4 mm	3.03.089	20
Impression coping for closed tray technique, single use, repositionable, screw-retained, aluminum, anodized, short, including screw		
PF 3.5, external Ø 3.9 mm, height 8.0 mm	5.03.074	16
PF 4.0, external Ø 5.0 mm, height 8.0 mm	5.03.079	16
PF 4.5, external Ø 5.5 mm, height 8.0 mm	5.03.075	16
PF 5.0, external Ø 6.0 mm, height 8.0 mm	5.03.076	16
PF 6.0, external Ø 7.0 mm, height 8.0 mm	5.03.077	16
Impression coping for closed tray technique, single use, repositionable, screw-retained, short		
PF 3.5, external Ø 3.9 mm, height 8.0 mm	3.03.074	16
PF 4.0, external Ø 5.0 mm, height 8.0 mm	3.03.079	16
PF 4.5, external Ø 5.5 mm, height 8.0 mm	3.03.075	16
PF 5.0, external Ø 6.0 mm, height 8.0 mm	3.03.076	16
PF 6.0, external Ø 7.0 mm, height 8.0 mm	3.03.077	16
Impression coping for closed tray technique, single use, repositionable, screw-retained, aluminum, anodized, long, including screw		
PF 3.5, external Ø 3.9 mm, height 12.0 mm	5.03.014	16
PF 4.0, external Ø 5.0 mm, height 12.0 mm	5.03.019	16
PF 4.5, external Ø 5.5 mm, height 12.0 mm	5.03.015	16

PF 5.0, external Ø 6.0 mm, height 12.0 mm	5.03.016	16
PF 6.0, external Ø 7.0 mm, height 12.0 mm	5.03.017	16
Impression coping for closed tray technique, single use, repositionable, screw-retained, long		
PF 3.5, external Ø 3.9 mm, height 12.0 mm	3.03.014	16
PF 4.0, external Ø 5.0 mm, height 12.0 mm	3.03.019	16
PF 4.5, external Ø 5.5 mm, height 12.0 mm	3.03.015	16
PF 5.0, external Ø 6.0 mm, height 12.0 mm	3.03.016	16
PF 6.0, external Ø 7.0 mm, height 12.0 mm	3.03.017	16
Impression coping for closed tray technique, reusable, repositionable, screw-retained, titanium short, including screw		
PF 3.5, external Ø 3.9 mm, height 8.0 mm	5.04.030	16
PF 4.0, external Ø 5.0 mm, height 8.0 mm	5.04.031	16
PF 4.5, external Ø 5.5 mm, height 8.0 mm	5.04.032	16
PF 5.0, external Ø 6.0 mm, height 8.0 mm	5.04.033	16
PF 6.0, external Ø 7.0 mm, height 8.0 mm	5.04.034	16
Impression coping for closed tray technique, reusable, repositionable, screw-retained, short		
PF 3.5, external Ø 3.9 mm, height 8.0 mm	3.04.030	16
PF 4.0, external Ø 5.0 mm, height 8.0 mm	3.04.031	16
PF 4.5, external Ø 5.5 mm, height 8.0 mm	3.04.032	16
PF 5.0, external Ø 6.0 mm, height 8.0 mm	3.04.033	16
PF 6.0, external Ø 7.0 mm, height 8.0 mm	3.04.034	16
Impression coping for closed tray technique, reusable, repositionable, screw-retained, titanium long, including screw		
PF 3.5, External-Ø 3.9 mm, Height 12.0 mm	5.04.046	16
PF 4.0, External-Ø 5.0 mm, Height 12.0 mm	5.04.047	16
PF 4.5, External-Ø 5.5 mm, Height 12.0 mm	5.04.048	16
PF 5.0, External-Ø 6.0 mm, Height 12.0 mm	5.04.049	16
PF 6.0, External-Ø 7.0 mm, Height 12.0 mm	5.04.050	16
Impression coping for closed tray technique, reusable, repositionable, screw-retained, long		
PF 3.5, external Ø 3.9 mm, height 12.0 mm	3.04.046	16
PF 4.0, external Ø 5.0 mm, height 12.0 mm	3.04.047	16
PF 4.5, external Ø 5.5 mm, height 12.0 mm	3.04.048	16
PF 5.0, external Ø 6.0 mm, height 12.0 mm	3.04.049	16
PF 6.0, external Ø 7.0 mm, height 12.0 mm	3.04.050	16
Impression coping for open tray technique, single use, retentive, screw-retained, conical		
PF 4.0, external Ø 5.0 mm, height 10.0 mm	3.03.078	17
PF 4.5, external Ø 5.5 mm, height 10.0 mm	3.03.071	17
PF 5.0, external Ø 6.0 mm, height 10.0 mm	3.03.072	17
PF 6.0, external Ø 7.0 mm, height 10.0 mm	3.03.073	17
Impression coping for open tray technique, single use, retentive, screw-retained, cylindrical		
PF 3.5, external Ø 3.8 mm, height 10.0 mm	3.03.010	17
PF 4.0, external Ø 4.3 mm, height 10.0 mm	3.03.018	17
PF 4.5, external Ø 4.8 mm, height 10.0 mm	3.03.011	17
PF 5.0, external Ø 5.3 mm, height 10.0 mm	3.03.012	17
PF 6.0, external Ø 6.3 mm, height 10.0 mm	3.03.013	17
Impression coping for open tray technique, reusable, retentive, screw-retained, conical		
PF 4.0, external Ø 5.0 mm, height 16.0 mm	3.04.037	17
PF 4.5, external Ø 5.5 mm, height 16.0 mm	3.04.038	17
PF 5.0, external Ø 6.0 mm, height 16.0 mm	3.04.039	17
PF 6.0, external Ø 7.0 mm, height 16.0 mm	3.04.040	17
Impression coping for PF 3.0, for open tray technique, reusable, retentive, screw-retained PF 3.0, external 3.3 mm, height 16.0 mm		
	3.04.028	12
Impression coping for open tray technique, reusable, retentive, screw-retained, cylindrical		
PF 3.5, external Ø 3.8 mm, height 16.0 mm	3.04.020	17
PF 4.0, external Ø 4.3 mm, height 16.0 mm	3.04.021	17
PF 4.5, external Ø 4.8 mm, height 16.0 mm	3.04.022	17
PF 5.0, external Ø 5.3 mm, height 16.0 mm	3.04.023	17
PF 6.0, external Ø 6.3 mm, height 16.0 mm	3.04.024	17
Impression coping for bar, Ø 6.0 mm, height 5.0 mm	3.03.101	19,50
Initial drill, guided, length 28.5 mm	3.04.110	56
Instrument holder set, for surgical cassette		
consisting of 1 holder, size M	8.03.091	57
consisting of 2 holders, size S	8.03.090 Q2	57
Insertion device for implant analog for CAD/CAM		
PF 3.5, length 35.0 mm	3.03.158	13,20,55
PF 4.0-6.0, length 35.0 mm	3.03.159	20,55
Insertion device for VARIOmulti analog for CAD/CAM	3.03.157	21,38,55
Laboratory cylindrical pin (5 pieces)		
PF 3.5, length 70.0 mm	2.03.450 Q5	12,33,36
PF 4.0-6.0, length 70.0 mm	2.03.451 Q5	33,36

Laboratory screw		
PF 3.5, length 25.0 mm	3.03.515	33
PF 3.5, length 25.0 mm [5 pieces]	3.03.515 Q5	33
PF 4.0-6.0, length 25.0 mm	3.03.516	33
PF 4.0-6.0, length 25.0 mm [5 pieces]	3.03.516 Q5	33
LOCATOR® impression coping [4 pieces]	8505	19,52
LOCATOR® block-out spacer [20 pieces]	8514	52
LOCATOR® abutment		
PF 3.5, collar height 0.73 mm	8875	51
PF 3.5, collar height 2.0 mm	8876	51
PF 3.5, collar height 3.0 mm	8877	51
PF 3.5, collar height 4.0 mm	8878	51
PF 3.5, collar height 5.0 mm, only available in the US	8879	51
PF 3.5, collar height 6.0 mm, only available in the US	8880	51
PF 4.0, collar height 1.0 mm	8461	51
PF 4.0, collar height 2.0 mm	8462	51
PF 4.0, collar height 3.0 mm	8463	51
PF 4.0, collar height 4.0 mm	8464	51
PF 4.0, collar height 5.0 mm	8465	51
PF 4.0, collar height 6.0 mm	8466	51
PF 4.5, collar height 1.0 mm	8786	51
PF 4.5, collar height 2.0 mm	8787	51
PF 4.5, collar height 3.0 mm	8788	51
PF 4.5, collar height 4.0 mm	8789	51
PF 4.5, collar height 5.0 mm	8790	51
PF 4.5, collar height 6.0 mm	8791	51
PF 5.0, collar height 1.0 mm	8792	51
PF 5.0, collar height 2.0 mm	8793	51
PF 5.0, collar height 3.0 mm	8794	51
PF 5.0, collar height 4.0 mm	8795	51
PF 5.0, collar height 5.0 mm	8796	51
PF 5.0, collar height 6.0 mm	8797	51
PF 6.0, collar height 1.0 mm	8881	51
PF 6.0, collar height 2.0 mm	8882	51
PF 6.0, collar height 3.0 mm	8883	51
PF 6.0, collar height 4.0 mm	8884	51
LOCATOR® abutment and collar for VARIOmulti [2 pieces]		
collar height 3.0 mm	8909-2	51
LOCATOR® analog		
Ø 4.0 mm [preferably used with PF 3.5, 4.0 and 4.5] [4 pieces]	8530	21,52
Ø 5.0 mm [preferably used with PF 5.0 and 6.0] [4 pieces]	8516	21,52
LOCATOR® insert for hand piece and for short MONO		
insert device		
length 23.0 mm	8913	52
length 29.0 mm	8914	52
LOCATOR® male replacement [4 pieces]		
blue	8529	51
pink	8527	51
clear	8524	51
LOCATOR® male replacement, for extended range [4 pieces]		
green	8547	51
orange	8915	51
red	8548	51
LOCATOR® core tool	8393	52
LOCATOR® laboratory set [pack contains 2 sets]	8519-2	51
LOCATOR® laboratory set, for extended range		
[pack contains 2 sets]	8540-2	51
LOCATOR® parallel posts [4 pieces]	8517	52
LOCATOR® male processing, black [20 pieces]	8515-20	52
LOCATOR® angle measurement guide, height 15.0 mm, width 50.0 mm		
	9530	52

Milling abutment		
PF 3.5, height 11.0 mm	4.03.420	49
PF 4.0, height 12.0 mm	4.03.428	49
PF 4.5, height 12.0 mm	4.03.421	49
PF 5.0, height 12.0 mm	4.03.422	49
PF 6.0, height 12.0 mm	4.03.423	49
Milling abutment for CAD/CAM Type II, incl. abutment screw		
PF 3.5, length 15.0 mm, Ø 8.0 mm	1.04.401	35
PF 4.0, length 15.0 mm, Ø 11.5 mm	1.04.403	35
PF 4.5, length 15.0 mm, Ø 11.5 mm	1.04.405	35
PF 5.0, length 15.0 mm, Ø 11.5 mm	1.04.407	35
PF 6.0, length 15.0 mm, Ø 11.5 mm	1.04.409	35
MONO torque ratchet, length 110.0 mm	3.03.160	54
MONO insertion device		
short, length 15.4 mm	3.03.162	40,42,55
long, length 25.8 mm	3.03.163	40,42,55

MONO insertion device for retentive anchor		
length 26.0 mm, Ø 8.5 mm	3.03.169	49
MONO guide key, length 94.7 mm	3.03.203	54
MONO screwdriver (4-lobe)		
extra short, length 14.5 mm, shaft length 5.1 mm	3.03.165	55
short, length 22.2 mm, shaft length 10.3 mm	3.03.166	55
long, length 28.2 mm, shaft length 16.3 mm	3.03.167	55
MONO circlip [2 pieces]	2.03.170 Q2	54
Mucosa punch, reusable		
PF 3.5, length 27.0 mm	3.03.315	10
PF 4.0, length 27.0 mm	3.03.316	10
PF 4.5, length 27.0 mm	3.03.320	10
PF 5.0, length 27.0 mm	3.03.317	10
PF 6.0, length 27.0 mm	3.03.318	10

NEVO implant LC INICELL®, incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.23.762	4
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.763	4
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.764	4
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.765	4
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.766	4
PF 4.0, endosseous Ø 4.0 mm, length 6.5 mm	4.23.771	4
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.23.772	4
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.23.773	4
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.23.774	4
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.23.775	4
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.23.776	4
PF 4.5, endosseous Ø 4.2 mm, length 6.5 mm	4.23.781	4
PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4.23.782	4
PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4.23.783	4
PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4.23.784	4
PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4.23.785	4
PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4.23.786	4
PF 5.0, endosseous Ø 5.0 mm, length 6.5 mm	4.23.791	4
PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4.23.792	4
PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4.23.793	4
PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.794	4
PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.795	4
PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.796	4
NEVO implant MC INICELL®, incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.23.812	4
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.813	4
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.814	4
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.815	4
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.816	4
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.23.822	4
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.23.823	4
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.23.824	4
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.23.825	4
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.23.826	4
PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4.23.832	4
PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4.23.833	4
PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4.23.834	4
PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4.23.835	4
PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4.23.836	4
PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4.23.842	4
PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4.23.843	4
PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.844	4
PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.845	4
PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.846	4
NEVO implant RC INICELL®, incl. healing cap		
PF 3.5, endosseous Ø 3.5 mm, length 8.0 mm	4.23.012	4
PF 3.5, endosseous Ø 3.5 mm, length 9.5 mm	4.23.013	4
PF 3.5, endosseous Ø 3.5 mm, length 11.0 mm	4.23.014	4
PF 3.5, endosseous Ø 3.5 mm, length 12.5 mm	4.23.015	4
PF 3.5, endosseous Ø 3.5 mm, length 14.0 mm	4.23.016	4
PF 4.0, endosseous Ø 4.0 mm, length 6.5 mm	4.23.021	4
PF 4.0, endosseous Ø 4.0 mm, length 8.0 mm	4.23.022	4
PF 4.0, endosseous Ø 4.0 mm, length 9.5 mm	4.23.023	4
PF 4.0, endosseous Ø 4.0 mm, length 11.0 mm	4.23.024	4
PF 4.0, endosseous Ø 4.0 mm, length 12.5 mm	4.23.025	4
PF 4.0, endosseous Ø 4.0 mm, length 14.0 mm	4.23.026	4
PF 4.5, endosseous Ø 4.2 mm, length 6.5 mm	4.23.031	4
PF 4.5, endosseous Ø 4.2 mm, length 8.0 mm	4.23.032	4
PF 4.5, endosseous Ø 4.2 mm, length 9.5 mm	4.23.033	4
PF 4.5, endosseous Ø 4.2 mm, length 11.0 mm	4.23.034	4
PF 4.5, endosseous Ø 4.2 mm, length 12.5 mm	4.23.035	4
PF 4.5, endosseous Ø 4.2 mm, length 14.0 mm	4.23.036	4
PF 5.0, endosseous Ø 5.0 mm, length 6.5 mm	4.23.041	4

PF 5.0, endosseous Ø 5.0 mm, length 8.0 mm	4.23.042	4
PF 5.0, endosseous Ø 5.0 mm, length 9.5 mm	4.23.043	4
PF 5.0, endosseous Ø 5.0 mm, length 11.0 mm	4.23.044	4
PF 5.0, endosseous Ø 5.0 mm, length 12.5 mm	4.23.045	4
PF 5.0, endosseous Ø 5.0 mm, length 14.0 mm	4.23.046	4
Occlusal screw for bar (4-lobe), length 4.3 mm	4.03.506	50
Occlusal screw (4-lobe), length 3.5 mm	4.03.507	37, 41
Permanent filter , 1200 sterilization cycles length 95.0 mm, width 215.0 mm	ER802.020	57
Positioning handle , length 17.0 mm, Ø 6.0 mm	3.03.522	16, 17
Positioning handle for angled VARIO and VARIOmulti abutments , length 25.0 mm, Ø 4.0 mm	3.03.521	40, 42
Prosthetic cassette , incl. screw organizer length 190.0 mm, width 140.0 mm, height 58.0 mm	1.03.022	57
Profile drill CONTACT AND ELEMENT , guided		
Profile drill CONTACT MC, Ø 3.5 mm, length 34.0 mm	3.04.171	56
Profile drill CONTACT MC, Ø 4.0 mm, length 34.0 mm	3.04.172	56
Profile drill CONTACT MC, Ø 4.5 mm, length 34.0 mm	3.04.173	56
Profile drill CONTACT RC, Ø 3.5 mm, length 32.5 mm	3.04.161	56
Profile drill CONTACT RC Ø 4.0 mm, length 32.5 mm	3.04.162	56
Profile drill CONTACT RC Ø 4.5 mm, length 32.5 mm	3.04.163	56
Profile drill ELEMENT MC, Ø 3.5 mm, length 31.5 mm	3.04.151	56
Profile drill ELEMENT MC, Ø 4.0 mm, length 34.5 mm	3.04.152	56
Profile drill ELEMENT MC, Ø 4.5 mm, length 37.5 mm	3.04.153	56
Retentive anchor		
PF 4.0, short, height 1.8 mm	4.03.048	49
PF 4.0, long, height 3.0 mm	4.03.049	49
PF 4.5, short, height 1.8 mm	4.03.040	49
PF 4.5, long, height 3.0 mm	4.03.041	49
PF 5.0, short, height 1.8 mm	4.03.042	49
PF 5.0, long, height 3.0 mm	4.03.043	49
Retentive anchor analog , length 13.0 mm	3.03.033	21, 49
Scan abutment PF 3.0	3.03.774	13
Scan abutment		
PF 3.5	3.03.775	18
PF 4.0	3.03.776	18
PF 4.5	3.03.777	18
PF 5.0	3.03.778	18
PF 6.0	3.03.779	18
Scan abutment, including screw		
PF 3.5	5.03.775	18
PF 4.0	5.03.776	18
PF 4.5	5.03.777	18
PF 5.0	5.03.778	18
PF 6.0	5.03.779	18
Screw for impression copings , reusable (4-lobe)		
PF 3.5, extra short, length 12.5 mm	3.03.572	12, 16, 17, 18
PF 3.5, short, length 16.5 mm	3.03.573	16, 17
PF 3.5, long, length 21.5 mm	3.03.574	12, 17
PF 3.5, extra long, length 27.5 mm	3.03.580	12, 17
PF 4.0–6.0, extra short, length 13.2 mm	3.03.575	16, 17, 18
PF 4.0–6.0, short, length 17.2 mm	3.03.576	16, 17
PF 4.0–6.0, long, length 22.2 mm	3.03.577	17
PF 4.0–6.0, extra long, length 28.2 mm	3.03.581	17
Screw organizer for prosthetic cassette length 56.0 mm, width 47.0 mm, height 28.0 mm	8.03.019	57
Screwdriver for hand piece (4-lobe)		
extra short, length 17.0 mm, shaft length 3.5 mm	3.03.500	54
extra long, length 38.0 mm, shaft length 24.5 mm	3.03.503	54
short, length 22.0 mm, shaft length 8.0 mm	3.03.501	54
long, length 28.0 mm, shaft length 14.5 mm	3.03.502	54
Seating instrument for guiding sleeve Ø 4.8 mm	3.04.100	56
Silicone holder set , for surgical and prosthetic cassettes	1.03.056	57
Solder pin for bar , length 13.5 mm	3.03.151	50
Single-use-paper-filter (100 per pack) length 118.0 mm, width 235.0 mm	ER802.000N	57
NEVO/ELEMENT profile drill , reusable, stainless steel		
PF 3.5, extra short, L 29.0 mm	3.03.751	10
PF 4.0, extra short, L 29.0 mm	3.03.752	10
PF 4.5, extra short, L 29.0 mm	3.03.753	10
PF 5.0, extra short, L 29.0 mm	3.03.754	10
Surgical cassette for guided surgery , for mechanical cleaning	1.04.020	57

Surgical cassette , for mechanical cleaning length 274.8 mm, width 176.0 mm, height 63.6 mm	1.03.030	57
Thread tap , reusable		
endosseous Ø 3.5 mm, length 34.0 mm	3.03.680	10
endosseous Ø 4.0 mm, length 34.0 mm	3.03.682	10
endosseous Ø 4.2 mm, length 34.0 mm	3.03.684	10
endosseous Ø 5.0 mm, length 34.0 mm	3.03.686	10
endosseous Ø 6.0 mm, length 34.0 mm	3.03.688	10
Titanium Base bridge for CAD/CAM , incl. abutment screw		
PF 3.5, height 5.2 mm	1.04.760	33
PF 4.0, height 5.2 mm	1.04.761	33
PF 4.5, height 5.2 mm	1.04.762	33
PF 5.0, height 5.2 mm	1.04.763	33
PF 6.0, height 5.2 mm	1.04.764	33
Titanium base with hexagon for CAD/CAM , incl. abutment screw		
PF 3.5, height 5.2 mm	1.04.750	33
PF 4.0, height 5.2 mm	1.04.751	33
PF 4.5, height 5.2 mm	1.04.752	33
PF 5.0, height 5.2 mm	1.04.753	33
PF 6.0, height 5.2 mm	1.04.754	33
Titanium cap for bar , height 4.7 mm	4.03.070	50
Ultrasonic cleaning-cassette length 160.0 mm, width 72.0 mm, height 28.0 mm	8.03.059	57
VARIO abutment 17° set		
Type A, PF 3.5, height 5.6 mm, shoulder height 0.5 mm	1.03.160	41
Type A, PF 4.0, height 5.6 mm, shoulder height 0.5 mm	1.03.161	41
Type A, PF 4.5, height 5.6 mm, shoulder height 0.5 mm	1.03.162	41
Type A, PF 5.0, height 5.6 mm, shoulder height 0.5 mm	1.03.163	41
Type B, PF 3.5, height 5.6 mm, shoulder height 0.5 mm	1.03.180	41
Type B, PF 4.0, height 5.6 mm, shoulder height 0.5 mm	1.03.181	41
Type B, PF 4.5, height 5.6 mm, shoulder height 0.5 mm	1.03.182	41
Type B, PF 5.0, height 5.6 mm, shoulder height 0.5 mm	1.03.183	41
VARIOeco burn-out plastic cap , for titanium base		
PF 3.5, height 12.0 mm	2.03.790	33
PF 4.0, height 12.0 mm	2.03.791	33
PF 4.5, height 12.0 mm	2.03.792	33
PF 5.0, height 12.0 mm	2.03.793	33
PF 6.0, height 12.0 mm	2.03.794	33
VARIO reamer for screw channel		
PF 3.5, length 44.0 mm	3.03.435	42
PF 4.0–6.0, length 44.0 mm	3.03.436	42
VARIO guide pin for VARIO reamer		
PF 4.0, length 12.5 mm	3.03.425	42
PF 4.5–6.0, length 12.5 mm	3.03.423	42
VARIO guide pin for VARIO/ VARIOmulti reamer		
PF 3.5, length 15.0 mm	3.03.424	40, 42
VARIOflex abutment set for bridge		
PF 3.5, height 12.0 mm	1.04.835	36
PF 4.0, height 12.0 mm	1.04.836	36
PF 4.5, height 12.0 mm	1.04.837	36
PF 5.0, height 12.0 mm	1.04.838	36
PF 6.0, height 12.0 mm	1.04.839	36
VARIOflex abutment set for crown		
PF 3.5, height 12.0 mm	1.04.830	36
PF 4.0, height 12.0 mm	1.04.831	36
PF 4.5, height 12.0 mm	1.04.832	36
PF 5.0, height 12.0 mm	1.04.833	36
PF 6.0, height 12.0 mm	1.04.834	36
VARIOflex burn-out plastic cap		
PF 3.5, height 11.5 mm	2.03.840	36
PF 4.0, height 11.5 mm	2.03.841	36
PF 4.5, height 11.5 mm	2.03.842	36
PF 5.0, height 11.5 mm	2.03.843	36
PF 6.0, height 11.5 mm	2.03.844	36
VARIO gold abutment for bridge		
PF 3.5, height 12.7 mm, cone 3.5 mm	2.03.400	41
PF 4.0, height 12.7 mm, cone 3.5 mm	2.03.404	41
PF 4.5, height 12.7 mm, cone 3.5 mm	2.03.401	41
PF 5.0, height 12.7 mm, cone 3.5 mm	2.03.402	41
PF 6.0, height 12.7 mm, cone 3.5 mm	2.03.403	41
VARIO gold abutment for crown		
PF 3.5, height 12.7 mm, cone 3.5 mm	2.03.410	41
PF 4.0, height 12.7 mm, cone 3.5 mm	2.03.414	41
PF 4.5, height 12.7 mm, cone 3.5 mm	2.03.411	41
PF 5.0, height 12.7 mm, cone 3.5 mm	2.03.412	41
PF 6.0, height 12.7 mm, cone 3.5 mm	2.03.413	41

VARIOmulti impression coping , Ø 5.3 mm, height 18.0 mm	3.04.805	19,38
VARIOmulti abutment angled , 17°, with handle and abutment screw, sterile		
PF 3.5, collar height 1.6 mm	4.03.300S	37
PF 3.5, collar height 2.5 mm	4.03.310S	37
PF 4.0, collar height 1.6 mm	4.03.301S	37
PF 4.0, collar height 2.5 mm	4.03.311S	37
PF 4.5, collar height 1.6 mm	4.03.302S	37
PF 4.5, collar height 2.5 mm	4.03.312S	37
PF 5.0, collar height 1.6 mm	4.03.303S	37
PF 5.0, collar height 2.5 mm	4.03.313S	37
PF 6.0, collar height 1.6 mm	4.03.304S	37
VARIOmulti abutment angled , 30°, with handle and abutment screw, sterile		
PF 3.5, collar height 1.2 mm	4.03.305S	37
PF 3.5, collar height 2.5 mm	4.03.315S	37
PF 4.0, collar height 1.2 mm	4.03.306S	37
PF 4.0, collar height 2.5 mm	4.03.316S	37
PF 4.5, collar height 1.2 mm	4.03.307S	37
PF 4.5, collar height 2.5 mm	4.03.317S	37
PF 5.0, collar height 1.2 mm	4.03.308S	37
PF 5.0, collar height 2.5 mm	4.03.318S	37
PF 6.0, collar height 1.2 mm	4.03.309S	37
VARIOmulti abutment , with handle, sterile		
PF 3.5, collar height 0.8 mm	4.03.600S	37
PF 3.5, collar height 2.0 mm	4.03.605S	37
PF 3.5, collar height 3.0 mm	4.03.610S	37
PF 4.0, collar height 0.8 mm	4.03.601S	37
PF 4.0, collar height 2.0 mm	4.03.606S	37
PF 4.0, collar height 3.0 mm	4.03.611S	37
PF 4.5, collar height 0.8 mm	4.03.602S	37
PF 4.5, collar height 2.0 mm	4.03.607S	37
PF 4.5, collar height 3.0 mm	4.03.612S	37
PF 5.0, collar height 0.8 mm	4.03.603S	37
PF 5.0, collar height 2.0 mm	4.03.608S	37
PF 5.0, collar height 3.0 mm	4.03.613S	37
PF 6.0, collar height 1.5 mm	4.03.604S	37
VARIOmulti analog , Ø 4.8 mm, height 21.2 mm	3.03.800	21,38
VARIOmulti analog for CAD/CAM , titanium	3.03.083	21,38
VARIOmulti reamer for screw channel , length 40.0 mm	3.03.437	40
VARIOmulti gold cap , incl. burn-out plastic cylinder, Ø 4.8 mm, height 4.2/13.5 mm	2.03.600	39
VARIOmulti burn-out cap (2 pieces) Ø 4.8 mm, height 13.5 mm	2.03.601 Q2	39
VARIOmulti temporary cap , incl. fabrication screw Ø 5.2 mm, height 15.0 mm	3.03.804	38
VARIOmulti scan abutment , titanium, surface treated Ø 4.5 mm, height 8.0 mm	3.03.780	18,39
VARIOmulti scan abutment , short, titanium, surface treated Ø 5.0 mm, height 5.0 mm	3.03.781	18,39
VARIOmulti protective cap Ø 5.3 mm, height 4.5 mm	4.03.801	38
VARIOmulti titanium base for CAD/CAM , incl. occlusal screw, titan/titanium alloy Ø 4.8 mm, height 4.5 mm	1.04.850	39
VARIOmulti titanium base for CAD/CAM , customizable, incl. occlusal screw, titanium/titanium alloy Ø 4.8 mm, height 9.0 mm	1.04.851	39
VARIO 17° gold screw seat (fits all platform sizes) Ø 2.9 mm, height 2.0/11.3 mm	2.03.610	41
VARIOtemp abutment set for bridges		
PF 3.5, height 12.0 mm	1.04.085	32
PF 4.0, height 12.0 mm	1.04.086	32
PF 4.5, height 12.0 mm	1.04.087	32
PF 5.0, height 12.0 mm	1.04.088	32
PF 6.0, height 12.0 mm	1.04.089	32
VARIOtemp abutment set for crowns		
PF 3.5, height 12.0 mm	1.04.080	32
PF 4.0, height 12.0 mm	1.04.081	32
PF 4.5, height 12.0 mm	1.04.082	32
PF 5.0, height 12.0 mm	1.04.083	32
PF 6.0, height 12.0 mm	1.04.084	32
VARIO/VARIOmulti reamer for base PF 3.5–4.0, length 16.0 mm	3.03.420	40,42
VARIO/VARIOmulti reamer for base PF 4.5–6.0, length 16.0 mm	3.03.421	42
VARIOunite abutment PF 3.0 for crown	1.04.138	12
VARIOunite burn-out plastic cap PF 3.0	2.03.848	12
VECTOdrill™ twist drill , single use (4 pieces)		
Pilot drill Ø 2.0 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.624 Q4	9

Pilot drill Ø 2.0 mm, short, length 34.0 mm	3.03.610 Q4	9
Pilot drill Ø 2.0 mm, long, length 40.0 mm	3.03.611 Q4	9,11
Drill Ø 2.8 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.625 Q4	9
Drill Ø 2.8 mm, short, length 34.0 mm	3.03.612 Q4	9,11
Drill Ø 2.8 mm, long, length 40.0 mm	3.03.613 Q4	9
Drill Ø 3.5 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.626 Q4	9
Drill Ø 3.5 mm, short, length 34.0 mm	3.03.614 Q4	9
Drill Ø 3.5 mm, long, length 40.0 mm	3.03.615 Q4	9
Drill Ø 4.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.627 Q4	9
Drill Ø 4.3 mm, short, length 34.0 mm	3.03.616 Q4	9
Drill Ø 4.3 mm, long, length 40.0 mm	3.03.617 Q4	9
Drill Ø 5.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.628 Q4	9
Drill Ø 5.3 mm, short, length 34.0 mm	3.03.618 Q4	9
VECTOdrill™ twist drill , reusable		
Pilot drill Ø 2.0 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.710	9
Pilot drill Ø 2.0 mm, short, length 34.0 mm	3.03.720	9
Pilot drill Ø 2.0 mm, long, length 40.0 mm	3.03.730	9,11
Drill Ø 2.8 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.712	
Drill Ø 2.8 mm, short, length 34.0 mm	3.03.722	9
Drill Ø 2.8 mm, long, length 40.0 mm	3.03.732	9
Drill Ø 3.5 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.714	9
Drill Ø 3.5 mm, short, length 34.0 mm	3.03.724	9
Drill Ø 3.5 mm, long, length 40.0 mm	3.03.734	9
Drill Ø 4.3 mm, extra short, length 29.0 mm, for implants of length 6.5–14.0 mm	3.03.716	9
Drill Ø 4.3 mm, short, length 34.0 mm	3.03.726	9
Drill Ø 4.3 mm, long, length 40.0 mm	3.03.736	9
X-ray reference sphere , Ø 5.0 mm	3.03.140	8
X-ray template , for planning with two-dimensional x-ray devices		
for the NEVO implant line	Fo_20d305	8
for the CONTACT implant line	Fo_20d185	8
for the ELEMENT implant line	Fo_20d184	8,11

Torque values

www.ifu-tm.com/THM61122

Abutment/screw	Torque values in Ncm				
	10	15	20	25	30
Healing cap Gingiva former Gingiva former+ Gingiva former narrow 	PF 3.0				
	PF 3.5				
	PF 4.0				
	PF 4.5				
	PF 5.0				
Abutment screws 		PF 3.0			
		PF 3.5			
				PF 4.0	
				PF 4.5	
				PF 5.0	
Dynamic abutment screw 		PF 3.5			
				PF 4.0	
				PF 4.5	
Abutment screw in combination with ART abutment 		PF 3.5	PF 4.0		
			PF 4.5		
			PF 5.0		
VARIOmulti abutment 		PF 3.5		PF 4.0	
				PF 4.5	
				PF 5.0	
				PF 6.0	
VARIOmulti protective cap 	PF 3.5				
	PF 4.0				
	PF 4.5				
	PF 5.0				
	PF 6.0				
Occlusal screw (VARIOmulti, VARIO 17°, bar) Occlusal closure screw, CAD/CAM bar 		PF 3.5			
		PF 4.0			
		PF 4.5			
		PF 5.0			
Retentive anchor 				PF 4.0	
				PF 4.5	
				PF 5.0	
ZEST LOCATOR® abutment 			PF 3.5		
					PF 4.0
					PF 4.5
					PF 5.0
ZEST LOCATOR® abutment and collar for VARIOmulti 			PF 4.0		
			PF 4.5		
			PF 5.0		
			PF 6.0		

New abutment screws must always be used for permanent insertion of the supraconstruction in the mouth.

Symbols



Manufacturer: Thommen Medical Ltd
Neckarsulmstrasse 28
2540 Grenchen, Switzerland
www.thommenmedical.com



Batch code



Use by date



Date of manufacture



Sterilized using irradiation



Single sterile barrier system



Single sterile barrier system with
protective packaging inside



Not more than 20 processing cycles



European representative



Temperature limitation



Do not re-use



Non-sterile



Attention



Article number



Manufacturer's declaration that the product com-
plies with the applicable EU legislation



Consult instructions for use or consult electronic
instructions for use



Do not resterilize



Do not use if package is damaged and consult in-
structions for use



Atmospheric pressure limitation



Importer



Distributor



Keep away from sunlight

Rx only

May only be sold to and prescribed by
physicians (USA)



Medical device



Unique device identifier

Sterile indicator – red means it has passed through a
source of radiation



[illegible]



HEADQUARTERS

Thommen Medical AG
Neckarsulmstrasse 28
2540 Grenchen | Switzerland
Tel. +41 61 965 90 20
Fax +41 61 965 90 21
info@thommenmedical.com



SUBSIDIARIES/NATIONAL DISTRIBUTORS

AUSTRIA

Thommen Medical Austria GmbH
Mühlgasse 3
2322 Zwölfaxing | Austria
Tel. +43 660 2011953
info@thommenmedical.at

BENELUX

Thommen Medical Benelux B.V.
Dierenriem 1
3738 TP Maartensdijk | Netherlands
Tel. +31 30 68 68 468
Info.benelux@thommenmedical.nl

CHINA

Shanghai Yujing Trading Co., Ltd.
Room 1112 | Block A | SOHO Zhongshan Plaza
No. 1055 West Zhongshan Rd | Changning District
200051 Shanghai | P.R. China
Tel. +86 21 80121250
Fax +86 21 62175264
sy@shanghaiyujing.com

CZECH REPUBLIC

C. Witt Dental spol. s r.o.
Bohumínská 1227/98
710 00 Slezská Ostrava | Czech Republic
Tel. +420 739 043 449
office@cwittdental.cz

FINLAND

B Imports Oy
Fabianinkatu 31 C
00100 Helsinki | Finland
Tel. +358 40 070 0193
thomas@betterbite.fi

FRANCE

Thommen Medical France
Le PARK, Bâtiment B, 1 Rue Charles Cordier
77164 Ferrières-en-Brie | France
Tel. +33 1 83 64 06 35
infos@thommenmedical.fr
commande@thommenmedical.fr



GERMANY

Thommen Medical Deutschland GmbH
Am Rathaus 2
79576 Weil am Rhein | Germany
Tel. +49 7621 422 58 30
Fax +49 7621 422 58 41
info@thommenmedical.de

HONG KONG

Shengyuan (Hong Kong) Int. Trade Co. Ltd.
Level 13, 68 Yee Wo Street
Causeway Bay | Hong Kong
Tel. +852 530 876 41

HUNGARY

Mori-Dent Kft.
Huszt utca 9 | 1147 Budapest
Hungary
Tel. +361 220 5443
morident@morident.hu
www.morident.hu

ITALY

Thommen Medical Italia S.r.l.
Head office: Via Goethe, 7 | 39012 Merano (BZ) | Italy
Administrative and operational headquarters: Via
Caduti di Amola, 11/2 | 40132 Bologna | Italy
Tel. +39 051 281 98 15 – 498 76 32
assistenza.it@thommenmedical.com
ordini.it@thommenmedical.com
corsi.it@thommenmedical.com
www.thommenmedical.com

JAPAN

J. Morita Corporation
3-33-18, Tarumi-cho
Suita | Osaka 564-8650 | Japan
Tel. +81 6 6384 6921
Fax +81 6 6384 6746
www.morita.com

JORDAN

Alzynoor for Medical Supplies
Complex No. 243
Barakat Center office 406, JO-Amman 11953 Jordan
Tel. +962 655 39020
alzynoor.medical.jo@gmail.com

KUWAIT

Logident
Yasmin Complex, 1st floor, Office B1
Ibn Khaldoun, St Hawally | Kuwait
Tel. +965 5113 8438
omar.alameddin@logidentco.com

LITHUANIA/LATVIA

LT projects, UAB
Europos pr. 121 | Kaunas | LT-46339 Lithuania
Tel. +370 65 771550
info@fordentist.lt
www.fordentist.lt

NORWAY

Novus Dental AS
Måkeveien 6
1679 Kråkerøy | Norway
post@novusdental.no
www.novusdental.no

OMAN

Al Inshirah Street, Madinat Sultan Qaboos
Building No.185, Way No.1947
P.O. Box 1181, P.C. 112.
Ruwi, Muscat, Sultanate Of Oman
Tel. +968 24602771
sam@almadinagroup.net

POLAND

C.WITT DENTAL Sp. z o. o.
Ul. Granitowa 10
87-100 Toruń | NIP 951-15-08-371 | Poland
Tel. +48 56 623 61 23
biuro@cwittdental.pl
www.cwittdental.pl

QATAR

Orient gate company
Al - Nasr, Area 39, Street 840, Building No: 53
P.O. Box 45393 | Doha Qatar
Mobile +974 50389808
lyaseen@orientgateqa.com

REPUBLIC OF CROATIA

Futura Dental d.o.o.
Ulica grada Vukovara 271 | Chromosov toranj
10 000 Zagreb | Republic of Croatia
Tel. +385 144 668 35
info@futura-dental.hr
www.futura-dental.hr

RUSSIAN FEDERATION

Geosoft Surgery LLC.
Vasnetsova Lane, House 7, Office 206
129090 Moscow | Russian Federation
Tel. +7 495 663 22 11
thommenmedical@geosoft.ru
www.geosoft.ru

SAUDI ARABIA

INNOVATION MEDICAL COMPANY
7324 King Abdulaziz Road
Ar-Rabi District
13315 Riyadh | Kingdom of Saudi Arabia
Tel. +966 50 926 5010
contact@innovation-medical.com

SINGAPORE

FONDACO Pte Ltd
7 Kaki Bukit Road 1, #03-06
Eunos Techno Link
Singapore 415937 | Singapore
Tel. +65 6392 2806
Fax +65 6392 1296
fondaco@fondacosg.com

SPAIN/PORTUGAL

Thommen Medical Ibérica
C/Los quintos n 1
03350 Cox (Alicante) | Spain
Tel. +34 96 536 10 20
Mobile +34 606 99 78 34
info@thommeniberica.com

SWEDEN

Erik Söderberg Group AB
Björnkärsvägen 112
187 42 Täby | Sweden
Tel. +46 70 567 00 67
erik@thommenmedical.se
www.thommenmedical.se

SWITZERLAND

Thommen Medical AG
Neckarsulmstrasse 28
2540 Grenchen | Switzerland
Tel. +41 32 644 30 20
Fax +41 32 644 30 25
info@thommenmedical.ch

TAIWAN

En-Jye International Co., Ltd.
No. 18, Lane 177, Sec 3, Chengde Rd.
Taipei, 103 Taiwan | Taiwan
Tel. +886 2 2585 1669
Fax +886 2 2585 0892
enjye168@gmail.com

TURKEY

Bioport Biyolojik Maddeler A. .S.
Büyükdere cd. Subay evleri 9. Blok D1 Esentepe
Şişli 34394 İstanbul | Turkey
Tel. +90 212 2727577
Fax +90 212 2727628
info@bioport.com.tr
www.bioport.com.tr

UKRAINE

BIG TIME GROUP LTD
Kyivska 5/1A | 46016 Ternopil
Ukraine
Tel. +380 67 54 60 147
btgukraine@gmail.com
bigtimegroup.com.ua

UNITED ARAB EMIRATES

City Pharmacy Co WLL
Taweelah, KIZAD Sector KHIA 9 | Plots 68 &69
P.O.Box 2098, Abu Dhabi | UAE
Tel. +971 507 407 047 or +971 5056 20568
faisal.m@citypharmacy.com
moawia.zaharna@citypharmacy.com

USA/CANADA

Thommen Medical USA L.L.C.
1375 Euclid Avenue | Suite 450
Cleveland OH 44115 | USA
Tel. +1 866 319 9800 (toll free)
Fax +1 216 583 9801
info@thommenmedical.us
orders@thommenmedical.us